

[Manuals.plus](#) /

› [LILTSDRAE](#) /

› LILTSDRAE 21 Cubic Feet Car Rooftop Cargo Carrier Bag Instruction Manual

LILTSDRAE 21 Cubic Feet

LILTSDRAE 21 Cubic Feet Car Rooftop Cargo Carrier Bag Instruction Manual

Model: 21 Cubic Feet

INTRODUCTION

Thank you for choosing the LILTSDRAE 21 Cubic Feet Car Rooftop Cargo Carrier Bag. This manual provides essential information for the safe and effective installation, operation, and maintenance of your cargo carrier. Designed for durability and weather protection, this bag offers significant additional storage for your vehicle, ensuring your belongings remain secure and dry during travel.

Please read these instructions thoroughly before first use and retain them for future reference.

SAFETY GUIDELINES

- **Do not exceed vehicle's maximum roof load capacity.** Consult your vehicle's owner's manual for specific limits.
- Ensure all straps are securely fastened before driving. Regularly check strap tension during long trips.
- Distribute weight evenly inside the cargo bag to maintain vehicle stability. Place heavier items at the bottom and center.
- Avoid overloading the bag. The maximum capacity is 21 cubic feet.
- Drive at reduced speeds, especially in strong winds, during heavy rain, or on uneven terrain, when the cargo bag is installed.
- Be aware of increased vehicle height when the cargo bag is installed, especially when entering garages, car washes, or low-clearance areas.
- This is a soft roof carrier. Do not attach front and rear straps to side bars during installation to prevent tearing.

PACKAGE CONTENTS

Verify that all components are present before installation:

- 1 x LILTSDRAE 21 Cubic Feet Car Rooftop Cargo Carrier Bag
- 1 x Anti-Slip Mat
- 6 x Door Hooks
- 2 x Extra Straps
- 1 x Storage Bag
- 1 x Combination Lock (optional, if included)

INSTALLATION INSTRUCTIONS

The LILTSDRAE cargo carrier is designed for universal fit on vehicles with or without roof racks.

Preparation:

1. Clean the vehicle's roof surface where the cargo bag will be placed.
2. Place the provided anti-slip mat on the vehicle's roof. This helps prevent the bag from shifting and protects your car's paint.
3. Position the empty cargo bag on top of the anti-slip mat.

Method 1: Installation with Roof Racks

If your vehicle has existing roof racks (side rails or crossbars):

1. Load your items into the cargo bag before securing it to the racks.
2. Thread the cargo bag's integrated straps through your vehicle's roof rack crossbars or around the side rails.
3. Fasten the buckles and tighten all straps securely. Ensure the bag is centered and stable.
4. Use the two extra straps provided for additional security, if desired, by wrapping them around the bag and roof racks.

FIT ALL HARD ROOF TOP



**WITHOUT
RACK**



WITHOUT RACK



WITHOUT RACK



WITHOUT RACK



WITHOUT RACK

**WITH
RACK**



Image: The cargo bag is compatible with vehicles both with and without roof racks, demonstrating its versatile fit.

Method 2: Installation without Roof Racks (Using Door Hooks)

If your vehicle does not have roof racks:

1. Load your items into the cargo bag before securing it.
2. Open your vehicle's doors. Carefully pull back the weatherstripping seal around the door frame.
3. Place one of the provided door hooks onto the metal doorframe.

4. Gently pop the weatherstripping seal back into place, ensuring it covers the hook's strap. Close the door.
5. Repeat this process for all 6 door hooks (one for each door, and additional hooks for the front/rear if applicable, ensuring even distribution).
6. Connect the cargo bag's integrated straps to the loops of the door hooks.
7. Tighten all straps evenly and securely. Ensure the bag is centered and stable.

HOW TO INSTALL THE DOOR HOOKS?



Image: Detailed steps for installing the door hooks to secure the cargo bag on vehicles without roof racks.

Installation Video Guide:

Your browser does not support the video tag.

Video: A visual guide demonstrating the installation process of the LILTSDRAE Car Rooftop Cargo Carrier Bag.

OPERATING INSTRUCTIONS

Loading the Cargo Bag:

- Unzip the main compartment.
- Place heavier items at the bottom and center of the bag to maintain a low center of gravity and vehicle stability.
- Distribute weight evenly to prevent shifting during transit.
- Fill the bag to its capacity to minimize flapping and wind noise, but do not overfill.
- Close the zipper completely and ensure the protective double flaps are securely fastened over the zipper for maximum waterproofing.
- If a combination lock is included, use it to secure the zippers.

MORE SECURITY

COME WITH BONUS COMBINATION LOCK



Image: The combination lock provides additional security for your belongings inside the cargo bag.

Driving with the Cargo Bag:

- Before starting your journey, double-check all straps for tightness and security.
- Periodically check the straps and bag stability during long drives, especially after the first few miles.
- Adjust your driving style: reduce speed, especially when cornering, braking, or in windy conditions.
- Be mindful of crosswinds, which can affect vehicle handling.

MAINTENANCE

- **Cleaning:** Clean the cargo bag with mild soap and water. Do not use harsh chemicals or abrasive cleaners. Rinse thoroughly and allow to air dry completely before storage.
- **Storage:** When not in use, fold the cargo bag and store it in the provided storage bag in a cool, dry place away from direct sunlight.
- **Inspection:** Before each use, inspect the bag, straps, buckles, and zippers for any signs of wear, damage, or deterioration. Replace if necessary.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Bag is flapping or making noise.	Straps are not tight enough; bag is underfilled.	Tighten all straps securely. Fill the bag more completely to reduce excess material.
Water leakage inside the bag.	Zipper not fully closed; protective flaps not covering zipper; damage to material.	Ensure zipper is fully closed and double flaps are properly positioned. Inspect for tears or punctures.
Bag shifting on the roof.	Anti-slip mat not used; straps not tight; uneven weight distribution.	Ensure anti-slip mat is in place. Re-tighten all straps. Redistribute cargo weight evenly.
Difficulty closing door with door hooks.	Weatherstripping not properly reseated.	Ensure the weatherstripping is fully and correctly reseated over the hook's strap before closing the door. Do not force the door.

SPECIFICATIONS

- **Brand:** LILTSDRAE
- **Model:** 21 Cubic Feet
- **Capacity:** 21 Cubic Feet
- **Material:** 840D Oxford Fabric
- **Dimensions (L x W x H):** 52" x 40" x 18" (132 cm x 101.6 cm x 45.7 cm)
- **Weight:** Approximately 5.28 kg (11.64 lbs)
- **Water Resistance Level:** Waterproof
- **Mounting Type:** Roof Mount (with or without racks)
- **Shell Type:** Soft
- **Automotive Fit Type:** Universal Fit



21 CUBIC FEET LARGE CAPACITY



6X



4X



2X



SLEEPINGBAG



SLEEPINGBAG



SLEEPINGBAG

Image: Overview of the LILTS DRAE cargo bag, highlighting its dimensions and large capacity.

CUSTOMER SUPPORT

For any questions, concerns, or assistance with your LILTS DRAE Car Rooftop Cargo Carrier Bag, please contact our customer support team. Refer to your purchase documentation for contact details or visit the LILTS DRAE official website.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question