

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [GoveeLife](#) /

› [GoveeLife Water Leak Detector H5059 User Manual](#)

GoveeLife H5059

GoveeLife Water Leak Detector

MODEL: H5059

Brand: GoveeLife

1. INTRODUCTION

This user manual provides comprehensive instructions for the installation, operation, and maintenance of your GoveeLife Water Leak Detector. Please read this manual thoroughly before using the device to ensure proper function and safety. This device is designed to provide early detection of water leaks and floods, helping to protect your property from potential damage.

2. PRODUCT OVERVIEW

The GoveeLife Water Leak Detector (Model H5059) is an essential tool for safeguarding your home against water damage. It features ultra-sensitive detection capabilities and a loud, adjustable alarm to alert you to leaks quickly. The device is built for durability with an IP67 waterproof rating and boasts a long-lasting battery for hassle-free operation.



Figure 2.1: GoveeLife Water Leak Detector (5-Pack).

Key Features:

- **Ultra-Sensitive Detection:** Equipped with two sets of sensor probes for early detection of water in various locations such as basements, kitchens, bathrooms, and near appliances like dishwashers, water heaters, or washing machines.
- **Loud Alarm Sound with Customizable Volume:** Features a 105dB audible alarm to instantly alert you to water threats. Volume settings are adjustable to 4 levels, suitable for different environments.
- **5 Years of Hassle-Free Operation:** Built-in battery designed to last up to 5 years, reducing the need for frequent replacements.
- **IP67 Waterproof & Durable Design:** Constructed to withstand harsh conditions, ensuring reliable performance in damp areas like under sinks, laundry rooms, or near sump pumps.

Detect Drips & Floods in 2 Seconds

From tiny leaks to burst pipes - we catch it all.



*The sensor is only paired with the GoveeLife H5044 gateway

Figure 2.2: The detector's dual sensor probes enable quick detection of both drips and floods.

0-105dB Adjustable Alarm Volume

Roar in the basement, whisper in the bedroom
ajust to your peace



*The sensor is only paired with the GoveeLife H5044 gateway

Figure 2.3: The alarm volume can be adjusted from 0-105dB to suit your environment.


Battery Life Up to 5 Years

Set it, forget it - focus on life, not battery changes

5 in standby mode
years



H5059



others



*The sensor is only paired with the GoveeLife H5044 gateway

Figure 2.4: Enjoy up to 5 years of battery life in standby mode.

IP67 WaterProof

IP67 is more water resistant than IP66



Figure 2.5: The IP67 waterproof design ensures durability and reliability in wet conditions.

Tiny Detector, Total Protection

Slips under sinks, behind washers – fits anywhere water lurks



Figure 2.6: Its compact size allows for placement in various risk zones, including under sinks, near washing machines, and in basements.

3. SETUP

Initial Activation:

1. Remove the protective sticker from the sensor's button.
2. Press and hold the button on the detector for 3 seconds to power it on. A red indicator light will briefly appear.

Placement:

Place the water leak detector in areas prone to water leaks, ensuring the sensor probes on the bottom are in direct contact with the surface. Common locations include:

- Under sinks (kitchen, bathroom)
- Near water heaters
- Behind or next to washing machines and dishwashers
- In basements or utility rooms
- Near sump pumps

App Integration (Optional, Requires Gateway):

The GoveeLife Water Leak Detector (H5059) cannot connect directly to the GoveeLife app. To enable remote monitoring and notifications via your smartphone, a GoveeLife H5044 gateway is required. This gateway is not included in the H5059 package and must be purchased separately (e.g., as part of kit "BB0DQLDBXWF"). The H5059 is not compatible with H5040/H5043 gateways.

Video 3.1: This video provides an overview of the GoveeLife Water Leak Detector and its features, including its sensitivity and alarm.

4. OPERATING THE DEVICE

Water Detection and Alarm:

When the sensor probes on the bottom of the device detect water, the alarm will sound immediately at 105dB. The device is highly sensitive and can detect even a tiny amount of water. If the top contacts also come into contact with water, the alarm will also activate.

Alarm Volume Adjustment:

To adjust the alarm volume, double-press the button on the device. There are 4 adjustable volume settings to choose from.

Silencing the Alarm:

The alarm will stop once the water is no longer detected by the sensor probes. You can also press the button on the device to temporarily silence the alarm. If connected to a GoveeLife H5044 gateway, you may also be able to silence the alarm via the app.

5. MAINTENANCE

Battery Replacement:

The GoveeLife Water Leak Detector features a built-in battery designed to last up to 5 years under normal standby conditions. When the battery is low, the device will indicate this (e.g., via a low battery alert in the app if connected to a gateway). To replace the battery:

1. Carefully remove the waterproof silicone pad from the bottom of the device using a small screwdriver.
2. Unscrew the screws on the back cover and gently pry it open.
3. Remove the old AAA batteries and insert new ones, ensuring correct polarity (positive and negative sides).
4. Reattach the back cover and tighten the screws.
5. Reinsert the waterproof silicone pad into its original position.

Video 5.1: This video demonstrates the steps to replace the battery in the GoveeLife Water Leak Detector.

Cleaning:

Wipe the device with a dry, soft cloth. Do not use abrasive cleaners or immerse the device in water (beyond what is expected for leak detection) as this may damage the internal components.

6. TROUBLESHOOTING

Common Issues and Solutions:

- **Alarm not sounding:**
 - Ensure the device is powered on (press and hold the button for 3 seconds).
 - Check if the sensor probes are in direct contact with the water.
 - Verify battery level and replace if necessary.
- **False alarms:**
 - Ensure the device is placed on a dry surface.
 - Avoid placing the detector in areas with condensation or high humidity that might trigger the sensors without an actual leak. For example, if placing near cold pipes, consider using a drip pan and positioning the sensor slightly beside the pan to avoid false alarms from condensation.
- **No app notifications (if using gateway):**
 - Confirm you are using a GoveeLife H5044 gateway, as other models (H5040/H5043) are not compatible.
 - Ensure the gateway is properly set up and connected to your Wi-Fi network.
 - Check app settings for notifications and ensure they are enabled for the specific sensor.

7. SPECIFICATIONS

Specification	Detail
Brand	GoveeLife
Model Number	H5059
Power Source	Battery Powered
Battery Type	Alkaline (10 AAA batteries included for 5-pack)
Voltage	15 Volts (DC)
Noise Level	105 dB
Control Method	App (via H5044 Gateway)
Maximum Range	550 Meters (Sensor Technology: 915Mhz)
Mounting Type	Floor Placement
Product Dimensions	3.66"L x 2.63"W x 1.49"H

Item Weight	1.01 pounds (for 5-pack)
UPC	810127738607

8. WARRANTY AND SUPPORT

For warranty information and technical support, please refer to the official GoveeLife website or contact their customer service directly. Keep your purchase receipt for warranty claims.

GoveeLife Official Website: www.govee.com