



Manuals.plus /

› Evermagin /

› Evermagin 67-inch Fluted Sideboard Cabinet Instruction Manual

Evermagin 67-inch Fluted Sideboard

Evermagin 67-inch Fluted Sideboard Cabinet Instruction Manual

MODEL: **SIDEBOARD-67**WALNUT

Introduction

This manual provides detailed instructions for the assembly, operation, and maintenance of your Evermagin 67-inch Fluted Sideboard Cabinet. Please read all instructions carefully before beginning assembly and retain this manual for future reference.

The Evermagin Fluted Sideboard is designed to offer elegant storage and a modern aesthetic to your dining room, kitchen, or living space. Its durable construction and thoughtful design ensure long-lasting use.

Safety Information

- Always assemble the unit on a soft, clean surface to prevent scratches.
- Ensure all screws and fasteners are securely tightened before use.
- Do not overload shelves. Refer to specifications for weight limits.
- Use the included anti-tipping hardware to secure the cabinet to a wall, especially in households with children or pets, to prevent accidental tipping.
- Keep small parts away from children during assembly.

Package Contents

Before assembly, verify that all components listed below are present and undamaged. If any parts are missing or damaged, please contact customer support.

- All necessary wood panels (top, bottom, side, back, shelves, doors)
- Hardware kit (screws, dowels, hinges, handles, anti-tipping kit)
- Assembly tools (typically an Allen wrench, screwdriver may be needed)
- Instruction manual

Assembly Instructions

Assembly typically requires two people and can take approximately 1.5 to 3.5 hours. Follow the step-by-step diagrams provided in your physical manual. Ensure you have ample space to lay out all components.

- 1. Unpack and Organize:** Carefully unpack all components and lay them out on a soft, clean surface. Group similar parts and hardware together. Note that pieces may be numbered, and assembly might start with higher-numbered parts.
- 2. Assemble the Base Frame:** Connect the bottom panel to the side panels using the provided dowels and screws. Ensure a snug fit.
- 3. Install Interior Shelves:** Insert the fixed interior shelves into their designated slots.
- 4. Attach the Top Panel:** Secure the top panel to the assembled frame using the appropriate hardware.
- 5. Install Back Panels:** Fasten the back panels to the rear of the cabinet.
- 6. Attach Doors and Handles:** Install the hinges onto the doors and then attach the doors to the cabinet. Secure the handles to the doors.
- 7. Adjust Door Alignment:** The door hinges may require adjustment to ensure proper alignment and smooth closing. Refer to the 'Troubleshooting' section for detailed hinge adjustment instructions.
- 8. Secure with Anti-Tipping Kit:** Attach the anti-tipping hardware to the back of the cabinet and to a wall stud, following the instructions provided with the kit.



Image: Fully assembled Evermagin 67-inch Fluted Sideboard Cabinet in a living room setting.

Product Size



Image: Product dimensions (66.92" W x 31.5" H x 15.74" D) and weight capacity (350 lbs).

Video: Installation and hinge adjustment guide for fluted panels, demonstrating how to correct door alignment and gaps.

Operation

The Evermagin Fluted Sideboard features six doors that open to reveal spacious storage compartments. Each compartment includes a fixed shelf, providing organized storage for various items.

- To open a door, gently pull on the integrated handle.
- To close a door, push it until it softly closes. The soft-close hinges prevent slamming.
- Utilize the six compartments for storing dinnerware, gadgets, books, media, or other essentials.



Image: Interior view of the sideboard, showcasing the six storage compartments with fixed shelves.

Video: Demonstrates the versatility of the sideboard, showing its use as both a storage unit and a TV stand.

Maintenance

- **Cleaning:** Wipe surfaces with a soft, damp cloth. Avoid harsh chemicals or abrasive cleaners, which can damage the finish.
- **Spills:** Clean spills immediately to prevent staining.
- **Protection:** Use coasters or placemats under hot or wet items to protect the top surface.
- **Inspection:** Periodically check all fasteners and tighten if necessary to maintain stability.

Troubleshooting

- **Uneven Doors or Gaps:**

The hinges on your cabinet doors are adjustable. There are typically three adjustment screws on each hinge:

- **Front Screw:** Adjusts the gap between the door and the side panel. Rotate clockwise to reduce the gap, counter-clockwise to increase it.
- **Rear Screw:** Adjusts the flatness of the door relative to the cabinet surface. Loosen, adjust the door

position, and re-tighten.

- **Vertical Adjustment Screws:** Loosen the screws that fix the two hinges to the cabinet. Adjust the door up or down as needed, then re-tighten the screws.
- **Doors Not Closing Smoothly:** Check for any obstructions within the cabinet. Ensure hinges are clean and lubricated if necessary. Adjust hinges as described above.
- **Wobbling or Instability:** Ensure the cabinet is placed on a level surface. Check and tighten all assembly screws. If the issue persists, verify that the anti-tipping hardware is securely installed.

Video: Detailed instructions on how to adjust cabinet door hinges to correct gaps, flatness, and vertical alignment.

Specifications

Feature	Detail
Brand	Evermagin
Model Name	Fluted Sideboard
Item Model Number	Sideboard-67walnut
Color	Walnut
Product Dimensions	15.74"D x 66.92"W x 31.5"H
Item Weight	107 Pounds
Material	Engineered Wood
Number of Doors	6
Number of Compartments	6
Number of Shelves	3 (fixed)
Special Feature	Anti-Tipping
Assembly Required	Yes
Installation Type	Freestanding

Warranty and Support

This product is manufactured by Evermagin. For any inquiries regarding your product, including assembly assistance, missing parts, or warranty claims, please contact Evermagin Direct customer support.

The product is returnable until January 31, 2026, as per the retailer's policy. Protection plans are available for purchase separately to extend coverage beyond the standard return period.