

GarveeTech One-Piece Elongated Dual Flush Toilet User Manual

Model: p0ItldkTNt5ZIEMFpXqu_ArcS | Brand: GarveeTech

[Safety](#)[Contents](#)[Specifications](#)[Installation](#)[Operation](#)[Maintenance](#)[Troubleshooting](#)[Warranty](#)

1. IMPORTANT SAFETY INFORMATION

Please read this entire manual carefully before installation and use. Failure to follow these instructions could result in property damage, personal injury, or product malfunction.

- Always wear appropriate safety equipment, including safety glasses and gloves, during installation.
- The toilet is heavy. Two people are required to safely unpack and move the product to avoid personal injuries.
- Inspect the toilet for any damage that may have occurred during transit before installation.
- Ensure all plumbing and building codes in your state and local requirements are observed.
- Do not overtighten bolts and nuts during installation to prevent damage to the ceramic.

2. PACKAGE CONTENTS

Verify that all components are present before beginning installation.



Image: GarveeTech One-Piece Toilet with its components, including chrome dual push-button, mounting hardware, toilet tank lid, soft-close toilet seat, toilet seat bolt kit, installation instructions, ceramic toilet material, and PP seat cover material.

- One-Piece Toilet Unit

- Soft-Close Toilet Seat
- Toilet Tank Lid
- Mounting Hardware (bolts, washers, nuts)
- Wax Ring Gasket
- Installation Instructions (this manual)

3. PRODUCT SPECIFICATIONS



Image: Detailed dimensions of the GarveeTech One-Piece Toilet, showing height, width, depth, and seat height measurements.

Model Number	p0ItldkTNt5ZlEMFpXqu_ArcS
Brand	GarveeTech
Color	White (D-Shaped Cover, Top Double Row, 3/4.8)
Product Dimensions (D x W x H)	31.69" x 18.9" x 29.57"
Item Weight	108.5 Pounds
Installation Type	Floor Mounted
Shape	D-Shape

Seat Material Type	Polypropylene
Flush Type	Dual Flush (0.8/1.28 GPF)

4. INSTALLATION GUIDE

This section provides step-by-step instructions for installing your GarveeTech One-Piece Toilet. Professional installation is recommended.

4.1 Preparing for Installation

- Ensure the water supply to the bathroom is turned off.
- Remove the old toilet if applicable and clean the flange area thoroughly.
- Gather all necessary tools: wrench, screwdriver, wax ring gasket, mounting bolt kit.

4.2 Toilet Installation Steps

1. **Install Mounting Bolts:** Lock the mounting bolts into position on the floor flange.
2. **Apply Wax Ring Gasket:** Apply the wax ring gasket evenly around the rear of the trapway on the bottom of the toilet.
3. **Position the Toilet:** Carefully position the toilet onto the floor flange, aligning the bolts with the holes in the toilet base. Gently press down to create a seal with the wax ring.
4. **Secure the Toilet:** Install the washers and nuts onto the bolts. Tighten the nuts evenly until the toilet is secure, but do not overtighten to avoid cracking the ceramic.
5. **Connect Water Supply:** Connect the supply line to the fill valve at the back of the toilet. Ensure a tight connection to prevent leaks. (Note: Water supply line is not included).
6. **Install Side Cover Set:** Assemble the side cover caps and attach them to the toilet to conceal the mounting bolts.

Video: Eridanus One Piece Toilet Installation Guide. This video demonstrates the steps for installing the toilet, including securing the mounting bolts, applying the wax ring, positioning the toilet, and connecting the water supply.

4.3 Toilet Seat Installation Steps

1. **Attach Seat Cover Hinges:** Attach the seat cover hinges to your toilet. Twist the bolt nuts gently. Do not overtighten at this stage, as you may need to adjust them later.
2. **Snap Toilet Seat:** Snap the new toilet seat over your toilet, aligning the pre-drilled holes on the seat with the hinges.
3. **Adjust and Tighten:** Adjust the nuts as needed to tighten the seat. Once satisfied with the seat's position, you can remove the seat to place the hinge cover on the hinge, then snap the toilet seat over your toilet again so everything is held firmly in place.

Video: Toilet Seat Installation Guide. This video demonstrates the process of attaching the seat cover hinges, snapping the toilet seat into place, and making final adjustments for a secure fit.

5. OPERATING INSTRUCTIONS

Your GarveeTech One-Piece Toilet features a dual-flush system designed for water efficiency and powerful cleaning.

5.1 Dual Flush Mechanism

- **Partial Flush (0.8 GPF):** Press the smaller button on the top of the tank lid for liquid waste. This conserves water.

- **Full Flush (1.28 GPF):** Press the larger button on the top of the tank lid for solid waste. This provides a powerful flush for effective waste removal.



Image: Visual representation of the powerful flushing system, demonstrating 360-degree cleaning action and improved water spot coverage within the toilet bowl.

Video: Toilet demonstration video. This short video demonstrates the flushing power of the toilet, showing how it effectively clears the bowl.

5.2 Soft-Closing Seat

The toilet is equipped with a soft-closing seat to prevent slamming and reduce noise. Gently push the seat down, and it will close slowly and quietly on its own.



Elongated Toilet Seat

offers enhanced comfort for users, ensuring a more pleasant and ergonomic experience during use.

Image: A visual demonstration of the soft-closing toilet seat, highlighting its quiet operation and noise reduction feature.

6. MAINTENANCE AND CLEANING

Proper maintenance ensures the longevity and hygiene of your toilet.

6.1 Cleaning the Toilet

- Use a soft cloth or sponge with a mild, non-abrasive cleaner to clean the exterior and interior surfaces.
- Avoid using harsh chemicals, abrasive pads, or strong acids, as these can damage the ceramic finish and internal components.
- The seamless one-piece design minimizes crevices, making cleaning easier.

Leaves no place for dirt to hide



Conventional



Our design

Image: A side-by-side comparison illustrating a conventional toilet rim with hidden areas for dirt accumulation versus the GarveeTech toilet's rimless design, which prevents dirt from hiding and simplifies cleaning.

6.2 Seat Maintenance

- Regularly clean the toilet seat with mild soap and water.
- Do not use strong chemical cleaners on the seat, as they may cause discoloration or damage to the polypropylene material.
- The soft-close hinges can be gently wiped clean.

7. TROUBLESHOOTING

This section addresses common issues you might encounter with your toilet.

Problem	Possible Cause	Solution
Toilet does not flush properly or has a weak flush.	Low water level in tank, clogged trapway, or partially closed water supply valve.	Check water level in tank and adjust if necessary. Inspect trapway for obstructions. Ensure water supply valve is fully open.
Toilet leaks at the base.	Loose mounting bolts, improperly seated wax ring, or cracked toilet base.	Gently tighten mounting bolts. If leak persists, the wax ring may need to be replaced. Inspect for cracks; if found, contact customer support.

Toilet runs continuously.	Flapper not sealing correctly, fill valve malfunction, or float ball out of adjustment.	Check flapper for proper seating and wear. Adjust float ball to ensure it's not too high. Inspect fill valve for issues.
Toilet seat is loose.	Loose seat mounting bolts.	Tighten the seat mounting bolts. Refer to Section 4.3 for seat installation.

8. WARRANTY AND CUSTOMER SUPPORT

GarveeTech stands behind the quality of its products. This toilet comes with a standard manufacturer's warranty covering defects in materials and workmanship under normal use.

For specific warranty details, claims, or technical assistance, please contact GarveeTech customer support. Have your model number (p0ItldkTNt5ZIEMFpXqu_ArcS) and purchase information ready when contacting support.

You can typically find contact information on the GarveeTech website or through your retailer.