ARKSEN 005-TH-5RR54

ARKSEN 54" x 39" x 5" Roof Rack Cargo Basket Instruction Manual

Model: 005-TH-5RR54

Introduction

This manual provides instructions for the proper assembly, installation, operation, and maintenance of your ARKSEN 54" x 39" x 5" Roof Rack Cargo Basket. Please read this manual thoroughly before use to ensure safe and efficient operation.



Image: The ARKSEN 54" x 39" x 5" Roof Rack Cargo Basket, showcasing its design and size.

Safety Information

- Do not exceed the maximum load capacity of 150 lbs.
- Ensure all mounting hardware is securely tightened before each use.
- Distribute cargo evenly across the basket to maintain vehicle stability.
- Regularly inspect the roof rack for any signs of wear, damage, or loose components.
- Crossbars are required for installation and are not included with this product. Ensure your vehicle's crossbars are compatible.

Setup and Installation

The ARKSEN Roof Rack Cargo Basket is designed for easy installation using adjustable U-bolts. No drilling is required.

Compatibility Requirements:

- Compatible with most SUVs, trucks, and vehicles equipped with crossbars.
- Crossbars must be up to 4.65" wide and 1.38" thick.
- Vehicle crossbar spacing must be greater than 29.7".

Installation Steps:

1. Assemble the roof rack basket components according to the included hardware instructions.
2. Position the assembled cargo basket onto your vehicle's crossbars.
3. Secure the basket to the crossbars using the adjustable U-bolts. Ensure the U-bolts are positioned correctly around the crossbars and tightened firmly to prevent movement.
4. Verify that all connections are secure and the basket is stable before loading any cargo or driving.



Image: Illustration of the universal vehicle fit, showing the required crossbar spacing for U-bolt installation.



Image: Depiction of the roof rack with extension capability, illustrating 34", 44", and 54" size configurations.

Operation

The ARKSEN Roof Rack Cargo Basket provides additional storage for your vehicle, ideal for luggage, camping gear, and other bulky items.

Loading Cargo:

- Ensure the total weight of the cargo does not exceed the 150 lbs capacity.
- Distribute weight evenly within the basket to maintain vehicle balance and stability.
- Secure all cargo using appropriate tie-downs, straps, or cargo nets to prevent shifting or falling during transit.
- The integrated wind fairing helps reduce wind resistance and noise for a smoother travel experience.



Image: The ARKSEN roof rack with a cargo bag securely loaded, demonstrating its use for carrying gear.



Image: Visual representation of the aerodynamic design, highlighting features that reduce noise and improve fuel efficiency.

Maintenance

To ensure the longevity and optimal performance of your ARKSEN Roof Rack Cargo Basket, follow these maintenance guidelines:

- **Cleaning:** Clean the roof rack regularly with mild soap and water to remove dirt, road grime, and debris. Rinse thoroughly and dry completely to prevent water spots and corrosion.
- **Inspection:** Periodically inspect all components, including the steel frame, welds, U-bolts, and mounting hardware, for any signs of damage, cracks, rust, or loose connections. Tighten any loose fasteners.
- **Corrosion Protection:** The black powder-coated finish provides corrosion resistance. To maintain this protection and for best longevity, store the roof rack indoors when not in use, especially during harsh weather conditions.



Image: Comparison illustrating the durable, galvanized, and powder-coated steel material with 1.0 mm thickness used in the ARKSEN roof rack, emphasizing its waterproof, rustproof, and anti-corrosion properties.

Troubleshooting

No specific troubleshooting steps are provided in this manual. For issues not covered here, please refer to the support section.

Common Considerations:

- **Noise:** Ensure all components are securely fastened. An integrated wind fairing is designed to minimize wind noise.
- **Stability:** Verify that the cargo is evenly distributed and properly secured. Check U-bolt tightness.
- **Fit:** Double-check that your vehicle's crossbars meet the specified dimensions and spacing requirements.

Specifications

Feature	Detail
Brand	ARKSEN
Model Number	005-TH-5RR54
Item Dimensions (L x W x H)	54 x 39 x 5 inches
Item Weight	27.5 Pounds
Load Capacity	150 Pounds
Material	Steel
Color	Black
Mounting Type	U-Bolt
Vehicle Service Type	Car, Truck, Vehicle Rooftop with Bars (Universal Fit)
Included Components	54" x 39" x 5" Roof Rack
Crossbar Compatibility	Up to 4.65" wide and 1.38" thick. Spacing > 29.7".



Image: Detailed diagram showing the 54" length, 39" width, and 5" height of the roof rack, along with its 150 lbs support capacity and anti-rust coated steel material.

Warranty Information

This ARKSEN product comes with a**1-year warranty** from the date of purchase. This warranty covers manufacturing defects but excludes misuse or improper installation. Please retain your proof of purchase for warranty claims.

Customer Support

For further assistance, technical support, or warranty inquiries, please contact ARKSEN customer service. Specific contact details are not provided in this manual. Refer to the product packaging or the retailer's website for current support information.

© 2026 ARKSEN. All rights reserved.