

manuals.plus /

› [Arbilato](#) /

› [Arbilato Samsung Galaxy A06 5G LCD Screen Replacement with Frame Instruction Manual](#)

Arbilato Samsung A06 5G LCD display

Arbilato Samsung Galaxy A06 5G LCD Screen Replacement with Frame Instruction Manual

Model: SM-A066B, SM-A066B/DS

1. INTRODUCTION

This manual provides essential instructions for the installation and proper use of your Arbilato LCD Screen Replacement for the Samsung Galaxy A06 5G. This product is designed to replace damaged or malfunctioning screens, restoring your device's display functionality.

2. PRODUCT COMPATIBILITY AND VERIFICATION

Before proceeding with installation, it is crucial to verify that this screen replacement is compatible with your specific device model. This product is compatible with the **Samsung Galaxy A06 5G**, specifically models **SM-A066B** and **SM-A066B/DS**.

Incorrect model identification may lead to incompatibility and potential damage to your device or the replacement part.



FOR samsung A06 5G

SM-A066B, SM-A066B/DS

Resolution : 720*1600 pixel

Size : 6.7 inches

Pixel density : 262 ppi

Color :

■ Black



Figure 1: Product compatibility details and specifications.

3. PACKAGE CONTENTS

Please ensure all items listed below are present in your package:

- 1x Arbilato LCD Screen Replacement with Frame for Samsung Galaxy A06 5G (Black)
- 1x Set of Repair Tools (screwdrivers, prying tools, suction cup)
- 1x Waterproof Sticker
- 1x Disassembly Tool Card



Figure 2: Contents of the package, including the screen assembly and repair tools.

4. SETUP AND PREPARATION

1. **Gather Tools:** Ensure you have all the necessary tools, including those provided in the package.
2. **Power Off Device:** Completely power off your Samsung Galaxy A06 5G before beginning any disassembly.
3. **Disconnect Battery:** Unplug the battery connector and remove the battery if possible to prevent short circuits during the repair process.
4. **Clear Old Adhesive:** Before installing the new LCD, carefully remove all old adhesive residue from the phone's frame. Residual adhesive can affect the proper seating and adhesion of the new screen.
5. **Inspect Phone Frame:** If your phone's frame is bent or damaged, it is recommended to replace the frame before installing the new screen. A distorted frame can put undue stress on the new screen, potentially leading to cracks or damage.
6. **Static Precautions:** Work in a clean, static-free environment. Consider using an anti-static wrist strap to prevent electrostatic discharge (ESD) damage to sensitive electronic components.

5. INSTALLATION (OPERATING) INSTRUCTIONS

Replacing a phone screen requires precision and specific technical skills. It is highly recommended to seek professional assistance or refer to detailed video guides before attempting the installation.

- **Professional Installation Recommended:** We advise finding a qualified technician to perform the replacement to avoid any damage during the process.
- **Online Resources:** For visual guidance, search for "Samsung A06 5G LCD With Frame replacement" on video platforms like YouTube. These videos often provide step-by-step instructions.

Key Considerations for Installation:

- **Screen with Frame vs. Screen Only:** This product includes the frame, which can simplify installation for some users, especially those new to screen replacements. A screen with a frame typically involves less adhesive work and frame transfer.

WHAT IS THE DIFFERENCE BETWEEN WITH AND WITHOUT A FRAME?



Inner Screen+Outer Screen+Bezel

Difficulty of installation: ★ ☆ ☆ ☆ ☆

- Recommended for newbies
- You can change the color of the phone's bezel
- You can change the color of the phone's bezel
- Avoid over-tightening which may cause the screen to explode



Inner Screen + Outer Screen

Easy to install: ★ ★ ☆ ☆ ☆

- Recommended for experienced buyers
- Needs to be glued
- Easily damaged
- Requires patience and care

Figure 3: Comparison of screen replacement types and their installation considerations.

- **Flex Cables:** Handle the flex cables (LCM and FPC) with extreme care. Bending or tearing them can render the screen inoperable.

SOLVE VARIOUS SCREEN PROBLEMS




Figure 4: Detail of the flex cables on the screen assembly.

- **Testing:** Before fully adhering the new screen, connect the flex cables and test the display and touch functionality. Ensure there are no dead pixels, display anomalies, or touch response issues.



Figure 5: Example of a screen undergoing testing for functionality.

6. TROUBLESHOOTING

If you encounter issues after installation, consider the following common problems and solutions:

Problem	Possible Cause	Solution
Screen does not turn on / Black screen	Loose flex cable connection, battery not connected, damaged screen during installation.	Recheck all flex cable connections. Ensure the battery is properly connected. If the issue persists, the screen may be faulty or damaged.
Touch not responding / Ghost touches	Flex cable issue, static electricity, faulty digitizer.	Ensure flex cables are securely seated. Power cycle the device. If the problem continues, the digitizer may be defective.
Display issues (lines, discoloration, dead pixels)	Damaged LCD, flex cable issue, pressure on the screen.	Inspect the screen for physical damage. Recheck flex cable connections. Ensure the screen is not under excessive pressure from the phone's frame.

HIGH DEFINITION TRANSPARENCY IMAGE QUALITY



No dark spots/highlights/chromatic aberration Sent after strict inspection of the real machine



Figure 6: Examples of common screen issues that this replacement part aims to resolve.

If troubleshooting steps do not resolve the issue, please contact customer support for further assistance.

7. MAINTENANCE

To ensure the longevity and optimal performance of your new screen, follow these maintenance guidelines:

- **Screen Protection:** Consider using a screen protector and a protective case to guard against scratches and impacts.
- **Cleaning:** Clean the screen with a soft, lint-free cloth, preferably microfiber. Avoid harsh chemicals or abrasive materials.
- **Avoid Pressure:** Do not apply excessive pressure to the screen, as this can damage the LCD panel.
- **Temperature Extremes:** Avoid exposing your device to extreme temperatures, which can affect screen performance and lifespan.

8. SPECIFICATIONS

Feature	Detail
Compatibility	Samsung Galaxy A06 5G (SM-A066B, SM-A066B/DS)

Feature	Detail
Screen Size	6.7 inches
Resolution	720 x 1600 pixels
Pixel Density	262 ppi
Color	Black
Fingerprint Function	Supported (with frame)
Item Weight	6 ounces
Manufacturer	Arbilato

9. WARRANTY AND SUPPORT

Arbilato is committed to customer satisfaction. If you encounter any issues with your Galaxy A06 5G screen replacement after receiving it, please contact our customer support team.

Upon learning the specific situation, we will work to resolve the problem and provide suitable and effective solutions. Your purchase from our store is backed by our after-sales guarantee.

For support, please refer to the contact information provided with your purchase or on the Arbilato official website.

© 2025 Arbilato. All rights reserved.

This manual is for informational purposes only. Arbilato is not responsible for any damage caused by improper installation.