BlessReach WB-2105

BlessReach Knee Scooter Walker WB-2105 Instruction Manual

Introduction

This manual provides essential information for the safe and effective use of your BlessReach Knee Scooter Walker, model WB-2105. Please read all instructions carefully before assembly and operation to ensure proper function and user safety. This knee scooter is designed as a mobility aid for individuals recovering from foot, ankle, or lower leg injuries, or for below-the-knee amputees, offering an alternative to traditional crutches.

Key features include a sturdy metal frame, an ergonomic comfortable knee pad, 8-inch wheels suitable for various terrains, a sensitive dual handbrake system, and height adjustability for users between 4'6" and 6'6". It has a maximum load capacity of 300 lbs and features a foldable design for easy transport and storage.

Product Components and Dimensions

Familiarize yourself with the various parts of your BlessReach Knee Scooter Walker. The following image illustrates the key dimensions and components.



Image: Overview of the BlessReach Knee Scooter Walker, showing its dimensions including a maximum load capacity of 300 lbs and adjustable handle and seat height for users between 4'6" and 6'6".

The knee scooter features an ergonomic design with a comfortable, high-resilience, breathable memory foam knee pad and a non-slip handle with a one-touch parking function.



Image: Close-up of the ergonomic non-slip handle with one-touch parking function and the breathable memory foam knee pad.

The scooter is equipped with customized shock absorbers for high-efficiency vibration damping and noise reduction, supporting up to 300 lbs.



Image: Detail of the customized shock absorbers, highlighting their vibration damping, noise reduction, and 300 lbs weight support capabilities.

Setup and Assembly

Follow these steps to assemble your BlessReach Knee Scooter Walker. Ensure all parts are present and undamaged before beginning assembly.

1. **Install the Front Wheels:** Securely attach the front wheels to the main frame. Ensure all screws are tightened before moving the wrench.

   Your browser does not support the video tag.

   Video: Demonstrates the correct procedure for installing the front wheel crossbar buckle, emphasizing the importance of tightening screws.

2. **General Assembly:** For a comprehensive assembly guide, refer to the detailed installation video provided by the manufacturer.

Your browser does not support the video tag.

Video: A complete installation guide for the BlessReach Knee Scooter Walker model 2105, showing step-by-step assembly.

Operating Instructions

Adjusting Handle and Knee Pad Height

The handle and knee pad heights are adjustable to suit users between 4'6" and 6'6". Ensure the height is set so your knee is comfortable and your hands can easily reach the handlebars and brakes.

Braking System

The knee scooter is equipped with dual handbrakes for safe slowing and stopping. To engage the parking brake, push down the brake levers until they lock into place. Always ensure the brakes are functioning correctly before use.

Your browser does not support the video tag.

Video: Instructions on how to adjust the brake tension for optimal performance and safety.

Folding and Unfolding

For easy transport and storage, the knee scooter can be folded. To fold, open the steering lock, push it to the left, and fold down the knee walker. To unfold, reverse this process, ensuring all locking mechanisms are securely engaged before use.



Image: The BlessReach Knee Scooter in its folded configuration, demonstrating its compact size for transport in a vehicle.

Using the Detachable Bag

The knee scooter includes a detachable canvas bag for personal belongings. This bag features a double-layer structure for durability and ease of use.

Terrain Use

The 8-inch all-terrain, non-slip tires are designed for various surfaces, including gravel, dirt, and sand roads, providing silent vibration damping and durability.



Image: Close-up of the 8-inch all-terrain, non-slip tire, illustrating its suitability for various surfaces like gravel, dirt, and sand.

Maintenance

Regular maintenance ensures the longevity and safe operation of your knee scooter.

- **Brake Inspection:** Periodically check the brake cables and levers for wear and proper function. Adjust brake tension as needed (refer to the brake adjustment video in the Operating Instructions section).
- **Wheel Inspection:** Inspect the 8-inch wheels for wear, damage, or debris. Ensure they rotate freely.
- **Fastener Check:** Regularly check all screws, bolts, and quick-release mechanisms to ensure they are tight and secure. Loose fasteners can affect stability and safety.
- **Cleaning:** Clean the frame and knee pad with a damp cloth and mild soap. Avoid abrasive cleaners.
- **Storage:** When not in use, store the knee scooter in a dry, protected area. The foldable design allows for compact storage.

Troubleshooting

If you encounter issues with your BlessReach Knee Scooter Walker, consider the following common solutions:

- **Brakes not holding securely:**
  - Check brake cable tension. Adjust as shown in the "Precautions for adjusting brake tightness" video.
  - Ensure the parking brake levers are fully depressed and locked. If the lock mechanism feels loose, inspect for wear or damage.
- **Knee pad wobbles or rotates:**
  - Verify that the knee pad post is securely inserted and tightened.
  - Ensure all associated fasteners are tight.
- **Difficulty steering or uneven movement:**
  - Check that all wheels are properly installed and free of debris.
  - Ensure the steering column is securely fastened and not loose.
- **General instability:**
  - Confirm that all assembly steps were followed correctly and all components are securely tightened.
  - Ensure the knee scooter is used on appropriate, relatively even surfaces.

Specifications

Feature	Detail
Product Dimensions	30 x 17 x 40 inches
Item Weight	22.05 Pounds (10 Kilograms)
Maximum Load Capacity	300 Pounds
Adjustable Height Range (User)	4'6" - 6'6"
Wheel Size	8-inch (front and rear)
Material Type	Carbon Steel
Brake Type	Dual Handbrake with Parking Function
Foldable	Yes
Model Name	WB-2105
Color	Black

*Note on Height: The product description states "Height adjustable suits for people: 4.6\"-6.6\"". The specifications for "Minimum Height" and "Maximum Height" (4.6 Inches and 6.6 Inches) likely refer to the adjustable range of a specific component, such as the knee pad or handle, rather than the overall user height. For user height compatibility, please refer to the product description's stated range of 4'6" to 6'6".

Warranty and Support

For warranty information, product support, or to purchase replacement parts, please contact BlessReach customer

service. Refer to the contact information provided with your product packaging or visit the official BlessReach website.
Manufacturer: BlessReach
Brand: BlessReach

© 2026 BlessReach. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question