

[Manuals.plus](#) /

> [GOFEI](#) /

> GOFEI Modern 30 Inch Floating Bathroom Vanity with Sink Instruction Manual

GOFEI SY410311Y-US3261

GOFEI Modern 30 Inch Floating Bathroom Vanity with Sink

MODEL: SY410311Y-US3261

Introduction

This manual provides detailed instructions for the installation, operation, and maintenance of your GOFEI Modern 30 Inch Floating Bathroom Vanity with Sink. Please read all instructions carefully before assembly and use to ensure proper function and safety.

The GOFEI floating vanity is designed to enhance your bathroom with its contemporary style and practical storage solutions. It features a wall-mounted design, four soft-glide drawers, a sliding door cabinet, and a durable ceramic sink with a waterproof finish.

Safety Information

- Always use proper safety gear, including eye protection and gloves, during installation.
- Ensure the wall structure is capable of supporting the weight of the vanity and its contents. Consult a professional if unsure.
- Exercise caution when handling the ceramic sink to prevent chipping or breakage.
- Be mindful of moving parts, such as drawers and the sliding door, to prevent pinching.
- Do not submerge the vanity in water. Avoid prolonged exposure to excessive moisture.
- Keep small parts and hardware out of reach of children.

Package Contents

Verify that all components are present before beginning assembly. If any parts are missing or damaged, contact customer support.

- Floating Vanity Cabinet (Engineered Wood)
- Ceramic Sink Top

- Drawer Slides and Hardware
- Mounting Hardware for Wall Installation
- Assembly Instructions



Image 1: Overview of the GOFEI Modern 30 Inch Floating Bathroom Vanity with Sink, showing its wall-mounted design and integrated ceramic top.

Setup and Installation

Installation requires basic tools and adherence to local plumbing codes. It is recommended to have two people for installation.

Tools Required (Not Included):

- Drill
- Level
- Measuring Tape
- Stud Finder

- Pencil
- Adjustable Wrench
- Screwdrivers (Phillips and Flathead)
- Caulk Gun and Silicone Sealant

Pre-Installation Steps:

1. Unpack all components and verify against the package contents list.
2. Inspect all parts for any damage. Do not proceed with installation if parts are damaged.
3. Turn off the main water supply to the installation area.
4. Clear the installation area and ensure adequate working space.

Mounting the Vanity Cabinet:

1. Determine the desired mounting height. The vanity measures 30"W x 18"D x 20.5"H.
2. Use a stud finder to locate wall studs. Mark the stud locations on the wall.
3. Hold the vanity cabinet against the wall at the desired height and use a level to ensure it is straight. Mark the mounting hole locations on the wall.
4. Drill pilot holes at the marked locations. Ensure the holes are appropriate for the provided mounting hardware.
5. Secure the mounting brackets (if separate) or the vanity directly to the wall studs using the provided hardware. Ensure all screws are tightened securely.

Installing the Sink Top:

1. Carefully place the ceramic sink top onto the vanity cabinet. Ensure it aligns correctly with the cabinet base.
2. Apply a bead of silicone sealant along the edges where the sink meets the wall and the vanity cabinet to create a watertight seal.
3. Install the faucet and drain assembly (not included) according to their respective manufacturer's instructions.
4. Connect the hot and cold water supply lines to the faucet and the drain pipe to the P-trap. Ensure all connections are tight to prevent leaks.
5. Turn on the main water supply and check for any leaks.



Image 2: Product dimensions (76cm/29.9" W, 52cm/20.4" H, 46cm/18.1" D) for planning installation space.



Image 3: Details of the smooth ceramic sink, highlighting the safe overflow drain and rounded edge design to prevent injury.

Operating Instructions

Drawers:

The vanity features four soft-glide drawers. To open, gently pull the integrated handle. To close, push the drawer back until it fully retracts. Avoid forcing the drawers, as this can damage the soft-glide mechanism.

Sliding Door Cabinet:

The central fluted panel functions as a sliding door. To access the cabinet, gently slide the panel to either the left or right. Ensure the path is clear of obstructions before sliding.



Image 4: Illustrates the stylish textured design, convenient sliding doors, and the large storage space available within the vanity.



Towels



skincare



toothbrush



toothpaste



air fresheners



Spacious Storage:

Holds towels, air fresheners, toiletries, etc

Drawer Storage:

For facial cleansers, creams, and more.



Image 5: View of the vanity with drawers and the sliding door open, demonstrating the spacious storage capacity for various bathroom items.

Maintenance

Cleaning the Vanity Cabinet:

Wipe the engineered wood surfaces with a soft, damp cloth. For stubborn marks, use a mild, non-abrasive cleaner. Avoid harsh chemicals or abrasive pads, as these can damage the waterproof finish.

Cleaning the Ceramic Sink:

Clean the ceramic sink with a non-abrasive bathroom cleaner and a soft sponge or cloth. Rinse thoroughly with water after cleaning. Avoid using abrasive powders or steel wool, which can scratch the surface.

General Care:

- Promptly wipe up any water spills to prevent moisture damage.
- Periodically check all hardware and connections for tightness and re-tighten if necessary.

- Avoid placing extremely hot items directly on the vanity surface without protection.

Troubleshooting

Problem	Possible Cause	Solution
Drawers do not close smoothly or are misaligned.	Improper installation of drawer slides; obstruction in the slide mechanism; uneven cabinet mounting.	Check that drawer slides are correctly installed and aligned. Ensure no objects are blocking the slides. Verify the vanity cabinet is level and securely mounted to the wall. Adjust drawer front screws if available.
Sink wobbles on the vanity.	Uneven vanity surface; insufficient sealant.	Ensure the vanity cabinet is level. Apply a fresh, even bead of silicone sealant between the sink and the cabinet, and between the sink and the wall. Allow adequate curing time.
Water leaks from plumbing connections.	Loose connections; damaged washers or seals.	Turn off water supply. Tighten all plumbing connections with an adjustable wrench. Replace any worn or damaged washers/seals. Apply plumber's tape to threaded connections if necessary.
Sliding door sticks or is difficult to move.	Debris in the track; misalignment.	Inspect the sliding door track for any debris and clean it. Ensure the door is properly seated in its track.

Specifications

Feature	Detail
Brand	GOFEI
Model Number	SY410311Y-US3261
Product Dimensions (D x W x H)	18" x 30" x 20.5" (46cm x 76cm x 52cm)
Material	Engineered Wood (Cabinet), Ceramic (Sink Top)
Color	Oak (Cabinet)
Mounting Type	Wall Mount
Number of Drawers	4
Number of Doors	1 (Sliding)
Storage Options	4 drawers, 1 sliding door cabinet
Item Weight	88.85 Pounds
Required Assembly	Yes

Warranty and Support

For warranty information or technical support, please contact GOFEL customer service. Keep your purchase receipt and model number (SY410311Y-US3261) readily available when contacting support.

Contact information can typically be found on the GOFEL official website or through your retailer's customer service portal.