

Tbest Tbestgtcqku1v5g

Tbest Paintless Dent Repair Tool Set (Model Tbestgtcqku1v5g) - Instruction Manual

Model: Tbestgtcqku1v5g | Brand: Tbest

1. INTRODUCTION

Thank you for choosing the Tbest Paintless Dent Repair Tool Set. This manual provides essential information for the safe and effective use of your new tool set. This kit is designed for the paintless repair of dents on various flat metal surfaces, such as automobile body panels. Please read these instructions carefully before use and retain them for future reference.

Important Note: This dent repair tool set is designed to be used in conjunction with other accessories, such as hammers and pulling devices. It cannot function effectively as a standalone tool.

2. PACKAGE CONTENTS

Please verify that all components listed below are present in your package:

- 2 x Stainless Steel Slots
- 2 x Short Pulling Lines (Blue)
- 2 x Long Pulling Lines (Blue)
- 2 sets of Screws (for attaching stainless steel slots)




Image Description: An overhead view displaying all components of the Tbest Paintless Dent Repair Tool Set. It includes two stainless steel rectangular slots with attached bolts/nuts, two longer blue plastic pulling lines, and two shorter blue plastic pulling lines. These parts are laid out on a white background, clearly showing their individual forms.

3. SAFETY INFORMATION

Always observe the following safety precautions when using this tool set:

- Wear appropriate personal protective equipment, such as safety glasses and gloves, to prevent injury.
- Ensure the work area is well-lit and free from obstructions.
- Keep children and bystanders away from the work area.
- Do not use the tools for purposes other than paintless dent repair.
- Inspect all components for damage before each use. Do not use damaged tools.
- Always use this tool set with compatible and appropriate additional tools (e.g., slide hammers, pulling bridges) as required for the specific dent repair task.
- Exercise caution when applying force to avoid further damage to the vehicle or injury.

4. SETUP AND ASSEMBLY

The Tbest Paintless Dent Repair Tool Set is designed for straightforward assembly. The stainless steel slots serve as anchor points for the pulling lines, which are then used with external pulling tools.

1. **Identify Components:** Separate the stainless steel slots, blue pulling lines (short and long), and screws.

2. **Attach Pulling Lines:** The blue pulling lines are designed to slide into the channels of the stainless steel slots. Ensure they are securely seated. The screws are typically used to attach the stainless steel slots to a pulling bridge or similar device, providing a secure connection for applying tension.
3. **Prepare for Use:** Once the pulling lines are attached to the stainless steel slots, these assemblies can be integrated with your chosen dent pulling equipment (e.g., a slide hammer or a pulling bridge).




Image Description: Various pieces of the dent repair kit are arranged on a light wooden surface. This includes two stainless steel rectangular pieces with threaded attachments, and several blue plastic pulling lines of different lengths. The image illustrates the individual parts before assembly or use.

5. OPERATING INSTRUCTIONS

This tool set is an integral part of a paintless dent repair process. The general steps for using this tool in conjunction with other PDR equipment are as follows:

1. **Assess the Dent:** Carefully examine the dent to determine its size, depth, and location. Clean the area thoroughly.
2. **Apply Adhesive (if applicable):** If using glue-pulling methods, apply appropriate PDR glue to a suitable pulling tab (not included) and attach it to the center or edge of the dent. Allow the glue to cure as per its instructions.
3. **Attach Pulling Lines:** Once the pulling tab is secure, attach the blue pulling lines from this kit to the pulling tab. The stainless steel slots will serve as the connection point to your pulling device.
4. **Connect to Pulling Device:** Securely connect the stainless steel slots (with attached pulling lines) to your chosen dent pulling device, such as a slide hammer or a pulling bridge.
5. **Apply Controlled Pulling Force:** Gradually and carefully apply pulling force using your external

device. The goal is to gently pull the dent outwards without damaging the paint. Multiple, controlled pulls are often more effective than one strong pull.

6. **Release and Refine:** Once the dent is pulled out, carefully release the pulling device. If using glue, remove the glue and tab. Use a knockdown tool (not included) to gently tap down any high spots around the repaired area, blending the repair seamlessly.
7. **Repeat if Necessary:** For larger or more complex dents, the process may need to be repeated, adjusting the pulling points and force as needed.



Image Description: This image shows the Tbest dent repair tool components (stainless steel slots and blue pulling lines) arranged in the foreground. In the background, two smaller inset images illustrate the application: one shows a close-up of a dent on a car fender, and the other shows a sleek silver sedan, indicating the type of vehicle the tool is designed for.

6. MAINTENANCE

Proper maintenance will extend the life of your Tbest Dent Repair Tool Set:

- **Cleaning:** After each use, wipe down all components with a clean, dry cloth to remove any dirt, glue residue, or moisture.
- **Storage:** Store the tool set in a dry, clean environment, away from direct sunlight and extreme temperatures. Keeping the components organized in a toolbox or dedicated storage case will prevent loss and damage.
- **Inspection:** Periodically inspect the stainless steel slots and pulling lines for any signs of wear,

cracks, or deformation. Replace any damaged components immediately to ensure safe and effective operation.

7. TROUBLESHOOTING

If you encounter issues while using the Tbest Paintless Dent Repair Tool Set, consider the following:

- **Tool Not Pulling Dent Effectively:**
 - Ensure the pulling lines are securely attached to both the pulling tab (if used) and the stainless steel slots.
 - Verify that the stainless steel slots are firmly connected to your external pulling device.
 - Check if the pulling tab (if used) has sufficient adhesive strength and is properly cured.
 - Confirm that the external pulling device is being operated correctly and applying adequate, controlled force.
- **Components Seem Loose:**
 - Re-check all screw connections and ensure they are tightened appropriately.
 - Ensure pulling lines are fully seated in the stainless steel slots.
- **Further Damage to Surface:**
 - This usually indicates excessive force or improper technique. Review operating instructions and apply force more gradually.
 - Ensure the pulling tab (if used) is appropriate for the dent size and material.

For issues not covered here, please refer to the support information provided in Section 9.

8. SPECIFICATIONS

Brand	Tbest
Model Number	Tbestgtcqku1v5g
Material	ABS Plastic (Pulling Lines), Metal (Stainless Steel Slots)
Color	Blue (Pulling Lines), Silver (Stainless Steel Slots)
Approximate Weight	250 g (0.55 lbs)
Parcel Dimensions	17 x 15 x 4 cm (6.7 x 5.9 x 1.6 inches)

9. WARRANTY AND SUPPORT

Specific warranty details for the Tbest Paintless Dent Repair Tool Set are not provided in the product information. For warranty claims, technical support, or inquiries regarding replacement parts, please contact the seller or manufacturer directly through the platform where the product was purchased. You may visit the [Tbest Store on Amazon](#) for more information about the brand and other products.

Documents - Tbest – Tbestgtcqku1v5g
no relevant documents