

T R P AC1001

T R P AC1001 Air Dryer Cartridge: Annual Replacement Filter Instruction Manual

Model: AC1001 | Brand: T R P

1. PRODUCT OVERVIEW

The T R P AC1001 Air Dryer Cartridge is designed to maintain the optimal performance of your vehicle's air brake system. It effectively removes moisture, oil aerosols, and other contaminants from compressed air, preventing damage and ensuring reliable brake operation. Regular replacement of this cartridge is crucial for the longevity and efficiency of your air brake system.



Image 1: The T R P AC1001 Air Dryer Cartridge, a vital component for air brake system maintenance.

2. COMPATIBILITY

This air dryer cartridge is a direct replacement for AC1001 air dryer cartridge systems commonly found in commercial trucks and heavy-duty vehicles. Verify your vehicle's specific requirements before installation.

3. INSTALLATION (SETUP)

The T R P AC1001 Air Dryer Cartridge features a simple spin-on design for quick replacement. Installation should be performed by a qualified technician or an individual with experience in vehicle air brake systems.

- Safety First:** Ensure the vehicle's air system is completely depressurized before beginning any work. Engage parking brakes and block wheels.
- Locate the Air Dryer:** Identify the existing air dryer unit on your vehicle.
- Remove Old Cartridge:** Using appropriate tools (e.g., a strap wrench), carefully unscrew the old air dryer cartridge counter-clockwise. Be prepared for residual air or moisture to escape.
- Inspect and Clean:** Inspect the mounting surface for any debris or old gasket material. Clean the

surface thoroughly to ensure a proper seal.

5. **Install New Cartridge:** Apply a thin film of clean oil to the new cartridge's gasket. Screw the new T R P AC1001 cartridge clockwise onto the air dryer head until the gasket makes contact. Then, tighten an additional 3/4 to 1 full turn, or as specified by the air dryer manufacturer. **Do not overtighten.**
6. **Re-pressurize and Check for Leaks:** Slowly re-pressurize the air system and carefully check all connections around the new cartridge for any air leaks using a soapy water solution.



Image 2: The T R P AC1001 Air Dryer Cartridge in its packaging, ready for installation.

4. OPERATION

Once installed, the T R P AC1001 Air Dryer Cartridge operates automatically as part of your vehicle's air brake system. It continuously filters compressed air, removing moisture and contaminants before they can enter and damage critical components. No user intervention is required during normal operation.

5. MAINTENANCE

The T R P AC1001 Air Dryer Cartridge is designed for annual replacement to ensure optimal air system performance and protection. Regular replacement helps prevent costly repairs and maintains the safety and efficiency of your air brake system.

- **Annual Replacement:** It is strongly recommended to replace the air dryer cartridge annually, or more frequently under severe operating conditions (e.g., high humidity, frequent braking, heavy usage).
- **System Checks:** Periodically inspect the air dryer unit and associated air lines for any signs of leaks, damage, or excessive moisture accumulation.
- **Desiccant Material:** The cartridge contains high-grade desiccant material that absorbs moisture. Over time, this material becomes saturated and loses its effectiveness, necessitating replacement.

6. TROUBLESHOOTING

If you experience issues with your air brake system after installing or during the use of the AC1001 cartridge, consider the following:

- **Air Leaks:** If air leaks are detected around the cartridge, ensure it is properly tightened (without overtightening) and that the gasket is seated correctly. Re-check with soapy water.
- **Excessive Moisture in Air System:** If moisture continues to be present in the air system shortly after replacement, verify that the correct cartridge was installed and that the air dryer purge valve is functioning correctly. A faulty purge valve can prevent proper moisture expulsion.
- **Reduced Air Pressure:** This is unlikely to be caused by a new, properly installed cartridge. Check other components of the air system, such as the compressor, governor, or other filters.

For persistent issues, consult a professional mechanic specializing in heavy-duty vehicle air brake systems.

7. SPECIFICATIONS

Model Number	AC1001
---------------------	--------

Brand	T R P (Generic)
Manufacturer	Paccar
Item Weight	1.5 pounds
Package Dimensions	24 x 18 x 12 inches
Exterior Material	METAL
OEM Part Number	AC1001

8. WARRANTY AND SUPPORT

Specific warranty information for the T R P AC1001 Air Dryer Cartridge is not provided in the product details. Please refer to the manufacturer's or seller's documentation for warranty terms and conditions. For technical support or further assistance, contact the product seller or a certified automotive service professional.

© 2025 T R P. All rights reserved.

This manual is for informational purposes only. Always follow safety precautions and consult a professional for complex installations or repairs.