

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [VEVOR](#) /

› [VEVOR Aluminum Awning 40 x 42 inch Instruction Manual \(Model QL-40INCH\)](#)

VEVOR QL-40INCH

VEVOR Aluminum Awning 40 x 42 inch Instruction Manual

Model: QL-40INCH

PRODUCT OVERVIEW

The VEVOR Aluminum Awning provides robust protection for doors, windows, patios, and porches. Designed for all-season use, it shields against sun, rain, and snow, ensuring durability and aesthetic appeal for your outdoor spaces.

- **All-Season Protection:** Offers strong protection against sun, rain, and snow, preventing damage to doors and outdoor items.
- **Reinforced Aluminum Alloy Construction:** Features 0.6mm aluminum sheets and a heavy-duty frame with 22mm thick support rods for long-term durability.
- **Smart Water Flow Design:** Curved edges and a drainage system effectively channel rainwater, preventing accumulation and ensuring a clean, dry canopy.
- **Practical and Stylish:** The sleek ripple design complements any home exterior, suitable for various outdoor applications.

SETUP AND ASSEMBLY

Follow these steps for proper assembly and installation of your VEVOR Aluminum Awning. It is recommended to have two people for assembly and installation.

Components Included:

- 1x User Manual
- 7x Panels
- 2x Side Brackets
- 1x Front Aluminum Bar

- 1x Rear Aluminum Bar A
- 1x Rear Aluminum Bar B
- 1x Reinforcement Piece
- 2x Support Pipes

Assembly Steps:

1. **Prepare Panels:** Carefully remove the protective film from the polycarbonate panels.
2. **Connect Panels:** Insert the panels into each other and fix them with the H-bar in the middle.
3. **Attach Brackets:** Install the side brackets and back bars to the assembled panels. Ensure proper alignment.
4. **Secure Frame:** Use the provided screws to fix the panels to the brackets and bars, creating the main awning structure.
5. **Mount to Wall:** Mark the desired installation position on your wall. Ensure at least 3 inches of clearance above your door/window. Drill pilot holes and fix the awning to the wall using the provided screws and anchors.
6. **Install Support Rods:** Attach the support pipes to the awning and secure them to the wall at the appropriate angle (typically 75 degrees for optimal drainage and stability).



Figure 1: Visual guide for the DIY assembly process.

Installation Videos:

Your browser does not support the video tag.

Video 1: Detailed installation notes for a window awning door canopy. This video provides step-by-step visual instructions for assembling and mounting the awning.

Your browser does not support the video tag.

Video 2: Full assembly video for the VEVOR Aluminum Awning. This video demonstrates the complete process from unboxing to final installation.

Your browser does not support the video tag.

Video 3: General awning installation video. This short video provides a quick overview of the installation process.

OPERATING INSTRUCTIONS

The VEVOR Aluminum Awning is a fixed structure designed to provide continuous protection. Once properly installed, it requires no manual operation for daily use.

- **Sun Protection:** Reduces direct sunlight exposure, helping to protect doors, windows, and interior furnishings from UV damage and heat.

- **Rain and Snow Shelter:** The curved design and integrated drainage system effectively divert rainwater and snowmelt away from your entryways, keeping them dry and clear.
- **Wind Resistance:** The robust aluminum alloy frame is designed to withstand various weather conditions, providing stable shelter.

MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your awning.

- **Cleaning:** Periodically clean the aluminum panels with mild soap and water. Avoid abrasive cleaners or harsh chemicals that could damage the finish.
- **Inspection:** Annually inspect all screws, bolts, and connections to ensure they are tight and secure. Re-tighten any loose fasteners.
- **Drainage Check:** Ensure the drainage channels are free from debris (leaves, dirt) to allow for proper water runoff.
- **Snow Removal:** While designed for snow protection, heavy accumulation of wet snow should be gently removed to prevent excessive stress on the structure.

TROUBLESHOOTING

If you encounter issues with your awning, consider the following common solutions:

- **Difficulty during Assembly:** Some users report instructions can be vague or screw holes difficult to align. Double-check the diagrams and ensure all pieces are oriented correctly before tightening. Pre-drilling pilot holes can assist with screw insertion.
- **Water Leakage:** Ensure all panel connections are tight and the H-bar is properly seated. Verify that the nail-free glue (if used) has cured properly to seal gaps. Check for any damage to the panels.
- **Awning Feels Unstable:** Confirm that all wall-mounting screws are securely fastened into a solid surface. Ensure support rods are correctly installed and tightened to maintain the intended angle and rigidity.

SPECIFICATIONS

Feature	Detail
Item Model Number	QL-40INCH
Material	Aluminum

Color	White
Size	40 x 42 inch
Product Dimensions	41.97"D x 40"W x 20.08"H
Item Weight	8.82 Pounds
Operation Mode	Manual (Fixed)
Assembly Required	Yes

WARRANTY AND SUPPORT

VEVOR is committed to providing high-quality products and excellent customer service. For any questions, concerns, or warranty claims regarding your VEVOR Aluminum Awning, please refer to the contact information provided in your product packaging or visit the official VEVOR website. VEVOR aims to empower Home Creators with pro-level products at exceptional value, ensuring superior performance through practical tech innovation.

© 2026 VEVOR. All rights reserved.