

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

> [Rust-Oleum](#) /

> [Rust-Oleum Stops Rust Turbo Spray Paint 393378-6PK User Manual](#)

## Rust-Oleum 393378-6PK

# Rust-Oleum Stops Rust Turbo Spray Paint (Model 393378-6PK)

Satin Black Protective Enamel

## 1. PRODUCT OVERVIEW

---

The Rust-Oleum Stops Rust Turbo Spray System Spray Paint is an oil-based enamel designed for large projects, offering superior coverage and durability. This product provides rust and corrosion protection for metal, wood, concrete, and masonry surfaces. Its advanced Turbo Spray System delivers a wide fan spread for efficient application.

### Key Features:

- **Turbo Spray System:** Features a 10-inch tall fan spread for professional spray equipment results and faster project completion.
- **Protective Enamel:** Oil-based formula prevents rust and corrosion on various surfaces.
- **Quick Drying:** Dries to the touch in 2-4 hours; recoat within 1 hour or after 48 hours.
- **Durable Finish:** Provides tough resistance to rust, abrasion, fading, chipping, and dulling.
- **Coverage:** Each 24 oz can covers up to 40 sq. ft.
- **Satin Finish:** Offers a low-sheen look with long-lasting durability.



Image 1.1: Rust-Oleum Stops Rust Turbo Spray Paint, Satin Black, 24 oz. can.

# SPRAY PATTERNS

GREAT FOR DETAILED NOOKS AND  
CRANNIES WITHOUT THE DRIPS

## STANDARD



COMFORTABLE & TIMELESS  
SPRAY EXPERIENCE

## TURBO SPRAY SYSTEM



UP TO 10" WIDE SPRAY  
PATTERN

\*SPRAY PATTERNS REPRESENTED WITH BLACK PAINT. RESULTS MAY VARY BY COLOR.

Image 1.2: Illustration comparing standard spray patterns with the Turbo Spray System's wider fan pattern (up to 10 inches).

# TURBO TIP

up to 10" fan spray



Image 1.3: Close-up view of the Turbo Tip, designed for a wide fan spray.

## 2. SAFETY INFORMATION

---

**WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Always read and follow all warnings and instructions on the product label.**

### General Safety Precautions:

- Use in a well-ventilated area. Avoid breathing vapors.
- Wear appropriate personal protective equipment, including safety glasses, gloves, and a respirator if ventilation is inadequate.
- Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
- Pressurized container: Do not pierce or burn, even after use.
- Do not expose to temperatures exceeding 120°F (49°C).
- Keep out of reach of children.

## 3. SETUP AND PREPARATION

---

## Surface Preparation:

1. Ensure the surface is clean, dry, and free of loose rust, dirt, grease, oil, and old paint.
2. For best adhesion, lightly sand glossy surfaces.
3. Prime bare metal or heavily rusted surfaces with a Rust-Oleum Stops Rust primer for optimal rust prevention and adhesion.

## Work Area Preparation:

- Protect surrounding areas from overspray using drop cloths or painter's tape.
- Ensure adequate ventilation in the work area.



Image 3.1: Recommended preparation and safety items for painting.

## 4. OPERATING INSTRUCTIONS (APPLICATION)

### Before You Spray:

1. Shake the can vigorously for one minute after the mixing ball begins to rattle. Continue to shake occasionally during use.

2. Test spray on a scrap piece of material to check color and spray pattern.

### Application Technique:

1. Hold the can upright 10-16 inches from the surface.
2. Press the spray button firmly and move the can back and forth in a steady motion, slightly overlapping each stroke.
3. For best results, apply two or more light coats a few minutes apart rather than one heavy coat. This helps prevent drips and runs.
4. The Turbo Spray System provides a wide fan pattern, allowing for faster coverage of large areas. Adjust your movement speed to achieve even coverage.



\* The image reflects application of Turbo Spray System and may not match the product color.

Image 4.1: Example of applying Rust-Oleum Turbo Spray Paint to a metal surface.

### Drying and Recoating:

- Dries to the touch in 2-4 hours.
- Recoat within 1 hour or after 48 hours. Applying additional coats between 1 and 48 hours may cause wrinkling.
- Full cure time may take several days.

# ADHERES TO



Image 4.2: Demonstrates paint adhesion to both wood and metal surfaces.

# CAP MATCHES COLOR

spray with confidence



Image 4.3: The spray can cap is designed to match the paint color for easy identification.

## 5. MAINTENANCE AND STORAGE

---

### After Each Use:

- To clear the valve and prevent clogging, invert the can and spray for 5 seconds or until only clear gas comes out.
- Wipe off the spray tip with a clean cloth.

### Storage:

- Store cans in a cool, dry, well-ventilated area away from direct sunlight and heat sources.
- Do not store at temperatures above 120°F (49°C).

## 6. TROUBLESHOOTING

---

### Common Issues and Solutions:

<b>Issue</b>	<b>Possible Cause</b>	<b>Solution</b>
<b>Sputtering or Uneven Spray</b>	Insufficient shaking, clogged nozzle, low can pressure.	Shake can vigorously for at least one minute before use and occasionally during application. Invert can and spray to clear nozzle. Ensure can is not too cold.
<b>Drips or Runs</b>	Spraying too close to the surface, applying too heavy a coat, moving the can too slowly.	Maintain a distance of 10-16 inches. Apply several light coats instead of one heavy coat. Move the can at a consistent, steady pace.
<b>Poor Coverage</b>	Spraying too far from the surface, moving the can too quickly.	Adjust spraying distance to 10-16 inches. Slow down movement slightly to ensure adequate paint deposition.
<b>Wrinkling of Paint</b>	Recoating between 1 and 48 hours.	Ensure recoating occurs within 1 hour or after 48 hours to avoid wrinkling.

## 7. SPECIFICATIONS

<b>Specification</b>	<b>Detail</b>
<b>Brand</b>	Rust-Oleum
<b>Model Name</b>	Stops Rust Turbo Spray Paint
<b>Model Number</b>	393378-6PK
<b>Color</b>	Satin Black
<b>Finish Type</b>	Satin
<b>Size</b>	24 Ounce (Pack of 6)
<b>Item Volume</b>	144 Fluid Ounces (total for 6 cans)
<b>Paint Type</b>	Spray, Oil-Based Enamel
<b>Specific Uses</b>	Interior/Exterior
<b>Surface Recommendation</b>	Metal, Wood, Concrete, Masonry
<b>Special Features</b>	Chip Resistant, Fade Resistant, Fast-Drying, Rust Resistant, Scratch Resistant
<b>Coverage</b>	24-40 square feet per can
<b>Water Resistance Level</b>	Water Resistant
<b>Product Dimensions</b>	8.38 x 5.69 x 14.69 inches (package)
<b>Item Weight</b>	11.68 pounds (package)



Image 7.1: Size comparison between a traditional 12oz aerosol can and the larger 24oz Turbo aerosol can.

# SHEEN GUIDE\*


FLAT  
no shine



SATIN  
medium shine



SEMI-GLOSS  
medium-high shine



GLOSS  
high shine

\*Colors may not be available in all sheens

Image 7.2: Sheen Guide illustrating different finish types: Flat (no shine), Satin (medium shine), Semi-Gloss (medium-high shine), and Gloss (high shine).

## 8. WARRANTY AND SUPPORT

### Warranty Information:

Specific warranty details for this product are not provided in the available information. For warranty inquiries, please refer to the product packaging or contact Rust-Oleum directly.

### Customer Support:

For further assistance, technical support, or product information, please visit the official Rust-Oleum website or contact their customer service department. You can also visit the [Rust-Oleum Store on Amazon](#).

## 9. OFFICIAL PRODUCT VIDEOS

No official product videos from the seller were found in the provided data.

