

[Manuals.plus](#) /

› [Jafeton](#) /

› Jafeton SF-4028LS-Faucet Kitchen Faucet User Manual

Jafeton SF-4028LS-Faucet

Jafeton SF-4028LS-Faucet Kitchen Faucet User Manual

Model: SF-4028LS-Faucet

1. INTRODUCTION

Thank you for choosing the Jafeton SF-4028LS-Faucet. This manual provides essential information for the safe installation, operation, and maintenance of your new kitchen faucet. Please read these instructions carefully before installation and retain them for future reference.



Image 1.1: Jafeton SF-4028LS-Faucet, Brushed Nickel finish, with pull-down sprayer and single handle.

2. PRODUCT OVERVIEW

The Jafeton SF-4028LS-Faucet is a modern kitchen faucet designed for versatility and ease of use. It features a high-arc design, a pull-down sprayer with three spray modes, and a single handle for precise control of water flow and temperature.

Key Features:

- **3-Mode Sprayer:** Easily switch between Stream, Spray, and Pause functions.
- **360° Swivel Spout:** Provides full sink coverage and flexibility.
- **Single Handle Control:** Allows for effortless adjustment of water temperature and volume.
- **Durable Construction:** Made from SUS304 stainless steel with food-grade PEX inner hoses for lead-free water.
- **Easy Installation:** Compatible with 1-hole or 3-hole sink configurations.

Premium Features



Pull Down Sprayer



360° Rotaton



One-handed Control



Stepless Temperature Control

Image 2.1: Overview of premium features including pull-down sprayer, 360° rotation, one-handed control, and stepless temperature control.

Package Contents:

Verify that all components are present before beginning installation.



Image 2.2: Included components: faucet body, deck plate, fasteners, and water supply lines.

- Faucet Assembly
- Deck Plate (for 3-hole installation)
- Mounting Hardware (fasteners)
- Water Supply Lines (2)
- Gravity Ball Weight

3. SAFETY INFORMATION

Please observe the following safety precautions during installation and use:

- Always turn off the main water supply before beginning any plumbing work.
- Wear appropriate personal protective equipment, such as safety glasses and gloves.
- Ensure all connections are secure to prevent leaks. Do not overtighten.
- If you are unsure about any step, consult a qualified plumber.
- Do not use harsh chemicals or abrasive cleaners on the faucet finish.

4. SETUP AND INSTALLATION

This faucet is designed for easy installation on 1-hole or 3-hole sinks. All necessary mounting hardware is included.

Pre-Installation:

1. Turn off the main water supply to your kitchen.
2. Remove your old faucet, if applicable. Clean the sink surface thoroughly.
3. Ensure the installation hole diameter is between 1.26-1.97 inches.

Perfect For All Kitchen Layouts



* The installation hole diameter is between 1.26-1.97IN.
Installation thickness within 1.77 IN

Image 4.1: Faucet dimensions and compatibility with 1-hole or 3-hole sink installations.

Installation Steps:

- 1. Prepare the Faucet:** If installing on a 3-hole sink, place the deck plate over the sink holes. Insert the faucet body through the center hole.
- 2. Secure the Faucet:** From underneath the sink, thread the rubber washer, metal washer, and mounting nut onto the faucet shank. Tighten the mounting nut securely to prevent movement.
- 3. Connect Water Supply Lines:** Connect the hot and cold water supply lines from the faucet to your angle stops. Ensure the hot water line connects to the hot water supply and the cold to the cold. Hand-tighten, then use a wrench for a quarter turn.
- 4. Install Gravity Ball Weight:** Attach the gravity ball weight to the pull-down hose approximately 6 inches from the bottom of the loop. This ensures the sprayer retracts properly.
- 5. Test for Leaks:** Turn on the main water supply slowly and check all connections for leaks. Operate the faucet to ensure proper function and spray modes.

Package Includes



Image 4.2: Illustration of high-quality components, including the ceramic valve and 360° rotation mechanism.

Effortless Flexibility with Release Bounce!



Image 4.3: Diagram showing the installation of the gravity ball weight on the pull-down hose for automatic retraction.

5. OPERATING INSTRUCTIONS

Your Jafeton faucet offers intuitive control for water flow, temperature, and spray modes.

Water Flow and Temperature Control:

- The single handle controls both water flow and temperature.
- Lift the handle to increase water flow. Push down to decrease or turn off.
- Move the handle left for hot water and right for cold water.

Sprayer Modes:

The pull-down sprayer features three distinct modes, easily switchable via buttons on the spray head.

3 Modes for All Your Needs

18In Braided Hose



Image 5.1: Illustration of the three spray modes: Stream, Spray, and Pause, and the 18-inch braided hose.

- **Stream Mode:** Provides a steady, aerated flow for filling pots and general washing.
- **Spray Mode:** Delivers a powerful spray for rinsing dishes and cleaning the sink.
- **Pause Mode:** Temporarily stops water flow without turning off the main handle, useful for moving the sprayer between tasks.

One-Hand Control: No Panic, Just Convenience

With a longer water pipe, reaching the switch can sometimes be tricky.

That's why we've added a convenient button to stop the water flow with ease.



■ Pause:



■ Spray:



■ Stream:



Image 5.2: Detailed view of the spray head buttons for mode selection and the 360° rotation feature.

6. MAINTENANCE

Regular cleaning and maintenance will help preserve the finish and functionality of your faucet.

Cleaning the Faucet:

- To maintain the finish, clean the faucet regularly with a soft cloth and mild soap.
- Rinse thoroughly with clean water and dry with a soft cloth to prevent water spots.
- Avoid using abrasive cleaners, steel wool, or harsh chemicals, as these can damage the finish.

Cleaning the Sprayer Nozzles:

- Over time, mineral deposits may accumulate in the rubber nozzles of the spray head.

- Gently rub the rubber nozzles with your finger or a soft brush to dislodge any deposits.
- For stubborn deposits, a solution of equal parts white vinegar and water can be used. Soak the spray head (if detachable) or apply the solution with a cloth.

7. TROUBLESHOOTING

If you encounter any issues with your faucet, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Low Water Flow	Aerator clogged; supply lines kinked; water supply partially off.	Clean or replace aerator; check and straighten supply lines; ensure water supply valves are fully open.
Leaks from Faucet Base	Mounting nut loose; O-rings damaged; internal connections loose.	Tighten mounting nut; inspect and replace O-rings if necessary; check internal hose connections.
Sprayer Does Not Retract Fully	Gravity ball weight improperly positioned or missing; hose obstructed.	Ensure gravity ball is correctly installed on the hose; clear any obstructions under the sink.
Water Temperature Control Issues	Hot/cold supply lines reversed; cartridge issue.	Verify hot and cold supply line connections; if issue persists, contact support for cartridge replacement.

If the problem persists after attempting these solutions, please contact customer support.

8. SPECIFICATIONS

Detailed technical specifications for the Jafeton SF-4028LS-Faucet:

Feature	Detail
Brand	Jafeton
Model Name	SF-4028LS-Faucet
Material	Stainless Steel (SUS304)
Finish Type	Finished (Brushed Nickel)
Mounting Type	Deck Mount
Number of Handles	1
Hole Count Compatibility	1 or 3 Hole
Maximum Flow Rate	1.6 Gallons Per Minute
Spout Height	4.33 Inches
Spout Reach	16.93 Inches

Feature	Detail
Product Dimensions	9.65"D x 14.96"W x 9.84"H
Item Weight	3.45 pounds
Special Features	Pull Out Sprayer, Easy to Install, 360 Swivel, Lead Free

9. WARRANTY AND SUPPORT

For warranty information and customer support, please refer to the documentation included with your purchase or contact the seller directly. Specific warranty terms may vary.

For further assistance, please reach out to Jafeton customer service through the retailer where the product was purchased.