

[Manuals.plus](#) /

> [HOMLYLINK](#) /

> HOMLYLINK 23"x19" White 3-Hole Pedestal Sink Instruction Manual

## HOMLYLINK 23x19 3 Hole with Backsplash

# HOMLYLINK 23"x19" White 3-Hole Pedestal Sink Instruction Manual

Model: 23x19 3 Hole with Backsplash

[Contents](#)   [Specifications](#)   [Overview](#)   [Safety Information](#)   [Package](#)  
[Installation](#)   [Operation](#)   [Maintenance](#)   [Troubleshooting](#)   [Warranty & Support](#)

## 1. OVERVIEW

---

The HOMLYLINK 23"x19" White 3-Hole Pedestal Sink is a rectangular bathroom fixture designed for both contemporary and traditional settings. It features a backsplash design to prevent water splashing, a compact column basin structure for space-saving, and a widened countertop for essential toiletries. Constructed from high-temperature fired porcelain with a white enamel glaze, it is designed to be stain-resistant and easy to clean.



STAIN-RESISTANT



EASY CLEANING



SMOOTH DRAINAGE



GLOSSY WHITE



FADELESS



STURDY

Image 1.1: The HOMLYLINK Pedestal Sink, showcasing its elegant design and space-saving profile.

## 2. SAFETY INFORMATION

---

- Always turn off the main water supply before beginning any installation or maintenance.
- Wear appropriate personal protective equipment, including safety glasses and gloves.
- Ensure the installation area is clear of obstructions and well-lit.
- The sink components are heavy. Use proper lifting techniques or seek assistance to prevent injury.
- Verify all connections are secure and watertight to prevent leaks.
- If you are unsure about any step, consult a qualified plumber.

## 3. PACKAGE CONTENTS

---

Verify that all components are present and undamaged before beginning installation.

- Sink Bowl
- Pedestal
- Paper User Manual (this document)



## SAFETY PACKAGE

### Packaging Upgrade

- Thicker Protective Layer
- Comprehensive Protection
- Tighter Buffer Layer



### Passed Tests

- Fall
- Collision
- Extrusion

Replacement and return policy within 30 days.

## MAIN ITEMS



BOWL



PEDESTAL



PAPER USER MANUAL

Image 3.1: Included components: sink bowl, pedestal, and user manual.

## 4. SPECIFICATIONS

Feature	Detail
Product Dimensions	19"D x 23"W x 34.5"H
Basin Interior Dimensions	17.5"D x 17"W x 6"H
Material	Porcelain
Color	White
Faucet Holes	3 (4-inch universal spacing, 1 1/8 inch diameter each)
Drain Opening	Standard 1 3/4 inch
Overflow Port	Yes
Installation Type	Freestanding, Back-mounted with pre-drilled holes
Item Weight	47 Pounds



Image 4.1: Detailed product dimensions for the sink bowl and pedestal.

## 5. INSTALLATION

This pedestal sink is designed for straightforward installation. Follow these general steps:

1. **Prepare the Installation Area:** Ensure the floor is level and the wall is structurally sound to support the sink's weight. Mark the desired location for the pedestal and the basin's mounting holes on the wall.
2. **Install Wall Anchors:** Drill pilot holes at the marked locations for the basin's mounting bolts. Insert appropriate wall anchors (not included, but typically required for secure wall mounting) and secure the mounting bolts, leaving enough thread exposed for the basin.
3. **Position the Pedestal:** Carefully place the pedestal in its designated position on the floor, ensuring it aligns with the basin's intended location.
4. **Mount the Basin:** Lift the sink basin and align its pre-drilled holes with the mounting bolts on the wall. Gently lower the basin onto the pedestal and slide it onto the bolts. Secure the basin to the wall using washers and nuts, tightening them firmly but without over-tightening to avoid cracking the porcelain.
5. **Install Faucet and Drain:** Install your chosen 3-hole faucet (not included) into the pre-drilled faucet holes. Install a standard 1 3/4 inch pop-up drain assembly (not included) into the basin's drain

opening, ensuring a tight, leak-free seal.

6. **Connect Plumbing:** Connect the hot and cold water supply lines to the faucet. Connect the drain assembly to your P-trap and the main drain line. Ensure all connections are hand-tightened, then use a wrench for a final quarter-turn, being careful not to overtighten.
7. **Test for Leaks:** Turn on the main water supply slowly and check all connections for leaks. Run water through the faucet and observe the drain for any signs of leakage.



## LARGE-CAPACITY SINK

This pedestal sink is designed to be splash-proof and offers large water storage capacity.

*Image 5.1: The sink basin with pre-drilled faucet holes and overflow port.*



## HIGH TEMPERATURE FIRED CERMAMIC

- Sturdy
- Smooth Surface
- Easy to Clean
- Stain Resistant

Image 5.2: Close-up view of the three faucet holes and the drain opening.

## 6. OPERATION

Operating the HOMLYLINK Pedestal Sink is straightforward. Once installed and plumbed, simply use the faucet handles to control water flow and temperature. The integrated overflow port prevents accidental basin overflow by diverting excess water into the drain system.



### MAIN FEATURES

- Simple Installation
- Easy to Clean
- Smooth Drainage
- Spacious Interior
- Glossy White
- Fadeless
- Overflow Design
- Splash-Proof Design
- Impact Resistance

### ADAPTING SIZE

- DIA 1 $\frac{3}{4}$ " Drain Hole
- Centerset Faucet Hole DIA 1 $\frac{3}{8}$ "

Image 6.1: The overflow design helps prevent water from spilling over the basin edge.

## 7. MAINTENANCE

The HOMLYLINK Pedestal Sink is designed for easy maintenance due to its high-temperature fired

ceramic and white enamel glaze, which makes it stain-resistant and non-yellowing.

- **Regular Cleaning:** Wipe the surface of the sink with a damp cloth to remove daily grime.
- **Drying:** After cleaning, wipe with a dry cloth to prevent water spots and maintain its pristine appearance.
- **Avoid Harsh Chemicals:** Do not use abrasive cleaners, scouring pads, or harsh chemical solutions, as these can damage the glaze.



*Image 7.1: The pure white, non-yellowing, and fadeless porcelain ensures long-lasting aesthetics.*

## 8. TROUBLESHOOTING

---

- **Leaking Connections:** If you notice leaks, first ensure all plumbing connections (faucet, supply lines, drain, P-trap) are securely tightened. Check for damaged washers or seals and replace if necessary.
- **Slow Drainage:** A slow-draining sink is often caused by a clog. Attempt to clear the clog using a plunger or a drain snake. Avoid using harsh chemical drain cleaners that could damage plumbing.
- **Wobbly Sink:** If the sink feels unstable, re-check the wall mounting bolts and the connection between the basin and the pedestal. Ensure they are tightened appropriately.

## 9. WARRANTY AND SUPPORT

---

The HOMLYLINK Pedestal Sink comes with a **3-year Limited Warranty**. HOMLYLINK is committed to customer satisfaction and provides lifetime after-sales support for their porcelain pedestal sinks.

For any questions or concerns regarding your product, please contact HOMLYLINK customer support.

They aim to provide a professional solution within 1 working day.

For further assistance, visit the official HOMLYLINK Store: [HOMLYLINK Store](#)