Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

ChipPower GS2

ChipPower GS2 Performance Chip Instruction Manual

For Alfa Romeo Giulietta 1.8 TBi 241 CV (2010-2020)

1. Introduction

Thank you for choosing the ChipPower GS2 Performance Chip. This unit is designed to optimize your vehicle's engine performance, offering increased power, torque, and improved fuel efficiency. The GS2 unit is an external module that connects to your vehicle's engine system without modifying the original ECU software. This manual provides essential information for safe installation, operation, and maintenance of your performance chip.

2. Safety Information

- **Vehicle Compatibility:** This product is only suitable for Alfa Romeo Giulietta 1.8 TBi 241 CV (177 kW) models manufactured between 2010 and 2020. Ensure your vehicle's engine specifications match the compatibility requirements.
- **Installation Environment:** Perform installation in a well-lit, dry, and safe environment. Ensure the vehicle's engine is cool and the ignition is off before beginning installation.
- **Professional Assistance:** While designed for self-installation, if you are unsure about any step, consult a qualified automotive technician.
- **Legal Disclaimer:** The use of this product is at your own risk. ChipPower is not responsible for any damages or issues arising from improper installation or use.

3. Product Overview

The ChipPower GS2 Performance Chip is an advanced tuning module designed for easy integration. It comes as a complete kit, ready for installation.

3.1 Package Contents

- ChipPower GS2 Chiptuning Module
- Robust Cable Set with Original Plug & Drive Connectors

- Cable Ties for secure routing
- QR Code for Online Installation Instructions



Figure 1: Complete ChipPower GS2 kit showing the module, wiring harness, cable ties, and QR code instruction cards.

3.2 Key Features

- Up to 15% increase in power and torque.
- Potential fuel savings of 5-10% with moderate driving.
- External module, no permanent ECU modifications.
- Plug & Drive installation, typically within 15 minutes.
- Adjustable unit for fine-tuning performance.
- CE, UKCA, RoHS certified.



Figure 2: Close-up view of the ChipPower GS2 module, highlighting its benefits such as increased power and torque, elimination of turbo lag, easy installation, and fuel saving.

4. Setup and Installation

The ChipPower GS2 unit features a Plug & Drive system for quick and easy installation. No special tools or workshop visits are required.

4.1 Pre-Installation Steps

1. Ensure the vehicle's engine is turned off and cool.
2. Locate the specific sensor connection point in your engine bay. Refer to the online instructions provided via the QR code for exact sensor location for your Alfa Romeo Giulietta 1.8 TBi.
3. Clean the area around the sensor if necessary.

4.2 Connecting the Module

1. Disconnect the original sensor plug from the vehicle's wiring harness.
2. Connect one end of the ChipPower GS2 wiring harness to the vehicle's sensor.
3. Connect the other end of the ChipPower GS2 wiring harness to the original sensor plug that was disconnected.
4. Ensure all connections are secure and click into place.



Figure 3: Step-by-step visual guide demonstrating how to connect the ChipPower GS2 module to its wiring harness, ensuring a secure fit.



Figure 4: Detailed view of the Plug & Drive connector, showing the secure locking mechanism for reliable connection.

4.3 Securing the Module and Wiring

1. Mount the ChipPower GS2 module in a secure location within the engine bay, away from excessive heat, moving parts, and moisture.
2. Use the provided cable ties to neatly route and secure the wiring harness, preventing it from interfering with other engine components.
3. Double-check all connections and mounting points before closing the hood.

4.4 Accessing Online Instructions

For detailed, vehicle-specific installation instructions, scan the QR code provided in your package. This will direct you to an online guide with visual aids for your specific Alfa Romeo Giulietta 1.8 TBi model.



Figure 5: The ChipPower GS2 module shown alongside the QR code for accessing online installation instructions. The image also indicates a potential adjustment point on the module.

5. Operation

Once installed, the ChipPower GS2 module operates automatically. It optimizes engine parameters to deliver enhanced performance and efficiency.

5.1 Initial Start-up

After installation, start your vehicle. The module will begin to adapt to your engine's characteristics. Drive moderately for the first few kilometers to allow the system to fully integrate.

5.2 Adjusting Performance (Optional)

The GS2 unit is adjustable, allowing you to fine-tune its performance characteristics. Refer to the online instructions (via QR code) for detailed guidance on how to access and adjust the settings on your module. Adjustments should be made incrementally and tested carefully.

5.3 Fuel Economy

While the module increases power, it can also contribute to fuel savings (5-10%) when maintaining a moderate driving style. Aggressive driving will naturally consume more fuel, regardless of the module's presence.

6. Maintenance

The ChipPower GS2 Performance Chip is designed to be maintenance-free. However, regular checks are recommended:

- Periodically inspect the module and its wiring for any signs of wear, damage, or loose connections.
- Ensure the module remains securely mounted and free from excessive dirt or moisture.
- Keep the engine bay clean to prevent debris from affecting the module or its connections.

7. Troubleshooting

If you experience any issues after installing the ChipPower GS2 module, consider the following:

- **No Performance Change:** Double-check all connections to ensure they are secure and correctly installed. Refer to the online instructions for specific sensor locations.
- **Engine Warning Light:** If an engine warning light appears, immediately disconnect the ChipPower GS2 module and reconnect the original sensor plug. If the light persists, consult a qualified mechanic. If the light disappears, re-check the module's installation.
- **Rough Idling or Hesitation:** Ensure the module's settings (if adjusted) are appropriate for your vehicle. Try resetting the module to its default settings or removing it to see if the issue resolves.
- **General Issues:** For any persistent issues, refer to the detailed troubleshooting section in the online manual (accessed via QR code) or contact ChipPower customer support.

8. Specifications

Model	GS2
Brand	ChipPower
Compatibility	Alfa Romeo Giulietta 1.8 TBi 241 CV (177 kW), 2010-2020
Certifications	CE, UKCA, RoHS
Module Dimensions (approx.)	110 mm (Height) x 90 mm (Width) x 37 mm (Depth)
Cable Length (approx.)	1000 mm



Figure 6: Dimensional drawing of the ChipPower GS2 module and its connecting cable, showing approximate measurements.

9. Warranty and Support

ChipPower is committed to providing high-quality products. For information regarding warranty terms, technical support, or any product-related inquiries, please refer to the official ChipPower website or contact their customer service directly. Contact details can typically be found on the ChipPower brand store page or within the online instructions accessed via the QR code.

© 2026 ChipPower. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B0FCYG3RZG

More documents and user manuals: **https://manuals.plus/**