

[Manuals.plus](#) /

› [JOINPAYA](#) /

› JOINPAYA Quick Connect Water Fill Inlet Valve Adapter User Manual

JOINPAYA C1381216WO6ITXAL

JOINPAYA Quick Connect Water Fill Inlet Valve Adapter User Manual

Model: C1381216WO6ITXAL

1. INTRODUCTION

This manual provides instructions for the proper installation, operation, and maintenance of your JOINPAYA Quick Connect Water Fill Inlet Valve Adapter. This adapter is designed to facilitate quick and secure connections for water systems in RVs, trailers, and garden hoses, ensuring a reliable water supply.

2. SAFETY INFORMATION

- Always turn off the main water supply before installing or performing maintenance on the adapter.
- Ensure all connections are tight to prevent leaks.
- Do not overtighten connections, as this may damage the plastic components.
- Inspect the adapter and hoses regularly for signs of wear or damage. Replace damaged parts immediately.
- This product is intended for water systems only. Do not use with other liquids or gases.

3. PACKAGE CONTENTS

Verify that all components are present in the package:

- 1 x JOINPAYA Quick Connect Water Fill Inlet Valve Adapter

4. PRODUCT OVERVIEW

The JOINPAYA Quick Connect Water Fill Inlet Valve Adapter features a durable plastic construction with quick-connect fittings on both ends and an integrated blue shut-off valve. It is designed for easy integration into existing water lines.



Figure 1: JOINPAYA Quick Connect Water Fill Inlet Valve Adapter. This image shows the main product, a white plastic adapter with quick-connect ends and a blue lever for controlling water flow.



Figure 2: Product Dimensions. This image illustrates the physical dimensions of the adapter: approximately 11.5 cm (4.52 inches) in length, 4.5 cm (1.77 inches) in height, and 2.6 cm (1.02 inches) in width.

5. SETUP AND INSTALLATION

Follow these steps for proper installation of the Quick Connect Water Fill Inlet Valve Adapter:

1. **Prepare the Water System:** Ensure the main water supply to your RV, trailer, or garden hose system is completely shut off.
2. **Identify Connection Points:** Determine where the adapter will be integrated into your water line. The quick-connect ends are designed for easy push-fit connections with compatible tubing.
3. **Connect the Adapter:** Firmly push the water tubing into each quick-connect end of the adapter until it seats securely. A slight tug should confirm a tight connection.
4. **Secure Connections:** Verify that both ends of the adapter are properly connected and that the tubing is fully inserted.
5. **Test for Leaks:** Slowly turn on the main water supply and carefully inspect all connections for any signs of leakage. If leaks are detected, turn off the water supply, re-seat the connections, and re-test.



Figure 3: Connecting the Adapter. This image shows hands demonstrating the push-fit connection of the adapter to a water line.

6. OPERATING INSTRUCTIONS

The integrated blue lever on the adapter controls the water flow:

- **To Open the Valve:** Rotate the blue lever to align with the direction of the water flow (typically parallel to the main body of the adapter).
- **To Close the Valve:** Rotate the blue lever perpendicular to the main body of the adapter. This will shut off the water flow through the adapter.

7. MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your adapter:

- **Inspection:** Periodically check the adapter and all connected tubing for any signs of wear, cracks, or leaks.
- **Cleaning:** If necessary, clean the exterior of the adapter with a mild soap and water solution. Avoid harsh

chemicals that could damage the plastic.

- **Replacement:** The quick-connect fittings allow for easy replacement of the adapter if it becomes damaged or worn. Simply depress the collar on the quick-connect fitting to release the tubing, then install a new adapter.
- **Winterization (for RV/Trailer/Outdoor Use):** Before freezing temperatures, ensure the adapter and connected lines are drained of water to prevent damage from ice expansion.

8. TROUBLESHOOTING

Refer to the following common issues and solutions:

- **Leakage at Connections:**
 - Ensure tubing is fully inserted into the quick-connect fittings.
 - Check for damaged O-rings or seals within the quick-connect fittings.
 - Verify that the tubing itself is not damaged or cut unevenly.
- **No Water Flow:**
 - Confirm the blue shut-off lever is in the OPEN position (parallel to the adapter body).
 - Check the main water supply to ensure it is turned on.
 - Inspect for any blockages in the water line or adapter.

9. SPECIFICATIONS

Attribute	Specification
Model Number	C1381216WO6ITXAL
Brand	JOINPAYA
Material	Plastic
Color	Multi
Dimensions (L x W x H)	2.83 x 1.77 x 1.02 inches (7.20 x 4.50 x 2.60 cm)
Item Weight	1.28 ounces
Included Components	1 x RV Water Inlet Connection

10. WARRANTY INFORMATION

Please refer to the product packaging or contact JOINPAYA customer service for specific warranty details regarding this product. General warranty terms typically cover manufacturing defects for a limited period from the date of purchase.

11. SUPPORT

For further assistance, technical support, or inquiries regarding your JOINPAYA Quick Connect Water Fill Inlet Valve Adapter, please contact JOINPAYA customer service through their official website or the retailer from whom the product was purchased.

