

## GiveBest PT910EO

# GiveBest PT910EO 1500W Ceramic Space Heater Instruction Manual

Model: PT910EO | Brand: GiveBest

## INTRODUCTION

The GiveBest PT910EO Ceramic Space Heater is designed to provide efficient and comfortable warmth for indoor spaces. Featuring 1500W power and PTC ceramic heating technology, it offers rapid heating for areas up to 200 square feet. This portable heater includes a thermostat for precise temperature control, a remote for convenient operation, and a 70° oscillation function for wide heat distribution. Integrated safety features ensure reliable and secure use.

## IMPORTANT SAFETY INSTRUCTIONS

### READ ALL INSTRUCTIONS BEFORE USE.

- **DO NOT COVER:** Never cover the heater, as this can lead to overheating and fire hazards.
- **Placement:** Place the heater on a firm, level, open surface free from obstructions and at least 3 feet (0.9m) away from any combustible materials. Do not use on an unstable surface such as bedding or deep carpeting.
- **Power Connection:** Always plug the heater directly into a wall outlet. **DO NOT use with an extension cord**, power strip, or surge protector, as this can cause overheating and fire risk. Ensure your home receptacle's connections are suitable for a 1500-watt heater.
- **Tip-Over Protection:** The heater is equipped with an innovative tilt-detection sensor that automatically shuts off the unit if it is knocked over.
- **Overheat Protection:** Built-in overheat protection automatically turns off the heater if it reaches an unsafe temperature.
- **Child Lock:** Activate the child lock feature to prevent accidental changes to settings by children or pets.
- **Materials:** Constructed with V-0 flame retardant materials and features an ETL certified safety plug.
- **Cool Down Cycle:** After turning off, the heater will enter a cool-down cycle (typically 30 seconds) to dissipate residual heat before fully powering down.

## PACKAGE CONTENTS

- GiveBest PT910EO Ceramic Space Heater Unit
- Remote Control (requires 2x AAA batteries, not included)
- Instruction Manual

## PRODUCT OVERVIEW

The GiveBest PT910EO features a sleek, tower design with a durable metal mesh exterior. The top panel includes intuitive touch controls, and a digital display provides clear feedback on settings. A convenient handle is integrated for easy portability.



Figure 1: GiveBest PT910EO Ceramic Space Heater and Remote Control.

### Control Panel & Display

The top of the heater features touch-sensitive buttons for power, mode selection, temperature adjustment, oscillation, and timer. The front digital display shows the current temperature setting and active modes.

# Save Energy, Stay Comfortable

ECO mode keeps your perfect temperature

**ECO** ECO mode  
keeps temps just right



Figure 2: Close-up of the heater's top control panel and digital display.

## SETUP

1. Unpack the heater and all accessories from the box.
2. Remove any protective plastic films from the digital display and power plug.
3. Place the heater on a stable, flat surface, ensuring adequate clearance from walls and furniture (at least 3 feet).
4. Insert 2x AAA batteries into the remote control (batteries not included).

5. Plug the heater directly into a 120V 60Hz wall outlet. The unit will emit a beep and the display will show the current ambient temperature.

## OPERATING INSTRUCTIONS

---

### Power On/Off

Press the **Power Button** on the top panel or the 'ON/OFF' button on the remote to turn the heater on or enter standby mode.

### Mode Selection

Press the **Mode Button** (MOD on remote) repeatedly to cycle through the available modes:

- **Heat Mode:** Provides 1500W of ceramic heating.
- **ECO Mode:** Maintains a comfortable temperature while optimizing energy consumption.
- **Fan Mode:** Circulates cool air without heating.

### Temperature Control

In Heat or ECO mode, use the **Temperature +/- Buttons** on the top panel or remote to set your desired temperature. The temperature can be adjusted in 1°F increments from 41°F to 95°F.

# Your Ideal Temp, Effortlessly



Figure 3: The heater's digital display showing the adjustable temperature range.

## Oscillation Function

Press the **Oscillation Button** (OSC on remote) to activate the 70° wide-angle oscillation feature, distributing heat evenly across a larger area. Press again to pause oscillation.

# Smooth Comfort, Aerodynamic Elegance.



Figure 4: The heater's 70° oscillation feature in action.

## Timer Setting

Press the **Timer Button** (TIME on remote) to set an automatic shut-off timer from 1 to 12 hours. Each press increases the timer by one hour.

## Child Lock

To activate the child lock, press and hold the **Child Lock Button** on the top panel for a few seconds until 'LO' appears on the display. This disables all other buttons. To deactivate, press and hold the Child Lock Button again.

## MAINTENANCE

---

### Cleaning

- Always unplug the heater and allow it to cool completely before cleaning.
- Wipe the exterior with a soft, damp cloth. Do not use abrasive cleaners or solvents.
- The heater features a detachable filter for easy cleaning. Regularly clean the filter to maintain optimal performance.

### Storage

When not in use, store the heater in a cool, dry place, away from direct sunlight and out of reach of children.

## TROUBLESHOOTING

---

- **Heater not turning on:** Ensure the power cord is securely plugged into a functioning wall outlet. Check if the tip-over or overheat protection has been activated.
- **No heat output:** Verify that the heater is not in Fan Only mode. Adjust the temperature setting to a higher value than the ambient room temperature.
- **Heater shuts off unexpectedly:** This is likely due to the tip-over or overheat safety features. Ensure the heater is on a stable surface and not covered. Allow it to cool before restarting.
- **Remote not working:** Check and replace the AAA batteries in the remote control. Ensure there are no obstructions between the remote and the heater.

## SPECIFICATIONS

---

<b>Brand</b>	GiveBest
<b>Model Number</b>	PT910EO
<b>Power</b>	1500W
<b>Heating Technology</b>	PTC Ceramic
<b>Oscillation</b>	70°
<b>Temperature Range</b>	41°F - 95°F
<b>Timer</b>	1-12 Hours
<b>Safety Features</b>	Tip-Over Protection, Overheat Protection, V-0 Flame Retardant Materials, Safety Plug, ETL Certified
<b>Product Dimensions</b>	6.4"D x 6.4"W x 8.3"H
<b>Item Weight</b>	3.25 pounds

## WARRANTY AND SUPPORT

---

**One Year Limited Warranty:** This product is covered by a one-year limited warranty against defects in materials and workmanship under normal use. This warranty does not cover damage resulting from misuse, accident,

modification, or unauthorized attempts to repair.

**Customer Support:** If you experience any problems or have questions, please contact GiveBest customer service:

- **Email:** [support@givebest.com](mailto:support@givebest.com)
- **Phone:** US +1 (888) 550-1319 (Mon-Fri 8AM-10PM EST)