

[Manuals.plus](#) /

› [EASYWORC](#) /

› EASYWORC Frameless Pivot Shower Door 34-36 inch W x 72 inch H Instruction Manual

EASYWORC 34-36 inch W x 72 inch H

EASYWORC Frameless Pivot Shower Door

Model: 34-36 inch W x 72 inch H

Brand: EASYWORC

INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of your EASYWORC Frameless Pivot Shower Door. Designed for openings between 34 and 36 inches wide and 72 inches high, this shower door features a smooth pivot system, tempered glass with nano explosion-proof film, and a sleek matte black finish. Please read all instructions carefully before beginning installation to ensure a safe and successful setup.

KEY FEATURES

- **Perfect Fit:** Designed for compact openings from 34 to 36 inches wide, offering effortless swinging operation.
- **Advanced Easy-Clean & Safety Glass:** Crafted with 6mm clear tempered glass and an interior nano coating to prevent splintering and resist water spots. Certified by CPSC, ANSI, and SGCC for enhanced safety.
- **Elegant Frameless Design:** Features a sleek frameless pivot construction with a smudge-resistant matte black frame for a minimalist aesthetic.
- **Convenient Operation:** The hinged door opens outward smoothly up to 90 degrees and includes an interior mini-handle and an exterior 304 stainless steel towel bar.
- **Hassle-Free Installation:** Comes with detailed instructions and a video guide to facilitate quick DIY setup.

SETUP AND INSTALLATION

Careful preparation is crucial for a successful installation. Ensure you have all necessary tools and components before starting. This shower door is designed for reversible installation, allowing for left or right-hand operation.

Pre-Installation Steps

1. **Unpack and Inspect:** Carefully unpack all components and inspect for any damage or missing parts. Refer to the parts list provided in your packaging.
2. **Measure and Mark:** Use a level and tape measure to accurately mark the positions for the wall profiles. Ensure the shower base is level.

3. **Drill Pilot Holes:** Drill pilot holes at the marked locations for securing the wall profiles.

Installation Process

For a comprehensive visual guide, please refer to the official installation video below. The video demonstrates key steps such as securing wall profiles, installing the pivot mechanism, and attaching the glass panel and handle.

Your browser does not support the video tag. Please refer to the text instructions or contact support.

Video Description: This video provides a step-by-step guide for installing the EASYWORC Frameless Pivot Shower Door, demonstrating how to measure, drill, secure components, and assemble the door for proper function.

- **Wall Profile Installation:** Secure the wall profiles to the wall using appropriate fasteners. The design allows for a maximum adjustment of 1 inch on each side for a perfect fit.
- **Pivot Mechanism Assembly:** Install the bottom and top lifting shafts of the pivot mechanism. These components ensure smooth door operation and a secure seal when closed.
- **Glass Panel Placement:** Carefully place the tempered glass panel into the installed pivot mechanisms and wall profiles.
- **Handle and Towel Bar Attachment:** Install the laser-engraved stainless steel handle and towel bar onto the glass door.
- **Sealing:** Apply silicone sealant along the exterior joints of the wall profiles and the shower base to ensure a watertight installation.

Reversible Installation

Reversible for left or right hand operation



Image Description: This diagram illustrates the reversible installation feature, showing how the shower door can be configured to open from either the right or the left side to suit your bathroom layout.

Width Adjustable On Both Sides

A maximum adjustment of **1 inch** on each side



Image Description: This image highlights the width adjustable feature, demonstrating how the wall jamba allow for up to 1 inch of adjustment on each side to accommodate varying opening sizes.

OPERATING INSTRUCTIONS

Your EASYWORC Frameless Pivot Shower Door is designed for smooth and reliable operation.

- **Opening the Door:** Gently pull the exterior towel bar or push the interior mini-handle to open the door. The pivot mechanism allows the door to swing outward up to 90 degrees.
- **Closing the Door:** Push the door back into the closed position. The smart pivot system ensures the door lowers slightly to create a tight seal against the shower base and wall profile, preventing leaks.
- **Magnetic Seal:** The angled magnetic seal strip ensures superior water-tightness and a quiet closing action.

Smart Pivot for Shower Doors

— Smooth & Waterproof

Lifts to Open — Silent & Effortless

RAISE UP

Seals to Close — Perfect & Leak-Proof

LOWER
DOWN

Image Description: This diagram shows the 'Smart Pivot' mechanism, explaining how the door lifts to open silently and effortlessly, and lowers to close for a perfect, leak-proof seal.

Angled Magnetic Seal Strip

✓ Superior water-tightness

✓ Whisper-quiet closing

✓ Perfect alignment

✓ Seamless modern look




Image Description: A detailed view of the angled magnetic seal strip, highlighting its design for superior water-tightness, quiet closing, perfect alignment, and a seamless modern look.

Laser-Engraved Stainless Steel Handle

Textured for Grip. Designed for Elegance

Space-saving with an inner grab handle



Corrosion-resistant towel/clothes rack handle

Image Description: This image showcases the laser-engraved stainless steel handle, emphasizing its textured grip, elegant design, and corrosion-resistant towel/clothes rack functionality.

MAINTENANCE

Proper maintenance will ensure the longevity and pristine appearance of your shower door.

- **Easy-Clean Nano Coating:** The interior nano coating on the glass resists water spots, soap scum, and limescale buildup, making cleaning easier.
- **Regular Cleaning:** For best results, wipe down the glass and metal components after each use with a soft cloth or squeegee.
- **Deep Cleaning:** For occasional deep cleaning, use a mild, non-abrasive glass cleaner. Avoid harsh chemicals, abrasive pads, or scouring powders, as these can damage the nano coating and finish.
- **Frame Care:** Clean the matte black aluminum frame with a soft, damp cloth. Do not use abrasive cleaners or solvents.

PREMIUM NANO COATING



Image Description: This image illustrates the benefit of the premium nano coating, showing how it prevents stains and water spots, making the glass easy to clean compared to uncoated glass.

TROUBLESHOOTING

If you encounter any issues with your shower door, consider the following common solutions:

- **Water Leakage:** Check all silicone seals for gaps or cracks. Reapply sealant if necessary. Ensure the door is closing properly and the magnetic seal is fully engaging. Verify the bottom lifting shaft is correctly installed and adjusted.
- **Door Not Closing Smoothly:** Inspect the pivot hinges for any obstructions or debris. Ensure the door is properly aligned within the wall profiles.
- **Loose Handle/Towel Bar:** Tighten the screws on the handle and towel bar if they become loose. Do not overtighten.
- **Glass Safety:** The tempered glass includes an anti-explosion film. In the rare event of breakage, this film helps hold glass fragments together, reducing the risk of injury.

When Glass Breaks



Image Description: This image demonstrates the safety features of the glass, comparing how regular glass, tempered glass, and EASYWORC's anti-explosion film tempered glass break, highlighting the film's ability to contain fragments.

SPECIFICATIONS

Feature	Detail
Brand	EASYWORC
Model	Frameless Pivot Shower Door
Dimensions	34-36 inches W x 72 inches H
Walk-in Width	29 5/8 - 31 5/8 inches
Color	Matte Black
Material	Aluminum (Frame), Tempered Glass
Glass Thickness	1/4 inch (6mm)

Glass Features	Nano Coating, Explosion-Proof Film
Certifications	CPSC, ANSI, SGCC
Item Weight	57.32 Pounds
Style	Modern



Image Description: This diagram provides key product dimensions, including shower door width (34-36 inches), height (72 inches), walk-in width (29 5/8 - 31 5/8 inches), and glass thickness (1/4 inch).

WARRANTY AND SUPPORT

EASYWORC is committed to providing excellent customer service. If you encounter any issues or have questions regarding your shower door, please follow these steps:

- **Before Purchase:** For quick answers to inquiries or concerns, help with installation preparation, or product matching, please reach out.

- **After Purchase:** Find your shower door order in 'Your Orders' and click 'Contact Seller'. This will allow us to see your details and assist you promptly.
- **Describe the Issue:** Provide a detailed description of the problem, ideally with a couple of photos, to help us understand and act faster.
- **Resolution:** We aim to reply within 24 hours with a solution, which may include a fast, free replacement of damaged or missing parts. Most cases are fully resolved in just a few days.

Customer Support:

Phone: 1-888-998-5388 (Monday-Friday, 9 AM - 5 PM PST)

Online Customer Care: 7/24 availability