

[Manuals.plus](#) /

› [SPEDWHEEL](#) /

› SPEDWHEEL OUXI V8 E-Bike Front Disc Brake Caliper Instruction Manual

SPEDWHEEL V8

SPEDWHEEL OUXI V8 E-Bike Front Disc Brake Caliper

INSTRUCTION MANUAL

1. Introduction

This manual provides essential information for the proper installation, operation, and maintenance of your SPEDWHEEL OUXI V8 E-Bike Front Disc Brake Caliper. Please read these instructions carefully before installation and use to ensure safe and optimal performance. Retain this manual for future reference.

2. Product Overview and Components

The SPEDWHEEL OUXI V8 Front Disc Brake Caliper is designed for reliable braking performance on OUXI V8 electric bicycles. It includes the caliper body, brake pads, and mounting hardware.



Figure 1: Front view of the SPEDWHEEL OUXI V8 Disc Brake Caliper, showing the main body and included mounting bolts.



Figure 2: Bottom view of the caliper, highlighting the brake pads and their position within the caliper body.

3. Safety Information

- Always wear appropriate safety gear when working on or riding your e-bike.
- Ensure all bolts are tightened to the manufacturer's recommended torque specifications. Over-tightening or under-

tightening can lead to component failure.

- Brakes are critical safety components. If you are unsure about any installation or adjustment procedure, consult a qualified bicycle mechanic.
- Regularly inspect your brakes for wear and damage. Replace worn components immediately.
- Keep brake pads and rotors free from oil, grease, and other contaminants, as this will severely reduce braking performance.

4. Setup and Installation

This section outlines the general steps for installing the front disc brake caliper. Ensure your e-bike is stable and secure before beginning.

1. **Compatibility Check:** Before installation, verify that this caliper is compatible with your OUXI V8 electric bicycle's front fork and disc rotor. Refer to Figure 1 and Figure 2 for visual confirmation of the caliper design.
2. **Remove Old Caliper (if applicable):** If replacing an existing caliper, carefully remove the old unit by loosening the mounting bolts and detaching the brake cable.
3. **Mount New Caliper:** Position the new SPEDWHEEL OUXI V8 caliper onto the front fork's disc brake mount. Align the caliper so that the brake pads are centered over the disc rotor.
4. **Install Mounting Bolts:** Insert the provided mounting bolts through the caliper and into the fork mount. Hand-tighten them initially.
5. **Connect Brake Cable:** Attach the brake cable to the caliper's actuation arm. Ensure the cable is routed correctly and secured firmly.
6. **Adjust Caliper Position:** Loosen the mounting bolts slightly. Squeeze the brake lever firmly to center the caliper over the rotor. While holding the brake lever, tighten the mounting bolts evenly and securely. Release the brake lever and check for proper alignment.
7. **Adjust Brake Cable Tension:** Adjust the brake cable tension using the barrel adjuster on the brake lever or caliper to achieve the desired lever feel and pad engagement. Ensure there is no excessive slack and the pads are not rubbing the rotor when the lever is released.
8. **Final Check:** Spin the wheel to ensure the rotor spins freely without rubbing. Actuate the brake lever several times to confirm proper function and firm braking.

5. Operating Instructions

Once installed, proper operation involves understanding brake function and initial bedding-in.

- **Brake Lever Actuation:** Squeeze the front brake lever (typically on the left handlebar) to engage the front brake. Apply pressure gradually for controlled stopping.
- **Bedding-in New Pads:** New brake pads require a bedding-in period to achieve optimal performance. Ride at a moderate speed and apply the brakes firmly (but not to a complete stop) about 20-30 times. Allow the brakes to cool between applications. This process transfers pad material to the rotor, improving friction and reducing noise.

6. Maintenance

Regular maintenance ensures the longevity and safety of your brake caliper.

- **Regular Inspection:** Periodically check the brake pads for wear. Replace pads when the friction material is less than 1mm thick. Inspect the brake rotor for damage or excessive wear.
- **Cleaning:** Keep the caliper and rotor clean. Use a clean cloth and isopropyl alcohol to remove dirt, dust, and

contaminants. Avoid using harsh chemicals or oil-based cleaners.

- **Cable Inspection:** Check the brake cable for fraying, corrosion, or kinks. Replace damaged cables promptly. Ensure the cable moves freely within its housing.
- **Bolt Torque:** Periodically check that all mounting bolts are securely tightened.

7. Troubleshooting

- **Squealing Brakes:**
 - Ensure pads and rotor are clean and free of contaminants.
 - Re-bed the brake pads.
 - Check for proper caliper alignment.
- **Poor Braking Performance:**
 - Check brake pad wear; replace if necessary.
 - Ensure brake cable tension is adequate.
 - Verify pads and rotor are clean.
- **Brake Pads Rubbing Rotor:**
 - Re-align the caliper (refer to Section 4, Step 6).
 - Check for bent rotor.

8. Specifications

Brand	SPEDWHEL
Model Name	V8
Material	Iron
Color	Black
Item Package Dimensions (L x W x H)	4 x 4 x 2 inches
Package Weight	3.2 ounces
UPC	761850632215

9. Warranty and Support

For warranty information, please refer to the terms provided by your retailer or contact SPEDWHEL directly. For technical support or further assistance, please reach out to the manufacturer or your point of purchase.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question