

[manuals.plus](#) /› [GAOMON](#) /› [GAOMON 67-inch Acrylic Freestanding Bathtub Instruction Manual](#)**GAOMON ZBC-3IHQXEPDxx58JBofESKiggceB**

GAOMON 67-inch Acrylic Freestanding Bathtub Instruction Manual

Model: ZBC-3IHQXEPDxx58JBofESKiggceB

1. INTRODUCTION

Thank you for choosing the GAOMON 67-inch Acrylic Freestanding Bathtub. This manual provides essential information for the safe installation, operation, and maintenance of your new bathtub. Please read all instructions carefully before beginning installation or use to ensure proper function and longevity of the product. Keep this manual for future reference.

2. SAFETY INFORMATION

- Always read and understand all instructions before installation and use.
- Professional installation by a licensed plumber is highly recommended to ensure compliance with local codes and proper function.
- Ensure the floor structure can support the weight of the bathtub when filled with water and a person. Consult a structural engineer if unsure.
- Exercise caution when entering and exiting the bathtub. The non-slip surface provides traction, but wet surfaces can still be slippery.
- Test water temperature before entering the tub to prevent scalding.
- Do not use abrasive cleaners, harsh chemicals, or sharp objects on the bathtub surface, as this can damage the finish and compromise the non-slip properties.
- This bathtub is CUPC Certified, indicating compliance with North American plumbing standards.

3. PACKAGE CONTENTS

Verify that all components are present and undamaged before beginning installation. If any parts are missing or damaged, contact customer support immediately.

- Freestanding Bathtub (1 unit)
- Matte Drain Assembly (1 set)

- Overflow Assembly (1 set)
- Flexible Drain Hose (1 unit)
- Adjustable Leveling Feet (pre-installed or separate, verify upon unpacking)

4. SETUP AND INSTALLATION

This section outlines the general steps for installing your freestanding bathtub. Specific plumbing configurations may vary. Always consult a licensed plumber.

4.1 Pre-Installation Checklist

- Ensure the installation area is clean, level, and structurally sound.
- Confirm that hot and cold water supply lines and a drain pipe are correctly positioned according to local plumbing codes.
- Unpack the bathtub and inspect for any shipping damage.

4.2 Installation Steps

1. **Positioning the Bathtub:** Carefully move the bathtub to its desired location. Ensure there is adequate space around the tub for cleaning and maintenance.
2. **Adjusting Leveling Feet:** Use a level to ensure the bathtub is perfectly level. Adjust the leveling feet located on the bottom of the tub as needed. This is crucial for proper drainage and stability.
3. **Connecting Drain and Overflow:** Connect the flexible drain hose from the bathtub's drain assembly to your floor drain pipe. Ensure all connections are secure and watertight. Install the overflow assembly according to the manufacturer's instructions, ensuring a tight seal.
4. **Water Test:** Fill the bathtub with water and let it sit for at least 10 minutes. Carefully inspect all drain and overflow connections for any leaks. Drain the tub and re-inspect. Address any leaks immediately before proceeding.
5. **Sealing (Optional but Recommended):** Apply a bead of silicone sealant around the base of the bathtub where it meets the floor. This helps prevent water from seeping underneath and provides additional stability. Allow the sealant to cure completely before use.



Image 1: GAOMON 67-inch Acrylic Freestanding Bathtub. This image shows the overall design of the bathtub, highlighting its modern aesthetic and ribbed exterior.

5. OPERATING INSTRUCTIONS

- **Filling the Bathtub:** Ensure the drain stopper is closed. Turn on the water supply to fill the tub to your desired level. Always check the water temperature before entering.
- **Soaking Experience:** The ergonomic deep design and integrated lumbar support are crafted for comfort. The double-walled insulation helps maintain water temperature for extended soaking periods.
- **Draining the Bathtub:** Open the drain stopper to allow water to flow out. The matte drain and overflow system are designed for efficient water removal.

6. MAINTENANCE

Regular cleaning and proper care will preserve the appearance and functionality of your bathtub.

- **Cleaning the Surface:** Clean the bathtub regularly with a soft cloth or sponge and a mild, non-abrasive bathroom cleaner. Rinse thoroughly with clean water after cleaning.
- **Avoiding Damage:** Do not use abrasive powders, scouring pads, steel wool, or cleaners containing

ammonia, bleach, or harsh acids, as these can scratch or dull the acrylic finish and damage the non-slip surface.

- **Drain Maintenance:** Periodically remove and clean the drain stopper to prevent hair and debris buildup, which can cause slow drainage.
- **Non-Slip Surface:** The integrated non-slip surface requires no special treatment beyond regular cleaning. Avoid applying waxes or polishes that could reduce its effectiveness.

7. TROUBLESHOOTING

Refer to this section for solutions to common issues. For problems not listed here, contact customer support or a qualified professional.

Problem	Possible Cause	Solution
Slow Drainage	Hair or debris in drain; improper drain connection.	Clean drain stopper and trap. Check drain hose for kinks or blockages. Ensure proper slope of drain pipe.
Leaks around drain/overflow	Loose connections; damaged seals.	Tighten all drain and overflow connections. Inspect and replace any damaged gaskets or seals. Reapply plumber's putty or silicone sealant if necessary.
Bathtub is unstable/wobbles	Uneven floor; leveling feet not properly adjusted.	Adjust the leveling feet until the bathtub is stable and level on all sides. Ensure the floor is capable of supporting the tub's weight.
Water temperature not maintained	External factors; extreme room temperature.	The double-walled insulation is designed to retain heat. Ensure the bathroom is not excessively cold. This is a passive insulation system, not an active heater.

8. SPECIFICATIONS

Feature	Detail
Model Number	ZBC-3IHQXEPDxx58JBofESKiggceB
Dimensions (L x W x H)	66.54 x 31.5 x 23.62 inches (169 x 80 x 60 cm)
Item Weight (Empty)	113.8 pounds (51.6 kg)
Material	Acrylic
Color	White
Drain Type	Matte Drain and Overflow
Certifications	CUPC Certified
Insulation	Double-Walled Construction
Special Features	Ergonomic Deep Design, Slip-Resistant Surface, Adjustable Leveling Feet

9. WARRANTY AND SUPPORT

For warranty information, please refer to the documentation provided at the time of purchase or contact GAOMON customer support directly. If you encounter any issues or require assistance with your bathtub, please reach out to our customer service team. Provide your model number and purchase date for faster service.

Manufacturer: GAOMON

Contact Information: Please refer to your purchase receipt or the official GAOMON website for the most current customer support contact details.