

[Manuals.plus](#) /

› [Lylting](#) /

› Lylting M085 Rechargeable LED Flashlight Instruction Manual

Lylting M085

Lylting M085 Rechargeable LED Flashlight Instruction Manual

Model: M085

INTRODUCTION

Thank you for choosing the Lylting M085 Rechargeable LED Flashlight. This manual provides detailed instructions for the safe and efficient use, setup, operation, and maintenance of your new flashlight. Please read this manual thoroughly before using the product and retain it for future reference.

WHAT'S IN THE BOX

Your Lylting M085 flashlight package includes the following items:

- 2x Lylting M085 Flashlights
- 2x Rechargeable Batteries (pre-installed or separate)
- 2x USB Charging Cables
- 2x Lanyards
- 1x User Manual
- 1x Storage Box



Image: Contents of the Lyting M085 flashlight package.

PRODUCT OVERVIEW

The Lyting M085 flashlight is designed for durability and high performance, featuring a robust aluminum alloy body and advanced LED technology. Key components and features are highlighted below:

- **Ultra-bright P50 LED Chip:** Provides 99,000 lumens of illumination.
- **Adjustable Focus (Zoomable):** Easily switch between floodlight and spotlight by pushing/pulling the light head.
- **5 Lighting Modes:** High, Medium, Low, Strobe, and SOS for various situations.
- **Rechargeable Battery:** Equipped with a 5000mAh rechargeable battery, offering up to 15 hours of use.
- **4-Level Power Indicator:** Displays battery status (25%, 50%, 75%, 100%).
- **USB-C Input Port:** For convenient and fast charging.
- **IPX6 Water-Resistant:** Designed to withstand splashes and rain.
- **Drop-Proof:** Constructed from aircraft-grade aluminum alloy for durability.
- **Safety Hammer Feature:** The front bezel can be used as a safety hammer in emergencies.

ADJUSTABLE FUNCTION



Image: Lytting M085 Flashlight Components.

SETUP

Initial Charging

1. Locate the USB-C input port on the side of the flashlight, usually protected by a rubber cover.
2. Open the rubber cover to expose the charging port.
3. Connect one end of the provided USB charging cable to the flashlight's USB-C port.
4. Connect the other end of the USB cable to a compatible USB power source (e.g., wall adapter, computer, power bank).
5. The 4-level power indicator lights will illuminate to show the charging progress. A full charge typically takes approximately 3 hours.
6. Once fully charged, all four indicator lights will be solid. Disconnect the charging cable and securely close the rubber cover to maintain water resistance.



Image: Charging port and power display on the Lylting M085 flashlight.

OPERATING INSTRUCTIONS

Power On/Off and Mode Selection

1. To turn the flashlight **ON**, press the power switch button located on the side of the flashlight.
2. Each subsequent press of the power switch will cycle through the 5 lighting modes in the following order: **High** → **Medium** → **Low** → **Strobe** → **SOS**
3. To turn the flashlight **OFF**, press and hold the power switch for approximately 2 seconds, or cycle through all modes until the light turns off.

ADVANCED COMPONENTS



Image: Demonstration of the 5 lighting modes.

Adjustable Focus (Zoom Function)

The Lyting M085 features an adjustable focus to switch between a wide floodlight and a concentrated spotlight beam:

- To achieve a **floodlight** (wide beam), gently pull the head of the flashlight outwards.
- To achieve a **spotlight** (narrow, focused beam), gently push the head of the flashlight inwards.

5 LIGHTING MODES



HIGH



MEDIUM



LOW



STROBE



SOS

Image: Adjustable focus (floodlight and spotlight).

Battery Level Indicator

The flashlight is equipped with a 4-level LED power indicator to show the remaining battery charge:

- **4 Blue Lights:** 75-100% charge
- **3 Blue Lights:** 50-75% charge
- **2 Blue Lights:** 25-50% charge
- **1 Blue Light:** Below 25% charge (recharge recommended)

Official Product Video: Features Overview

Your browser does not support the video tag.

Video: This official product video demonstrates the Lytting M085 flashlight's super bright output, adjustable focus, multiple lighting modes, USB fast charging, power display, IPX6 waterproof rating, and anti-fall durability.

MAINTENANCE

- **Cleaning:** Wipe the flashlight body with a soft, damp cloth. Do not use abrasive cleaners or solvents.
- **Water Resistance:** Ensure the USB-C port's rubber cover is securely closed to maintain the IPX6 water-resistant rating. Avoid submerging the flashlight in water.

- **Storage:** Store the flashlight in a cool, dry place away from direct sunlight and extreme temperatures. For long-term storage, charge the battery to approximately 50% every 3-6 months to prolong battery life.
- **Battery Care:** Use only the provided USB charging cable. Do not attempt to open or replace the built-in rechargeable battery.



Image: Lytting M085 Flashlight demonstrating IPX6 water resistance.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Flashlight does not turn on.	Low or depleted battery.	Charge the flashlight using the provided USB cable. Check the power indicator lights.
Flashlight does not charge.	Faulty cable or power source; charging port obstruction.	Try a different USB cable or power source. Ensure the charging port is clean and free of debris.

Problem	Possible Cause	Solution
Light output is dim or inconsistent.	Low battery; lens is dirty.	Recharge the battery. Clean the lens with a soft cloth.
Flashlight cannot be turned off.	Internal switch malfunction.	Press and hold the power button for an extended period (5-10 seconds). If the issue persists, contact customer support.

SPECIFICATIONS

Model Number:

M085

Light Source Type:

LED (P50 Chip)

White Brightness:

99,000 Lumens

Illumination Distance:

Up to 3,280 feet

Power Source:

Battery Powered

Battery Type:

5000mAh Rechargeable NiCAD Battery

Charging Time:

Approximately 3 hours

Run Time:

Up to 15 hours (depending on mode)

Lighting Modes:

High, Medium, Low, Strobe, SOS

Special Features:

Adjustable Focus (Zoomable), 4-Level Power Indicator, Safety Hammer, IPX6 Water-Resistant, Drop-Proof

Material:

Aircraft-grade Aluminum Alloy

Product Dimensions:

0.1"D x 0.1"W x 0.1"H

Item Weight:

1.12 pounds

WARRANTY & SUPPORT

Lylting provides a **2-year free replacement service** for this product. For any questions, concerns, or support needs, please do not hesitate to contact our customer service team. We are available 7 days a week, 24 hours a day, to assist you. Please refer to your purchase documentation or the Lylting official website for specific contact information.

