

[Manuals.plus](#) /

› [FEIYUE](#) /

› FEIYUE FY503 Serger Overlock Machine User Manual

FEIYUE FY503

FEIYUE FY503 Serger Overlock Machine User Manual

Model: FY503

1. INTRODUCTION AND OVERVIEW

This manual provides instructions for the operation and maintenance of your FEIYUE FY503 Serger Overlock Machine. The FY503 is designed for household sewing tasks, offering versatile stitching capabilities for various fabric types.

Key features include 2/3/4-thread capability, a built-in rolled hem function, adjustable differential feed, and an integrated cutting system. The machine is built with a durable metal frame and operates at up to 1100 stitches per minute (SPM).

FEIYUE



2/3/4 THREAD CAPABILITY

This machine is capable of producing various types of stitches according to the combination of needle positions




Figure 1.1: Overview of the FEIYUE FY503 Serger Overlock Machine. This image displays the machine's overall design, including the thread stand and main body.

HEAVY DUTY SERGER FOR HOME USE

FEIYUE | FY503

2/3/4 - Thread Capability

Differential Feed

Color-Coded Threading Guide

Removable Extension Table

Up to 1100 Stitches Per Minute

Adjustable Stitch Length & Cutting Width



SUITABLE FOR A WIDE RANGE OF FABRICS



Figure 1.2: Key features of the FY503 Serger. This image highlights the 2/3/4-thread capability, differential feed, color-coded threading guide, removable extension table, 1100 SPM, and adjustable stitch length and cutting width.

Your browser does not support the video tag.

Video 1.1: Demonstration of the FEIYUE FY503 Serger Overlock Machine. This video provides a visual overview of the machine's functions and capabilities.

2. SETUP

2.1 Unpacking and Placement

Carefully remove the machine from its packaging. Place the serger on a stable, flat surface with adequate lighting. Ensure there is enough space around the machine for fabric handling and comfortable operation.

2.2 Power Connection

Connect the power cord to the machine and then to a standard 120V electrical outlet. Ensure the power switch is in the "OFF" position before connecting.

2.3 Threading the Machine

The FEIYUE FY503 features a color-coded threading system for ease of use. Follow the numbered and color-coded guides printed on the machine to correctly thread each of the 2, 3, or 4 threads. Refer to the detailed threading diagram below.



Figure 2.1: User-Friendly Threading System. This image illustrates the color-coded threading paths and independent tension dials, providing clear reference points for setting up the machine.

2.4 Needle Installation

Ensure needles are correctly inserted and secured. The machine supports multiple needle positions for different stitch types. Refer to the diagram for proper needle orientation.



Figure 2.2: Close-up view of the serger needles. This image shows the needle area, indicating where needles are inserted and their typical arrangement.

3. OPERATING INSTRUCTIONS

3.1 Selecting Stitch Type

The FY503 offers 2, 3, and 4-thread overlock capabilities. The type of stitch is determined by the number of threads used and needle positions. Common stitch types include:

- **2-Thread Wrapped Edge Overlock:** For fine finishes on delicate fabrics.
- **2-Thread Standard Rolled Hem:** Ideal for decorative edges on lightweight fabrics.
- **3-Thread Overlock:** A common stitch for general seaming and finishing.
- **3-Thread Wrapped Edge Overlock:** Provides a secure and neat finish.

- **3-Thread Flatlock:** Creates decorative seams that lie flat.
- **4-Thread Stretch Mock Safety Stitch:** Strong and flexible, suitable for knits and stretch fabrics.

MULTIFUNCTIONAL SERGER MACHINE

FEIYUE | FY503




Figure 3.1: Examples of stitch types. This image demonstrates various stitches achievable with 2, 3, and 4 threads, including wrapped edge overlock, rolled hem, standard overlock, flatlock, and stretch mock safety stitch.

3.2 Adjusting Differential Feed

The adjustable differential feed system helps manage fabric stretching or gathering. Adjust the differential feed dial to prevent wavy seams on knits or puckering on fine fabrics. A setting of 1.0 is neutral. Settings above 1.0 will gather fabric, while settings below 1.0 will stretch it.




Figure 3.2: Differential Feed Control. This image shows the dial used to adjust the differential feed, which helps control fabric movement to prevent stretching or puckering.

3.3 Adjusting Stitch Length and Cutting Width

Use the stitch length dial to adjust the density of your stitches. The cutting width can be adjusted to trim fabric edges precisely, ensuring clean and even seams. Experiment with scrap fabric to find the optimal settings for your project.



Figure 3.3: Stitch Length Adjustment. This image displays the dial for controlling stitch length, which affects stitch density.



Figure 3.4: Cutting Width Adjustment. This image shows the lever used to adjust the cutting width, allowing for precise trimming of fabric edges.




Figure 3.5: Rolled Hem Standard Selector. This switch allows for quick selection between standard overlock and rolled hem functions.

3.4 Integrated Cutting System

The machine features a built-in movable upper knife and stationary lower knife that trim fabric edges as you sew. This creates clean, professional-looking seams. Ensure the knives are sharp and properly aligned for optimal performance.



Figure 3.6: User operating the FEIYUE FY503 Serger. This image shows a person using the machine to sew fabric, demonstrating its practical application.

4. MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your serger machine.

4.1 Cleaning

- Always unplug the machine before cleaning.
- Use a small brush to remove lint and dust from the looper area, feed dogs, and around the needles.
- Wipe the exterior surfaces with a soft, dry cloth. Avoid using harsh chemicals.

4.2 Oiling

Refer to your machine's specific oiling points in the full manual. Generally, a few drops of sewing machine oil should be applied to moving metal parts periodically to ensure smooth operation.

4.3 Needle and Knife Replacement

Replace needles regularly, especially if they become bent or dull, to prevent skipped stitches and fabric damage. The cutting knives may also need replacement if they become dull and no longer cut fabric cleanly.

4.4 Ventilation

The machine is equipped with ventilation for heat dissipation. Ensure these vents are not blocked during operation to prevent overheating.



Figure 4.1: Ventilation for Heat Dissipation. This image shows the ventilation grilles on the machine, designed to prevent overheating during extended use.

5. TROUBLESHOOTING

This section addresses common issues you might encounter with your FEIYUE FY503 serger. For more complex problems, consult a qualified technician.

5.1 Skipped Stitches

- **Cause:** Bent or dull needle, incorrect needle insertion, improper threading, incorrect tension.
- **Solution:** Replace the needle, re-insert correctly, re-thread the machine carefully following color codes, adjust tension dials.

5.2 Fabric Puckering or Wavy Seams

- **Cause:** Incorrect differential feed setting, improper tension, dull knives.
- **Solution:** Adjust the differential feed dial (increase for wavy seams, decrease for puckering), check and adjust thread tension, ensure knives are sharp.

5.3 Thread Breakage

- **Cause:** Incorrect threading, too much tension, poor quality thread, burrs on thread path, bent needle.
- **Solution:** Re-thread the machine, reduce tension, use good quality thread, check thread path for obstructions, replace needle.

5.4 Machine Not Feeding Fabric

- **Cause:** Presser foot not lowered, feed dogs disengaged, lint buildup in feed dogs.
- **Solution:** Lower the presser foot, ensure feed dogs are engaged, clean feed dog area.

6. SPECIFICATIONS

Feature	Detail
Brand	FEIYUE
Model Number	FY503
Thread Capability	2/3/4-Thread
Stitches Per Minute (SPM)	Up to 1100
Power Source	Corded Electric
Input Voltage	120 Volts
Material	Metal, Plastic
Product Dimensions (D x W x H)	11.92"D x 13.89"W x 10.62"H
Item Weight	13.6 Pounds
Included Components	Embroiderer Plate (Note: This might be a specific accessory. Refer to actual product contents.)

7. WARRANTY AND SUPPORT

For warranty information and technical support, please contact the manufacturer, FEIYUE, or the authorized seller from whom you purchased the machine. Keep your proof of purchase for warranty claims.

For further assistance, refer to the official FEIYUE website or contact their customer service department. Contact details are typically provided in the product packaging or on the manufacturer's website.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B0FRF23SMQ>

More documents and user manuals: **<https://manuals.plus/>**