

[Manuals.plus](#) /

› [Weitieke](#) /

› Weitieke Heat Gun RSG-3000A User Manual: Dual Temperature Control with 5 Accessories

Weitieke rsg-3000A

Weitieke Heat Gun RSG-3000A User Manual

Model: RSG-3000A | Brand: Weitieke

INTRODUCTION

Thank you for choosing the Weitieke Heat Gun RSG-3000A. This heavy-duty hot air gun is designed for a variety of tasks including paint stripping, crafting, vinyl wrap application, and heat shrink tubing. It features dual temperature control, fast heating, and multiple safety features to ensure efficient and safe operation. Please read this manual thoroughly before use to ensure proper operation and maintenance.

IMPORTANT SAFETY INSTRUCTIONS

WARNING: Read all safety warnings and instructions. Failure to follow the warnings and instructions may result in electric shock, fire, and/or serious injury.

- Always wear appropriate personal protective equipment, including safety glasses and gloves.
- Do not direct the hot air stream at people or animals.
- Do not use the heat gun near flammable materials or gases.
- Ensure adequate ventilation when working, especially when removing paint, as fumes can be toxic.
- Allow the heat gun to cool down completely before storing.
- Do not block the air intake or outlet nozzles.
- Keep children and bystanders away while operating the tool.
- The nozzle and accessories become very hot during use and remain hot for a period after use. Handle with care.
- This appliance has a polarized plug (one blade is wider than the other). To reduce the risk of electric shock, this plug is intended to fit in a polarized outlet only one way. If the plug does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified electrician. Do not modify the plug in any way.

SAFE & RELIABLE



Figure 1: Internal components highlighting safety features like double heating wires and overload protection.

PRODUCT OVERVIEW

Components and Features

The Weitieke Heat Gun RSG-3000A is designed for ease of use and durability. Key components and features include:

- **Hot Air Nozzle:** Directs the heated airflow.
- **Thickened Anti-Scalding Sheath:** Provides protection against accidental contact with hot surfaces.
- **Airflow Speed Switch:** Controls the fan speed and temperature settings (Low/High).
- **Hand Protection:** Ergonomically designed handle for comfortable and secure grip.
- **Hands-Free Stand:** Integrated stand for stable, hands-free operation.
- **UL-Certified Power Cord (10ft):** Long, durable power cord for extended reach and safety.
- **Overload Protection:** Automatically shuts off the unit if it overheats to prevent damage.
- **Dual Heating Wires:** Ensures rapid and consistent heating.



Figure 2: Detailed view of the heat gun and its accessories, including the 4 nozzles and paint scraper.

Included Accessories

Your Weitieke Heat Gun RSG-3000A comes with 5 essential accessories:

- **Reflector Nozzle:** For wrapping around pipes or soldering.
- **Concentrator Nozzle:** For directing heat to a specific area.
- **Deflector Nozzle:** For protecting glass or other heat-sensitive surfaces.
- **Additional Nozzle:** A general-purpose nozzle for various tasks.
- **Paint Scraper:** For assisting in paint removal.



Figure 3: Examples of applications using the included nozzles.

SETUP

1. **Unpacking:** Carefully remove the heat gun and all accessories from the packaging. Inspect for any damage.
2. **Nozzle Attachment:** Select the appropriate nozzle for your task. Align the nozzle with the heat gun's outlet and push it firmly into place. Ensure it is securely attached before operation.
3. **Power Connection:** Plug the 10-foot power cord into a standard electrical outlet. Ensure the outlet matches the voltage requirements of the heat gun (120V AC).
4. **Work Area Preparation:** Ensure your work area is clean, well-ventilated, and free from flammable materials. Secure any loose items that could be blown around by the airflow.



Figure 4: The 10-foot UL-certified power cord provides ample reach.

OPERATING INSTRUCTIONS

Powering On and Temperature Control

1. **Select Temperature/Airflow:** The heat gun features a two-level switch for temperature and airflow control.
 - **Setting I (Low):** Provides a temperature range of 0~572°F (250 L/MIN airflow). Ideal for delicate tasks like phone repair, candle making, and precision crafts.
 - **Setting II (High):** Provides a temperature range of 572~1112°F (500 L/MIN airflow). Suitable for high-heat jobs such as paint removal, heat shrink tubing, and heavy-duty tasks.
2. **Turn On:** Slide the power switch to the desired setting (I or II). The heat gun will begin to heat up rapidly (approximately 1.5 seconds).
3. **Adjusting Temperature (if applicable):** For models with a stepless temperature adjustment knob, rotate the knob to fine-tune the temperature within the selected range.
4. **Hands-Free Operation:** Utilize the integrated hands-free stand by placing the heat gun on a stable, heat-resistant surface. This allows for greater control and safety during certain applications.

Your browser does not support the video tag.

Video 1: Demonstration of the Weiteke Heat Gun's dual temperature settings and rapid heating capability.

Applications

- **Paint Stripping:** Apply heat evenly to the painted surface. Once the paint softens and bubbles, use the included paint scraper to remove it.
- **Heat Shrink Tubing:** Place the heat shrink tubing over the wire or connection. Apply heat evenly around the tubing until it shrinks tightly.
- **Vinyl Wrap Application:** Use low heat to make vinyl more pliable for stretching and conforming to surfaces.
- **Crafting:** Ideal for embossing, drying paint, or softening materials for various craft projects.
- **Soldering/Brazing:** With appropriate nozzles, the heat gun can be used for light soldering or brazing tasks.



Figure 5: Using the heat gun for paint removal.



Figure 6: Applying heat shrink tubing with the heat gun.

MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your heat gun.

- **Cleaning:** After each use, ensure the heat gun is unplugged and completely cooled. Wipe the exterior with a damp cloth. Do not use abrasive cleaners or solvents.
- **Air Vents:** Keep the air intake and outlet vents clear of dust and debris. Use a soft brush or compressed air to clean them if necessary. Blocked vents can lead to overheating.
- **Cord Inspection:** Regularly inspect the power cord for any signs of damage, cuts, or fraying. If damaged, have it replaced by a qualified technician.
- **Storage:** Store the heat gun in a dry, safe place, out of reach of children. Ensure it is cool before storing. The compact design allows for easy storage.

Compact Design

Small in size, easy to carry and store




Figure 7: The heat gun's compact design facilitates easy storage.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Heat gun does not turn on.	No power supply. Power switch is off. Damaged power cord.	Check if the plug is securely inserted into a working outlet. Ensure the power switch is set to I or II. Inspect the power cord for damage. If damaged, do not use and contact customer support.
Heat gun stops working during use.	Overload protection activated. Blocked air vents.	Turn off the heat gun, unplug it, and allow it to cool down for at least 15-20 minutes. Clear any obstructions from the air vents. Restart the unit.

Problem	Possible Cause	Solution
Insufficient heat output.	Incorrect temperature setting. Distance from workpiece too far.	Ensure the switch is on Setting II for higher temperatures. Reduce the distance between the nozzle and the workpiece.
Excessive sparking from motor.	Normal wear of carbon brushes (if applicable). Internal fault.	Minor sparking is normal. If sparking is excessive or accompanied by smoke/smell, discontinue use and contact customer support.

SPECIFICATIONS

Model Number	RSG-3000A
Brand	Weitieke
Power Source	AC
Wattage	1600 watts
Temperature Settings	Dual Temperature Control: Setting I: 0~572°F (250 L/MIN) Setting II: 572~1112°F (500 L/MIN)
Power Cord Length	10 feet (3.0 meters)
Item Weight	9.6 ounces (approx. 272 grams)
Product Dimensions	9.4 x 2.4 x 10.24 inches (approx. 23.9 x 6.1 x 26 cm)
Included Components	Heat Gun, 4 Nozzles (Reflector, Concentrator, Deflector, General Purpose), 1 Paint Scraper

WARRANTY AND SUPPORT

Weitieke products are manufactured to high-quality standards. For warranty information, technical support, or service inquiries, please contact Weitieke customer service through the retailer where the product was purchased or visit the official Weitieke website. Please retain your proof of purchase for warranty claims.

Contact Information: Refer to your purchase documentation or the Weitieke brand store on Amazon for the most current support details.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B0G28BVVGW>

More documents and user manuals: **<https://manuals.plus/>**