

Zeltrivonex VTS10-SLTgao

Zeltrivonex Black Tall Basin Faucet Instruction Manual

Model: VTS10-SLTgao

INTRODUCTION

Thank you for choosing the Zeltrivonex Black Tall Basin Faucet. This manual provides essential information for the safe installation, operation, and maintenance of your new faucet. Please read these instructions carefully before installation and retain them for future reference.

SAFETY INFORMATION

- Always turn off the main water supply before beginning any installation or maintenance.
- Ensure all connections are secure to prevent leaks.
- If you are unsure about any part of the installation, consult a qualified plumber.
- Do not use abrasive cleaners or harsh chemicals on the faucet's finish.

PRODUCT FEATURES

- **Stainless Steel Body with Matte Black Finish:** Constructed from high-quality stainless steel with a matte black finish, designed to resist fingerprints and simplify cleaning.
- **Tall Design for Countertop Basins:** With a total height of approximately 290 mm and a spout height of 200 mm, this faucet is ideal for countertop basins without a faucet hole, providing ample clearance.
- **Single Lever Mixer:** Easy control of water flow and temperature (hot and cold) with a single lever for comfortable use.
- **Durable Components:** Equipped with long-lasting components and a brass locking nut for stable and secure mounting on standard sink plates.
- **80 cm Connection Hose:** Includes an 80 cm connection hose with a standard EU fitting for quick and reliable installation.
- **Lead-Free Water:** Designed to provide clean, lead-free water.
- **Durable Ceramic Valve:** Features a leak-resistant ceramic valve for long-term performance.
- **High-Quality Hose:** Heat and scale resistant hose for enhanced durability.



Image: Key product features including no-splash spout, metal fittings, and water-saving design.



Image: The faucet is designed to provide clean, lead-free water.



Image: Detailed view of the single-hand control, durable ceramic valve, and high-quality, heat-resistant hose.

PRODUCT DIMENSIONS

Understanding the dimensions of your faucet is crucial for proper installation and compatibility with your basin.



Image: Comprehensive diagram illustrating all key dimensions of the faucet and its components, including an 80cm connection hose, 29cm total height, and 20cm spout height.

- Total Height: Approximately 29 cm (11.4 inches)
- Spout Height: Approximately 20 cm (8.7 inches)
- Spout Reach: Approximately 15 cm (5.9 inches)
- Base Width: Approximately 11 cm (4.3 inches)
- Connection Hose Length: 80 cm (31 inches)

SETUP AND INSTALLATION

This faucet is designed for single-hole installation, particularly suitable for countertop basins without a pre-drilled faucet hole. Ensure you have all necessary tools before starting.

Tools Required (Not Included):

- Adjustable wrench
- Screwdriver
- Sealant tape (Teflon tape)
- Basin wrench (optional, for tight spaces)

Installation Steps:

1. **Prepare the Basin:** Ensure the mounting surface of your countertop basin is clean and dry.
2. **Insert Faucet:** Place the faucet body into the single mounting hole on your basin.
3. **Secure Faucet:** From underneath the basin, slide the rubber washer, metal washer, and brass locking nut onto the threaded shank of the faucet. Tighten the brass locking nut securely using an adjustable wrench to ensure a stable mount.
4. **Connect Water Hoses:** Attach the hot and cold water supply lines (80 cm hoses included) to the corresponding inlets on the faucet. The hot water inlet is typically on the left, and cold on the right. Use sealant tape on the threads for a watertight seal.
5. **Connect to Water Supply:** Connect the other ends of the supply lines to your hot and cold water supply valves. Tighten connections firmly but do not overtighten.
6. **Test for Leaks:** Slowly turn on the main water supply and check all connections for leaks. If any leaks are detected, tighten the connections further.

7. **Flush the Faucet:** Remove the aerator from the spout and turn on both hot and cold water for a few minutes to flush out any debris from the lines. Reinstall the aerator.



Image: Visual guide detailing the installation process, from inserting the faucet to securing it with washers and nuts, and connecting the water supply hoses.



Image: Illustration demonstrating that the faucet is designed to fit above-counter basins, showing compatible and incompatible basin types.

OPERATING INSTRUCTIONS

The Zeltrivonex faucet features a single lever for convenient control of water flow and temperature.

- **Turning On/Off:** Lift the lever upwards to turn on the water. Push the lever downwards to turn off the water.
- **Adjusting Water Flow:** The further you lift the lever, the greater the water flow.
- **Adjusting Temperature:**
 - Move the lever to the left for hot water.
 - Move the lever to the right for cold water.
 - Position the lever in the middle for mixed (lukewarm) water.



Image: Illustration of the ergonomic handle's function, indicating that moving the lever left provides hot water and moving it right provides cold water.

CARE AND MAINTENANCE

Proper care will ensure the longevity and appearance of your Zeltrivonex faucet.

- **Cleaning the Finish:** Clean the faucet regularly with a soft cloth and mild soap or a non-abrasive liquid cleaner. Rinse thoroughly with water and dry with a soft cloth to prevent water spots.
- **Avoid Harsh Cleaners:** Do not use abrasive cleaners, scouring pads, ammonia-based cleaners, bleach, or other harsh chemicals, as these can damage the matte black finish.
- **Aerator Maintenance:** Periodically unscrew the aerator from the spout and clean any mineral deposits or debris that may have accumulated. This helps maintain optimal water flow.
- **Check for Leaks:** Occasionally inspect the connections under the sink for any signs of leaks. Tighten if necessary.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator; partially closed shut-off valve; debris in supply lines.	Clean or replace aerator; fully open shut-off valves; flush supply lines.
Leaking from Spout	Worn ceramic cartridge.	Replace the ceramic cartridge.
Leaking from Base	Loose mounting nut; damaged O-rings.	Tighten mounting nut; inspect and replace O-rings if damaged.

Problem	Possible Cause	Solution
Water Temperature Issues	Incorrect hot/cold supply connections; issues with water heater.	Verify hot and cold supply line connections; check water heater settings.

SPECIFICATIONS

Brand	Zeltrivonex
Model Name	CHR07-shuilongt-251210
Model Number	VTS10-SLTgao
Material	Stainless Steel (Body), Brass (Handle, Locking Nut)
Finish	Matte Black
Color	Black
Mounting Type	Freestanding, Single-Hole Installation
Number of Handles	1 (Single Lever)
Spout Design	Tall
Recommended Use	Bathroom Basin
Item Dimensions (L x W x H)	29 cm x 11 cm x 15 cm (approx.)
Connection Hose Length	80 cm
GTIN	717639559761
UPC	717639559761

WARRANTY INFORMATION

Specific warranty details are not provided in the product information. Please refer to your purchase documentation or contact the seller for warranty terms and conditions.

CUSTOMER SUPPORT

For technical assistance, replacement parts, or any questions regarding your Zeltrivonex faucet, please contact your retailer or the manufacturer directly. Please have your model number (VTS10-SLTgao) and purchase date available when contacting support.

Seller: Versstas Trade Limited
Seller ID: A10K2ZK4X01VGO

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question