



8840 SINGLE BOARD PROCESSOR

Contents [[hide](#)]

[1 OVERVIEW](#)

[2 FEATURES](#)

[3 TECHNICAL SPECIFICATIONS](#)

[4 Documents / Resources](#)

[4.1 References](#)

OVERVIEW

The VMAX 8840, is an XT single board computer with solid state disk emulation, as well as serial/parallel port capabilities. The 8840's integral solid state disks(s) utilize up to 1Meg of non-volatile memory. The disk access is many times faster than hard drive access and the disk may be bootable. Up to 2 drives may be emulated. Completely MS/DOS compatible, the 8840 can be used in conjunction with floppy and hard disks as needed. The WatchDog Timer resets the card in the event your application software should stop executing. The 8840 plugs into any ISA 8 or 16 bit passive PC Bus backplane, creating a state of the art personal or industrial computing system. As opposed to using a standard mother board, the new 8840 simplifies upgrades and repairs by being quick and easy to install and remove. The VMAX 8840 is ideal for applications which cannot tolerate rotating media storage. It may serve as a single board computer or as a system accelerator for diverse applications.

FEATURES

- FAST 8088 Turbo XT 10MHz or 4.77MHz Processor / 10MHz or 4.77MHz Bus Speed
- SOLID STATE DISK Emulates up to 2 Floppy Drives 1Meg total storage capacity, FLASH and OTP PROM
- 100% DOS COMPATIBLE
- COMMUNICATIONS2 Serial Ports, 1 Parallel Port
- COMPACT 4.2" x 6.7" / Surface Mount / PC/XT Bus
- SOFTWARE INCLUDED for user defined port assignments, solid state disk handling and EMM
- TEMPERATUREoperation over a wide range
- NO SWITCHES64K fully compatible ROM BIOS with automatic configuration
- STRONGsix layer design with internal power and ground planes
- 30 Day Money Back Guarantee
- One Year Warranty / Made in the U.S.A

TECHNICAL SPECIFICATIONS

- VOLTAGE Requirements
 - +5 Volts @ 650 mA
 - +12V @ 25mA (-12V for RS232 generated on board)
 - Total consumption less than 3.6 watts
- OPERATING TEMPERATURE
 - Operating 0 to 60 Degrees C (32 to 140 F)
 - Non-operating -40 to 85 Degrees C (-40 to 185 F)
- **RELATIVE HUMIDITY**
 - 5-95%, Non-Condensing
 - BOARD Construction
 - 6 Layer
 - Power and Ground Plane
- PHYSICAL SIZE
 - 4.2 x 6.7 inches
 - .75 inches thick
- EXTERNAL CONNECTIONS
 - 0.1" connector headers for

- Keyboard
- Remote Reset
- Speaker
- 2 Serial Ports
- 1 Parallel Port
- STANDARD XT RESOURCES
 - 3 Timer Channels
 - 8 Vectored Interrupts
 - 4 DMA Channels
- PROCESSOR
 - CMOS NEC V20/8088 Turbo XT
 - 8 Bit microprocessor operating at 10MHz
 - ISA Bus operating at 4.77MHz or 10MHz
 - Speed Index 4.0 (Norton SI v4.5) relative to 4.77MHz PC
- COMMUNICATIONS
 - Serial Ports 1 and 2 support RS232
 - Communication BAUD Rate from 50 to 56,000
 - Parallel Port (Centronics compatible)
- DISK DRIVE(S)
 - Supports 2 Floppy Disk Drives / 360K, 720K
 - Capable of supporting 2 Solid State Disk Drives (3 configurations available, inquire about custom variations)

Drive 1 consists of up to 1Meg (FLASH/OTP PROM)

Drive 1 consists of up to 512K (FLASH/OTP PROM)

Drive 2 consists of up to 512K (FLASH/OTP PROM)

Drive 1 consists of up to 256K (FLASH/OTP PROM)

Drive 2 consists of up to 768K (FLASH/OTP PROM)
- DRAM
 - Standard Inline Memory Modules
 - 1Meg and 2Meg options
- ROM BIOS
 - Auto Configuration
 - 64K EPROM
 - Supports Low Density Floppy

- Drives (inquire about High Density support)
- WATCHDOG TIMER
 - Resets after 1.2 seconds when enabled
- REAL TIME CLOCK (optional)
- WAIT STATES
 - Software selectable

ORDERING INFORMATION

When ordering, please specify the following information

Description is: Half card/XT CPU with Flash Part number is: VMAX 8840-*

* Specify 1MB to 2MB DRAM FLASH 256KB to 1MB PLCC

Tempustech, Inc. accepts Visa, Mastercard and Net 30 for applicants that qualify for credit terms.

1991/1992 Tempustech, Inc. All rights reserved. Specifications subject to change without notice. IBM PC/XT/AT are registered trademarks of the International Business Machines Corporation.

Tempustech, Inc.

295 Airport Road Naples, Florida 34104


Voice: [800-634-0701](tel:800-634-0701)

Fax: [941-643-4981](tel:941-643-4981)

cpusales@tempustech.com

The Wayback Machine – <https://web.archive.org/web/19980204063605/http://tempustech.com:80/8840.htm>

Documents / Resources

	<p>ASRock 8840 Single Board Processor [pdf] Owner's Manual</p> <p>8840, 8840 Single Board Processor, Single Board Processor, Board Processor, Processor</p>
---	---

References

- [User Manual](#)

💎 8840, 8840 Single Board Processor, ASRock, Board Processor, Processor, Single Board

📁 ASRock Processor

Leave a comment

Your email address will not be published. Required fields are marked *

Comment *

Name

Email

Website

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment

Search:

e.g. whirlpool wrf535swhz

Search

[Manuals+](#) | [Upload](#) | [Deep Search](#) | [Privacy Policy](#) | [@manuals.plus](#) | [YouTube](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.