



ASSA ABLOY IN100 Limited Modular Transmitter Integration Instruction Manual

[Home](#) » [ASSA ABLOY](#) » ASSA ABLOY IN100 Limited Modular Transmitter Integration Instruction Manual 

ASSA ABLOY IN100 Limited Modular Transmitter Integration Instruction Manual



The IN100 RF Module is only intended for Assa Abloy products.

The IN100 PCB transmitter module and plastics are assembled at an Assa Abloy contract manufacturer. Assa Abloy provides all programming and test fixtures to our supplier to ensure the limited modular assemblies remain

compliant.

Final assembly of the Module into the Host Products and Host Product testing are done at an Assa Abloy factory per our factory process.

For additional hosts other than the specific host originally granted with this limited module, a Class II permissive change is required on the module grant to register the additional host as a specific host also approved with the module.

Applicable FCC Rules:

FCC Part 15, Subpart C, Sections 15.225, 15.247 and 15.209

Applicable ISED Rules:

ISED Canada RSS-210 Issue 10 Annex B.6, RSS-247 Issue 2 and RSS-GEN Issue 5 Section 8.9

Host Labelling Instructions:

The module is labelled with its own FCC and IC certification numbers that are not visible when inside the host. Therefore, when the module is installed into the host a label containing the following shall be applied in a visible area on the back of the Host assembly.

Contains:

FCC ID: U4A-SCYMCA1

IC: 6982A-SCYMCA1

Warning: Changes or modifications to this device are strictly prohibited.

This device complies with part 15 of the FCC Rules. This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The final host product still requires Part 15 Subpart B compliance testing with the modular transmitter installed.

RF Exposure:

The antenna(s) used for this module must be installed to provide a separation distance of at least 20cm from all persons and must not be collocated or operated in conjunction with any other antenna or transmitter.

Contents

[1 Documents /](#)

[Resources](#)

[1.1 References](#)

Documents / Resources

