



ASSURED EAC 4000 Series Arm Based Edge AI Computing Owner's Manual

[Home](#) » [ASSURED](#) » ASSURED EAC 4000 Series Arm Based Edge AI Computing Owner's Manual 



Vecow EAC-4000-AR04-S256 Get Quote
EAC 4000

Arm-based Edge AI Computing
NVIDIA® Jetson Orin™ NX/Nano Compact AI Computing System





Contents

- 1 EAC 4000 Series Arm Based Edge AI Computing
- 2 Specifications
- 3 Order Information
- 4 Dimensions & Drawing
- 5 Assured Systems
- 6 Documents / Resources
 - 6.1 References

EAC 4000 Series Arm Based Edge AI Computing

- NVIDIA Jetson Orin™ NX/Nano, up to 100 TOPS AI performance
- Up to 16GB LPDDR5 RAM, pre-installed with NVMe SSD up to 1TB
- 1 GigE LAN, 4 USB 3.1, 1 HDMI 2.0
- 2 COM RS-232/422/485
- 1 Full-size Mini PCIe with SIM for 4G/Wi-Fi/BT
- Optional Allxon OOB Support

▼ Auto Optical Inspection



▲ Delivery Robot



Specifications

System	
CPU	XR16 : 8-core Arm® Cortex® -A78AE v8.2 64-bit CPU XR08/AR08/AR04 : 6-core Arm® Cortex® -A78AE v8.2 64-bit CPU
GPU	XR16/XR08/AR08 : NVIDIA Ampere™ architecture w/1024 NVIDIA® CUDA® cores, 32 Tensor cores AR04 : NVIDIA Ampere™ architecture w/512 NVIDIA® CUDA® cores, 16 Tensor cores
DL Accelerator	XR16 : 2 NVDLA Engines XR08 : 1 NVDLA Engines AR08/AR04 : None
Memory	XR16 : 1 LPDDR5 DRAM, 16GB XR08/AR08 : 1 LPDDR5 DRAM, 8GB AR04 : 1 LPDDR5 DRAM, 4GB
Software Support	– Linux – NVIDIA JetPack SDK
I/O Interface	
USB	4 USB 3.1 Type A
Micro USB	1 Micro USB Flash Port
Button	– 1 Power Button – 1 Force Recovery Button – 1 Reset Button
LED	Power, SSD
SIM	1 Nano SIM Card Socket
Antenna	2 Antenna for WiFi/4G
Serial	2 COM RS-232/422/485
Expansion	
Mini PCIe	1 Mini PCIe (Full-size, PCIe, USB 2.0)
Graphics	
Video Encode	XR16/XR08 : – HEVC : 1x 4K @60, 3x 4K @30, 6x 1080p @60, 12x 1080p @30 – H.264 : 1x 4K @60, 2x 4K @30, 5x 1080p @60, 11x 1080p @30
Video Decode	XR16/XR08 : – HEVC : Up to 1x 8K @30, 2x 4K @60, 4x 4K @30, 9x 1080p @60, 18x 1080p @30 – H.264 : Up to 1x 4K @60, 2x 4K @30, 5x 1080p @60, 11x 1080p @30 AR08/AR04 : – HEVC : Up to 1x 4K @60, 2x 4K @30, 5x 1080p @60, 11x 1080p @30 – H.264 : Up to 1x 4K @30, 3x 1080p @60, 7x 1080p @30
Interface	1 HDMI 2.0, up to 4K@60
Storage	
M.2	1 M.2 Key M Socket (2242, PCIe 4.0 x4)
Ethernet	

LAN	10/100/1000 Base-T GigE LAN, RJ45 Connector
Power	
Power Input	12V DC Power Input
Power Interface	3-pin 3.5mm Terminal Block V+, V-
Others	
OOB	Out-of-band mgmt by Nuvoton NUC980 (Optional, by Module)
TPM	Infineon SLB9673 supports TPM 2.0 (Optional)
Mechanical	
Dimensions	112 x 103 x 45 mm
Weight	0.6 kg (1.32 lb)
Mounting	– Wallmount – DIN Rail (Optional)
Environment	
Operating Temperature	15W TDP Mode : -25°C to 55°C 25W TDP Mode : -25°C to 45°C
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% Humidity, non-condensing
Relative Humidity	95% @55°C
Shock	Operating, MIL-STD-810G, Method 516.7, Procedure I
Vibration	Operating, MIL-STD-810G, Method 514.6, Procedure I, Category 4
EMC	CE, FCC, EN50155, EN50121-3-2, EN62368-1, MIL-STD-810G

* All product information may subject to change without prior notice.

* The rights of all brand names, product names and trademarks belong to their respective owners.

Copyright © 2024 Vecow Co., Ltd. All rights reserved.

Vecow



info@vecow.com

Order Information

Model	Platform	RAM	LAN	USB 3.1	Serial	SIM	HDMI	Antenna
4000-XR16 -SXX X*	Jetson Orin NX	16GB	1	4	2	1	1	2
4000-XR08 -SXX X*		8GB						
4000-AR08 -SXX X*	Jetson Orin Nano	8GB	1	4	2	1	1	2
4000-AR04 -SXX X*		4GB						

*A NVMe SSD is included in default. Please refer to NVMe SSD List to select NVMe SSD capacity.

NVMe SSD List


S128	128GB NVMe SSD	S512	512GB NVMe SSD
S256	256GB NVMe SSD	S01T	1TB NVMe SSD

Accessories

PWA-60WP3-WT-12V	60W, 12V, 90V AC to 264V AC Power Adaptor for 3 PIN 5.0mm Terminal Block, -30°C~+70°C
PWA-135W-WT-12V	135W, 12V, 85V AC to 264V AC Power Adapter with 3-pin Terminal Block, Wide Temperature -30°C to +70°C
DIN-RAIL	DIN Rail Kit
M.2 Storage Module	M.2 Key M/Key B PCIe Storage Module
4G Module	4G/GPS Module with Antenna
WiFi & Bluetooth	WiFi & Bluetooth Module with Antenna

Dimensions & Drawing

Unit : mm (inch)



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave

Ste 1200

Sheridan

WY 82801

USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park

Stone Business Park

Stone

ST15 0YJ

United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660

Documents / Resources



[ASSURED EAC 4000 Series Arm Based Edge AI Computing](#) [pdf] Owner's Manual
EAC-4000-AR04-S128, EAC-4000-AR04-S256, EAC 4000 Series Arm Based Edge AI Computing, EAC 4000 Series, Arm Based Edge AI Computing, Based Edge AI Computing, Edge AI Computing, AI Computing, Computing

References

- [Industrial Embedded Computers and Displays - Assured Systems](#)
- [Industrial Embedded Computers and Displays - Assured Systems](#)
- [Industrial Embedded Computers and Displays - Assured Systems](#)
- [User Manual](#)

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.