



ATAG WU50311BM Built In Unit (50 cm) User Manual

[Home](#) » [ATAG](#) » ATAG WU50311BM Built In Unit (50 cm) User Manual 

Contents

- [1 ATAG WU50311BM Built In Unit \(50 cm\)](#)
- [2 PRODUCT INFORMATION](#)
- [3 Documents / Resources](#)
- [4 Related Posts](#)

ATAG

ATAG WU50311BM Built In Unit (50 cm)





PRODUCT INFORMATION

Type of model WU50311BM

- Annual Energy Consumption: AEC hood/ 48,2
- Time increase factor: $f / 0,8$
- Fluid Dynamic Efficiency: FDE hood / 33,4
- Energy Efficiency Index: EEI hood / 47
- Energy efficiency class: A
- Measured air flow rate at best efficiency point: Q BEP / 406
- Measured air pressure at best efficiency point: P BEP / 456
- Maximum air flow: Q max / 610
- Measured electric power input at best efficiency point: W BEP/ 154,2
- Nominal power of the lighting system: W L/ 4,4
- Average illumination of the lighting system on the cooking surface: E middle/ 331
- Measured power consumption in standby mode: P s/ 0,5
- Measured power consumption off mode: P o/ 0,49
- Sound power level: L WA/ 62

“Data determined according to standard EN 60350-1 and Commission Regulations (EU) No 65/2014 and (EU) No 66/2014”.

Documents / Resources



ATAG WU50311BM Built In Unit (50 cm) [pdf] User Manual

WU50311BM Built In Unit 50 cm, WU50311BM, Built In Unit 50 cm, Unit 50 cm