



## Atlantic TidalWave L-Series pump Instruction Manual

[Home](#) » [Atlantic](#) » Atlantic TidalWave L-Series pump Instruction Manual 

*Atlantic TidalWave L-Series pump  
Instruction Manual*



## Product Manual



L-305 - 73897 | L-310 - 73898

1.330.274.8317

[www.ATLANTICWATERGARDENS.com](http://www.ATLANTICWATERGARDENS.com)

[www.ATLANTICWATERGARDENS.com](http://www.ATLANTICWATERGARDENS.com)


## Contents

- 1 Introduction
- 2 Prior to Operation and Installation
- 3 Caution
- 4 Before You Start
- 5 Electrical Safety
- 6 Operation
- 7 Motor Protection System
- 8 Maintenance and Inspection
- 9 Monthly Inspection
- 10 Winterizing
- 11 Warranty
- 12 Warranty Claims
- 13 Troubleshooting Guide
- 14 Documents / Resources
  - 14.1 References
- 15 Related Posts

## Introduction

Thank you for choosing this Atlantic TidalWave L-Series pump. Before using this pump please take a moment to review this manual.

To avoid an accident do not use the pump in any way other than as described in this manual. Please note the manufacturer cannot be responsible for accidents arising because the product was not used as prescribed. After reading this manual keep it as a reference in case questions arise during use. Using the pump in a manner that is not prescribed will void the warranty.



## Prior to Operation and Installation

When the pump is delivered, first perform the following checks:

- Check for any damage to pump and power cable that may have occurred during the shipment.
- Check the model number to make sure it is the product that was ordered and verify the voltage and frequency are correct.

## Caution

- DO NOT operate this product under any condition other than those for which it is specified. Failure to observe this precaution can lead to electrical shock, electrical leakage, fire, water leakage or other problems.
- L-305/L-310 pumps require a single phase 115 volt / 60 hz power supply. Always verify that the supplied power meets the requirements listed on the upper pump cover.
- DO NOT apply any paint over the stainless steel motor body. Reduced cooling ability will result in overheating.

overload, introduce undesirable performance reductions, periodic auto shut-off and pump malfunction.

- Never place your hand or any object in or near the inlet opening while this equipment is operating. If pump inlet is clogged, always turn off the power supply, fuse box or circuit breaker and wait until the motor is completely stopped before attempting to remove any clogged material.
- Please make sure that the power plug and the AC outlet receptacle is protected and away from water or pump discharge hose to prevent accidental electric shock or short circuit.
- Always operate the pump completely submerged in water.
- Avoid dry operation, which will not only lower performance but can cause the pump to overheat/malfunction, leading to electrical leakage, shock or premature failure.

- **CAUTION:**

THIS PUMP IS TO BE USED IN A CIRCUIT PROTECTED BY A GROUND CIRCUIT INTERRUPTER.

- **CAUTION:**

THIS PUMP HAS BEEN EVALUATED FOR USE IN WATER ONLY.

## **Before You Start**

- Check the model name plate to make sure once again that the product is of the correct voltage and frequency rating.
- The setting on the circuit breaker or other overload protector should be made in accordance with the rated currency of the pump.
- Turn off the power supply or circuit breaker before inserting the power supply plug to avoid electrical shock, shorting, or unexpected starting of the pump, which could lead to injury.
- Never operate the pump while it is suspended in air. The recoil may result in injury or other major accident.

## **Electrical Safety**

- Electrical wiring should be installed by a qualified electrician in accordance with all applicable safety regulations. Incorrect wiring can lead to a pump malfunction, electrical shock or fire.
- Pumps should operate on a designated, circuit rated at 15 Amps (minimum).
- Pump must be protected by a ground fault circuit interrupter (GFCI).
- Pump must be plugged into a standard, properly grounded, three pronged outlet.
- Do not cut the electrical cable. If a cable with cut insulation or other damage is submerged in water, there is danger of water seeping into the pump motor and causing a short. This may result in damage to the pump, electrical shock or fire. Altering the electrical cable in any way will void the warranty.
- Never move or handle the pump by pulling on the electrical cable. Make sure the electrical cable does not become excessively bent or twisted, does not rub against a structure in a way that might damage it, and does not come in contact with heated surfaces.

## **Operation**

- In case of a power outage, turn off the power to the pump to avoid having it start unexpectedly when the power is restored.
- L-Series pumps are cooled internally as the water flows around the motor. Entire pump including intake screen must be completely submersed during operation.

- In case of very excessive vibration, unusual noise or odor, turn off the power immediately and consult with your nearest dealer. Continuing to operate the pump under abnormal conditions may result in electrical leakage, electrical shock or fire.

## Motor Protection System

- The pump has a built-in motor protection system. The following reasons may cause the pump to stop automatically regardless of water level.
  - Motor overheating
  - Excessive current
  - Change in voltage polarity
  - Open-phase operation or operation under constraint
- Repeating cycles of stopping and restarting will damage the water pump. Do not continue operation at low lift, low water level, or while the inlet is clogged with debris. Not only will performance suffer, but also such conditions may cause noise, heavy vibration, and pump failure.

## Maintenance and Inspection

- Regular maintenance and inspections are a necessity for continued efficient functioning. If any abnormal conditions are noticed, refer to the section on Troubleshooting and take corrective measures immediately.

## Monthly Inspection

- Check for any drop in performance. Reduced performance is usually caused by debris blocking the intake screen.
- Detach the power cable from the receptacle and turn off the power supply (circuit breaker).
- Disconnect the pump discharge and remove the pump from the water.
- Remove any accumulated debris from the surface of the pump, inlet screen and impeller. · Make sure all nuts and bolts are fastened securely.

## Winterizing

- Under no circumstances should the pump be left in frozen water.
- When the pump is out of use for an extended period, wash it and dry it thoroughly, then store it indoors.

**Note:** Always run a test operation before putting the pump back into operation. When the pump is left installed in water it should be run at regular intervals (about once per week).

## Warranty


All TidalWave L-Series Pumps carry a two-year limited warranty. This limited warranty is extended solely to the original purchaser commencing from the date of original purchase receipt and is void if any of the following apply:

- The pump has been run while not fully submersed causing the thermal protection to trip.  
Skimmers using inadequate vertical filtration may create “run dry” conditions.

- The pump was not run on a dedicated circuit.
- The cord has been cut or altered.
- The pump has be mounted horizontally.
- The pump has been run in salt or chlorinated water.
- The pump has been misused or abused.
- Serial number tag has been removed.
- The pump has been fully or partially disassembled other than described in this manual.

## **Warranty Claims**

- In case of warranty claims, pump should be returned to place of purchase accompanied by original receipt.



NO.	Description
1	Outlet
2	Cable
3	Upper Cover
4	Handle
5	Capacitor
6	Cable Sleeve
7	Upper Bearing
8	Cable Base Cover
9	Bracket

NO.	Description
10	Auto-cut
11	Motor Frame
12	Shaft (with rotor)
13	Stator
14	Outer Cover
15	Lower Bearing
16	Lubricant
17	M. Seal Bracket
18	Oil Plug

NO.	Description
19	M. Seal
20	Casing
21	Oil Seal
22	Oil Seal Bush
23	Impeller
24	Impeller Key
25	Wear Ring
26	Strainer
27	Footing

## Troubleshooting Guide

Always turn off power before inspecting the pump. Failure to observe this precaution can result in a serious accident.

Before ordering repairs, carefully read through this instruction booklet. If the problem persists, contact your dealer.


Problem	Possible Cause	Possible Solution
Pump does not start	No power to the outlet	Check the breaker and GFCI
	Power failure	Check power supply or contact local power company
	Power cord is not connected	Connect power cord
Pump motor hums with no flow	Impeller is blocked	Remove debris from the impeller
	Capacitor failure	Contact dealer for repair / replacement parts
Pump stops after starting	Pump is overheating	Submerge pump below handle/ Raise water level/ Allow pump to cool
	Insufficient power to the pump	Check outlet for proper voltage while the pump is running
Diminished flow rate or no water flow	Air lock	Restart/Clean air valve
	Obstruction in pump or plumbing	Clear obstruction
	Improper plumbing diameter or length	Refer to the Resource section on <a href="http://www.atlanticwatergardens.com">www.atlanticwatergardens.com</a> for plumbing recommendations



1.330.274.8317

[www.ATLANTICWATERGARDENS.com](http://www.ATLANTICWATERGARDENS.com)

## Documents / Resources

	<p><a href="#">Atlantic TidalWave L-Series pump</a> [pdf] Instruction Manual Atlantic, L-305 - 73897, L-310 - 73898</p>
---	---

## References



- [Home | Atlantic Water Gardens](#)

Manuals+.