

audio-technica ES945O/FM3 Omnidirectional Condenser Boundary Microphone User Guide

<u>Home</u> » <u>Audio-Technica</u> » audio-technica ES9450/FM3 Omnidirectional Condenser Boundary Microphone User Guide [™]

audio-technica ES945O/FM3 Omnidirectional Condenser Boundary Microphone User Guide



Contents

- 1 Included accessories
- 2 How to Mount the product
- 3 Connection procedure
- 4 Safety precautions
- 5 Notes on use
- 6 Switch setting and

functions

- 7 Warranty
- 8 Documents / Resources
- 9 Related Posts

Included accessories


Rubber isolator (1)



Rubber isolator (2)




Nut




How to Mount the product

Table/ceiling hole size (actual size)


When using isolators



When not using isolators



Example: Mounting on a table




Connection procedure

The output connector is an XLR-M type with polarity as shown in the figure below


ES945O/FM3 / ES947C/FM3

Output terminals



ES945O/FM5 / ES947C/FM5

Output terminals



Thank you for purchasing this product. Before using the product, read through the user manual to ensure that you will use the product correctly. Please keep this manual for future reference.

Safety precautions

Although this product was designed to be used safely, failing to use it correctly may result in an accident. To ensure safety, observe all warnings and cautions while using the product.

Cautions for the product


- Do not subject the product to strong impact to avoid malfunction.
- Do not disassemble, modify or attempt to repair the product.
- Do not handle the product with wet hands to avoid electric shock or injury.
- Do not store the product under direct sunlight, near heating devices or in a hot, humid or dusty place.

Notes on use

- Do not swing or pull with the cable connected to the microphone to prevent the microphone from becoming disconnected or damaged.
- Do not wind the cable around the rack or allow the cable to become pinched.
- The microphone should be placed on a flat, unobstructed mounting surface.
- Placing any object on a surface (such as a conference table) before its finish is fully cured may result in damage to the finish.


Switch setting and functions

ES945O/FM3 / ES947C/FM3



1. Action	2. Audio status	3. LED color LED color MC ON MC ON LED color MC ON MC ON LED color MC ON MC O	4, LED status
	•	e july e july s michi. Wicon	Ö
	½	MEDH MICH	Ö

ES9450/FM5 / ES947C/FM5



1. Action	2. Contact closure status	3. Audio status	4. LED color LED COLOR MIC OF MIC ON STATE OF ST	5. LED status
5	Ϊ́β		MIC DISC. MIC DN	
	E E	•	MCOS UCCO	


LED color

	1	2	3
OFF	RED	GREEN	YELLOW


4	5	6	7
BLUE	MAGENTA	CYAN	WHITE

Dimensions

ES9450/FM3 / ES947C/FM3



ES945O/FM5 / ES947C/FM5



Warranty

Warranty (Please be sure to read the notes below.)

End-User LIMITED WARRANTY information for the USA is available at www.audio-technica.com/usawarranties.

You may also contact Audio-Technica U.S., Inc. to request a written copy of the Limited Warranty at 1-330-686-2600 or via mail at 1221 Commerce Drive, Stow, OH 44224.

Audio-Technica Corporation

2-46-1 Nishi-naruse, Machida, Tokyo 194-8666, Japan

www.audio-technica.com

©2021 Audio-Technica Corporation

Global Support Contact: www.at-globalsupport.com

Documents / Resources



<u>audio-technica ES945O/FM3 Omnidirectional Condenser Boundary Microphone</u> [pdf] Use r Guide

ES945OFM3, ES945OFM5, ES945OFM3 Omnidirectional Condenser Boundary Microphone, O mnidirectional Condenser Boundary Microphone, Condenser Boundary Microphone, Microphone e

Manuals+,