




AUTEL ROBOTICS EVO 2 Dual 640T V3 Enterprise Bundle Drone User Guide

[Home](#) » [AUTEL ROBOTICS](#) » AUTEL ROBOTICS EVO 2 Dual 640T V3 Enterprise Bundle Drone User Guide 

AUTEL ROBOTICS EVO 2 Dual 640T V3 Enterprise Bundle Drone User Guide




Contents

- [1 OVERVIEW](#)
- [2 FLIGHT LED INDICATIONS](#)
- [3 CHARGING](#)
- [4 POWERING UP](#)
- [5 TAKE OFF](#)
- [6 COMMAND STICK CONTROLS\(MODE 2\)](#)
- [7 SPECIFICATIONS](#)
- [8 Aircraft](#)
- [9 Remote Controller](#)
- [10 Documents / Resources](#)
 - [10.1 References](#)
- [11 Related Posts](#)

OVERVIEW


The EVO II Dual 640T V3 brings excellent flight performance, achieving a top speed of 20m/s (45mph), 38-minute flight time, and an operating distance at 15km (9.32miles, FCC). The aircraft comes with a 7.9 inch touch-screen controller, boasts a 2048×1536 pixel resolution.




⚠ NOTE

Please read all documentation before your first flight. Failure to operate the aircraft responsibly could lead to injury or damages, and may void any applicable warranty coverage.


AIRCRAFT




1. Propellers
2. Motors
3. Front LED Indicators
4. Landing Gear
5. Front Vision System
6. Gimbal Camera




- 7. Power Button
- 8. Rear Vision System
- 9. Rear LED Indicators




- 10. Left Side Vision System
- 11. SD Card Slot



- 12. Right Side Vision System
- 13. Aircraft Battery
- 14. Air Vent
- 15. USB-C Port
- 16. Pairing Button / Pairing Indicator



17. Upward Vision System



18. Ultrasonic Sensor

19. Downward Vision Lighting LED

20. Downward Vision System

FLIGHT LED INDICATIONS

A LED indicator is located on the end of each aircraft arm. The front LEDs will light up solid red to help you identify the direction of the aircraft's nose.

The rear LEDs will display the current flight status of the aircraft. The chart below shows the meaning of each status indicator.

Indicator Key:

Slow Flashing: Flashes once every 2s
Fast Flashing: Flashes twice per second


Color Key

R – Red Color
 G – Yellow Color

Alternate Flashing: Alternates among different colors Y – Green Color

Definitions of Indicator Status	
Normal	
RGY – Alternate Flashing	System self-test is activated
YG – Alternate Flashing	The aircraft is warming up
G – Slow Flashing	The aircraft is in GPS mode
Warning	
Y – Slow Flashing	The aircraft is in ATTI mode
Y – Fast Flashing	No connection between the aircraft and smart controller
R – Slow Flashing	Low Battery Warning
R – Fast Flashing	Critically Low Battery Warning
R – Solid Light	Critical problems, IMU error
RY – Alternate Flashing	Abnormal compass, calibration is required / Magnetometer interference
Compass Calibration	
Y – Fast Flashing	Be ready to calibrate the compass/ The aircraft is calibrating
G – Solid Light	Calibration is successful
R – Solid Light	Calibration is failed


REMOTE CONTROLLER




1. Left Command Stick
2. Gimbal Pitch Angle Wheel
3. Video Recording Button
4. Customizable Button C1
5. Air Outlet
6. HDMI Port

- 7. USB TYPE-C Port
- 8. USB TYPE-A Port
- 9. Power Button
- 10. Customizable Button C2
- 11. Photo Shutter Button
- 12. *Zoom Control Wheel
- 13. Right Command Stick

*The function may alter, please take the practical effect as standard.




- 14. Battery Indicator
- 15. Antenna
- 16. Touch Screen
- 17. Pause Button
- 18. Auto-takeoff/RTH Button
- 19. Microphone




- 20. Speaker Hole
- 21. Tripod Mount Hole
- 22. Air Inlet
- 23. Bottom Hook
- 24. Grips

CHARGING



Aircraft Battery: Plug the charging connector into the battery's charge port, and connect the other end to power adapter. Plug the power adapter into a power outlet (100-240V).



Controller: Connect the charging cable to the USB port at the top of the controller, and the other end to power adapter. Plug the power adapter into a power outlet (100- 240V AC).

NOTE:


- Always fully charge the aircraft and smart controller battery before flying.
- It takes approximately 90 minutes to fully charge the aircraft battery, and 120 minutes to charge the controller.

AUTEL EXPLORER APP


Search for 'Autel Explorer' from Google Play and install the app on your controller

PREPARING THE AIRCRAFT

Before powering on the aircraft, please remove the gimbal cover.



Unfold the arms and propellers.



**NOTE:**


Power off the aircraft before folding the arms. Fold in the rear arms and propellers first, and then the front ones.

PROPELLERS

Because the propellers come attached to the aircraft, the following instructions apply if you need to reinstall propellers.

• Attaching the Propellers

1. Power off the aircraft.
2. Pair the propellers and corresponding motors according to the white mark .
3. Press each propeller down firmly and rotate in the lock direction to securely attach the propeller.

**• Detaching the Propellers**

1. Power off the aircraft.
2. Press each propeller down firmly and rotate in the unlock direction to detach the propeller.

LEGEND

Lock Direction: Fasten the propeller by rotating it as indicated.




Unlock Direction: Unfasten the propeller by rotating is as indicated.



**NOTE:**

- Power off the aircraft before attaching or detaching propellers.
- Propellers must be undamaged and firmly attached.


PREPARING THE CONTROLLER




Unfold the antenna, detach the stick heads on the back of the controller handle, and screw them into the corresponding screw holes on both sides of the screen.



POWERING UP




Press and hold the power button for 2 seconds to turn on the controller.




Press and hold the power button 3 seconds to turn on the aircraft. The current battery level will be clearly displayed.

TAKE OFF



Start the motors by holding both command sticks for 2 seconds as shown below.



Push the left command stick slowly upward.




NOTE:

- The default control stick mode is mode 2. The left stick controls the altitude and heading of the aircraft, while the right stick controls the forward, backward and sideward movements.
- Before takeoff, place aircraft on a level surface, stand well clear of the rear of the aircraft.


COMMAND STICK CONTROLS(MODE 2)

Left Command Stick


Left Side View




Left Side View



Top View




Top View




Right Command Stick


Left Side View




Left Side View



Rear View



Rear View



SPECIFICATIONS

Aircraft	
Operating Frequency	902~928MHz (FCC);2.4~2.4835GHz;5.725~5.850GHz (Non-Japan);5.650-5.755GHz (Japan)
Transmission Power (EIRP)	900MHz: FCC/ISED<=31dBm 2.4GHz: FCC/ISED<=32dBm;CE/MIC/SSRC/RCM<=20dBm 5.8GHz/5.7GHz: FCC/ISED/SSRC/MIC<=33dBm; CE/RCM<=14dBm
Remote Controller	
Operating Frequency	902~928MHz (FCC);2.4~2.4835GHz;5.725~5.850GHz (Non-Japan);5.650-5.755GHz (Japan)
Transmission Power (EIRP)	FCC: ≤33dBmCE: ≤20dBm@2.4G , ≤14dBm@5.8G/5.7G SSRC: ≤20dBm@2.4G , ≤33dBm@5.8G/5.7G

FCC and ISSED Canada Compliance

This device complies with part 15 of the FCC Rules and ISSED Canada licence-exempt RSS standards. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. this device must accept any interference received, including interference that may cause undesired operation

Le présent appareil est conforme aux CNR d'ISED Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

1. l'appareil ne doit pas produire de brouillage, et
2. l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

NOTE:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Aircraft

RF Exposure Information

This equipment complies with RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be operated with minimum distance 20cm between the radiator and your body.

Remote Controller

FCC Specific Absorption Rate (SAR) information

SAR tests are conducted using standard operating positions accepted by the FCC with the device transmitting at its highest certified power level in all tested frequency bands, although the SAR is determined at the highest certified power level, the actual SAR level of the device while operating can be well below the maximum value, in general, the closer you are to a wireless base station antenna, the lower the power output. Before a new model device is available for sale to the public, it must be tested and certified to the FCC that it does not exceed the exposure limit established by the FCC. Tests for each device are performed in positions and locations (e.g. at the ear and worn on the body) as required by the FCC. For limb worn operation, this device has been tested and meets the FCC RF exposure guidelines when used with an accessory designated for this product or when used with an accessory that contains no metal. For body worn operation, this device has been tested and meets the FCC RF exposure guidelines when used with an accessory designated for this product or when used with an accessory that contains no metal and that positions the device a minimum of 10mm from the body.

ISED Specific Absorption Rate (SAR) information


SAR tests are conducted using standard operating positions accepted by the ISED with the device transmitting at its highest certified power level in all tested frequency bands, although the SAR is determined at the highest certified power level, the actual SAR level of the device while operating can be well below the maximum value, in general, the closer you are to a wireless base station antenna, the lower the power output. Before a new model device is available for sale to the public, it must be tested and certified to the ISED that it does not exceed the exposure limit established by the ISED. Tests for each device are performed in positions and locations (e.g. at the ear and worn on the body) as required by the ISED. For limb worn operation, this device has been tested and meets the ISED RF exposure guidelines when used with an accessory designated for this product or when used with an accessory that contains no metal. For body worn operation, this device has been tested and meets the ISED RF exposure guidelines when used with an accessory designated for this product or when used with an accessory that contains no metal and that positions the device a minimum of 10mm from the body.

www.autelrobotics.com

©2022 Autel Robotics Co., Ltd. All Rights Reserved



Documents / Resources



[AUTEL ROBOTICS EVO 2 Dual 640T V3 Enterprise Bundle Drone](#) [pdf] User Guide
EVO 2 Dual 640T V3 Enterprise Bundle Drone, EVO 2 Dual 640T V3, Enterprise Bundle Drone,
Bundle Drone, Drone

References

- [Autel Robotics Enterprise Drone, Quadcopter & UAV for Sale | Leader in Drones](#)