


AXXESS AXTO-MI2 Mitsubishi Amplifier Interface



AXXESS AXTO-MI2 Mitsubishi Amplifier Interface Installation Guide


[Home](#) » [AXXESS](#) » AXXESS AXTO-MI2 Mitsubishi Amplifier Interface Installation Guide 

Contents

- [1 AXXESS AXTO-MI2 Mitsubishi Amplifier Interface](#)
- [2 Product Usage Instructions](#)
- [3 APPLICATIONS](#)
- [4 FEATURES](#)
- [5 INTERFACE COMPONENTS](#)
- [6 TOOLS REQUIRED](#)
- [7 Connections to be made](#)
- [8 Initializing and adjusting the AXTO-MI2](#)
- [9 Documents / Resources](#)
 - [9.1 References](#)
- [10 Related Posts](#)



AXXESS AXTO-MI2 Mitsubishi Amplifier Interface



Specifications

- **Product Name:** AXTO-MI2 Mitsubishi Amplifier Interface
- **Compatibility:** Mitsubishi vehicles – Lancer 2008-2013, Outlander Sport 2011-2013, Outlander 2007-2013
- **Model:** AXTO-MI2
- **Revision Date:** 1/21/2020

Product Usage Instructions

Installation

1. Before starting the installation process, ensure to disconnect the negative battery terminal as a safety precaution.
2. Make all necessary connections as per the provided instructions, ensuring that all accessories and switches are plugged in before reconnecting the battery or cycling the ignition.

Connections

1. If the radio lacks RCA outputs or only has one pair, utilize the Axxess AXLOC4-80A (4 Ch.) or AXLOC-80A (2 Ch.) line-level converters (sold separately).

Initializing and Adjusting

1. Use the AXTO-MI2 for mid/high speaker control and subwoofer control. Refer to Figure A for visual guidance.

FAQ

Q: What should I do if unsure about the installation process?

A: If you are unclear about the instructions or lack the understanding to complete the installation safely, it is recommended to consult a technician with the necessary knowledge. For further assistance, contact Metra at 1-800-2210932.

Q: Where can I enhance my installation skills?

A: Consider enrolling in the Installer Institute to improve your installation and fabrication skills. Visit www.installerinstitute.com or call [800-354-6782](tel:800-354-6782) for more information.

APPLICATIONS

MITSUBISHI

- **Lancer** 2008-2013
- **Outlander** Sport 2011-2013
- **Outlander** 2007-2013

FEATURES

- Retains the factory amplifier
- Provides multimedia wires (parking brake, reverse, and speed sense)
- RCA level input
- Retains balance and fade

INTERFACE COMPONENTS

- AXTO-MI2 interface
- AXTO-MI2 harness
- 14-pin harness with stripped leads and RCA jacks

TOOLS REQUIRED

- Cutting tool
- Crimping tool
- Tape
- Small flat-blade screwdriver
- **Connectors (example:** butt-connectors, bell caps, etc.
- **CAUTION:** Metra recommends disconnecting the negative battery terminal before beginning any installation.
- All accessories, switches, and especially air bag indicator lights must be plugged in before reconnecting the battery or cycling the ignition.
- **NOTE:** Refer to the instructions included with the aftermarket radio.

Connections to be made

From the 14-pin harness to the aftermarket radio:

- Connect the Red wire to the accessory wire.
- Connect the Blue/White wire to the amp and turn on the wire (this wire must be connected to hear sound from the factory amplifier).
- Tape off and disregard the Brown wire, it will not be used in this application.
- Connect the White RCA to the left front output.
- Connect the Gray RCA to the right front output.
- Connect the Green RCA to the left rear output.
- Connect the Purple RCA to the right rear output.
- **Note:** If the radio does not have RCA outputs or only one pair, use the Axxess AXLOC4-80A (4 Ch.) or AXLOC-80A (2 Ch.) line-level converters (sold separately).
- The following wires are for aftermarket multimedia/navigation radios that provide these wires (if not required, tape them off and disregard them):
- Connect the Light Green wire to the parking brake wire.
- Connect the Blue/Pink wire to the speed sense/ V.S.S. wire.
- Connect the Green/Purple wire to the reverse wire.


- **Note:** Reverse wire is not available on manual transmission vehicles.
- Plug the 14-pin harness into the AXTO-MI2

From the AXTO-MI2 harness:

- Connect the Black wire to the ground wire.
- Connect the Yellow wire to the battery wire.
- Connect the Blue wire to the power antenna turn-on wire.
- Connect the Orange wire to the Illumination wire. (If the aftermarket radio has no Illumination wire, tape off the Orange wire.)
- Connect the 16-pin harness to the AXTO-MI2.
- Connect the 18-pin and 20-pin harness to the vehicle.

Initializing and adjusting the AXTO-MI2

- Initialize the interface by turning the ignition on for 30 seconds, then turn the ignition back off, and on again.
 - If the speakers are too loud, or not loud enough, you can adjust the output by following the steps below:
1. Locate the end of the AXTO-MI2 with the 14-pin harness with stripped leads and RCA jacks.
 2. Using a small flat-blade screwdriver, turn the gain knob clockwise to make it louder, or counterclockwise to make it lower.



(Figure A)

IMPORTANT WARNING

- This product includes instructions for installation which must be carefully followed.
- The instructions are worded in such a manner as to assume that the installer is capable of completing these types of electronic installations.
- If you are unclear as to what you are instructed to do or believe that you do not understand the instructions to properly and safely complete the installation you should consult a technician who does have this knowledge and understanding.
- Failure to follow these instructions carefully and to install the interface as described could cause harm to the vehicle or safety systems on the vehicle.
- Interference with certain safety systems could cause harm to persons as well. If you have any questions in this regard please call the Helpline or Metra at 1-800-221- 0932 for assistance.

KNOWLEDGE IS POWER

- Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry.
- Log onto www.installerinstitute.com or call [800-354-6782](tel:800-354-6782) for more information and take steps toward a better tomorrow.
- Metra recommends MECP-certified technicians
- METRA. The World's best kits.™ 1-[800-221-0932](tel:800-221-0932) metraonline.com
- © COPYRIGHT 2020 METRA ELECTRONICS CORPORATION



Documents / Resources



[AXXESS AXTO-MI2 Mitsubishi Amplifier Interface](#) [pdf] Installation Guide
AXTO-MI2, AXTO-MI2 Mitsubishi Amplifier Interface, Mitsubishi Amplifier Interface, Amplifier Interface, Interface

References

- [🌐 Installer Institute Announces Closure after 31 Years | installerinstitute.edu](https://www.installerinstitute.edu/news/installer-institute-announces-closure-after-31-years)
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.