



Baihuon BH-18E Remote Control Transmitter Instruction Manual

[Home](#) » [Baihuon](#) » Baihuon BH-18E Remote Control Transmitter Instruction Manual 

Contents

- [1 Baihuon BH-18E Remote Control Transmitter](#)
- [2 INSTALLATION](#)
- [3 OPERATION](#)
- [4 CHANGING THE BATTERY](#)
- [5 TECHNICAL DATA](#)
- [6 FCC warning](#)
- [7 Documents / Resources](#)
- [8 Related Posts](#)



Baihuon BH-18E Remote Control Transmitter



INSTALLATION

Install one (1) x 12V (23A) battery in the compartment, make sure the installation of battery is correct.

OPERATION

Transmitter with 2 buttons for individual ON and OFF function. Each push of the ON or OFF button on remote controller will turn on or off the corresponding receivers accordingly.

CHANGING THE BATTERY

Regularly change the battery in the remote control for best use – however if you find the receivers are not responding or the indicator light becomes dim then you must change the battery at the earliest available time. Always dispose of old batteries with consideration for the environment.

TECHNICAL DATA

Transmission frequency: 433.92MHz Transmitter powered by: DC 12V 23A battery (1pc)

FCC warning

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

Documents / Resources

[illegible]