

bbpos QB33 Intuit Node Instruction Manual

Home » bbpos » bbpos QB33 Intuit Node Instruction Manual



Contents

- 1 bbpos QB33 Intuit Node
- 2 Intuit Node (QB33 / CHB80) Instruction

Manual

- **3 NFC Status Indictors**
- **4 Product Specifications**
- **5 FCC Caution Statement**
- 6 Documents / Resources
 - **6.1 References**
- **7 Related Posts**



bbpos QB33 Intuit Node



Intuit Node (QB33 / CHB80) Instruction Manual

Follow your application instruction to start the transaction process, then insert or tap the card to complete the transaction.

• If you pay via inserting an EMV IC card, please ensure that the EMV chip of the card is facing the right direction. If you pay using NFC card, please ensure you tap the NFC payment card within 4cm range on top of the NFC marking.



NFC Status Indictors

- "TAP" + "BEEP"- Ready for tapping card
- "CARD READ" Reading card information
- "PROCESSING" + "BEEP" Card reading process successfully completed "APPROVED" + "BEEP" Transaction completed
- A rolling dot is shown in LED matrix, "." Standby mode

Cautions & Important Notes

- Ensure the device is fully charged before use.
- Please ensure EMV chip of the card is facing the right direction when inserting card.
- The NFC card should be tapped within 4 cm range on top of the reader mark.
- Don't drop, disassemble, tear, open, crush, bend, deform, puncture, shred, microwave, incinerate, paint or insert foreign object into the device. Doing any of which will damage the device and void the Warranty.
- Don't immerse the device into water and place near washbasins or any wet locations. Don't spill food or liquid
 on the devices. Don't attempt to dry the device with external heat sources, such as microwave or hair dryer.
 Don't use any corrosive solvent or water to clean the device.
- · Recommend using dry cloth to clean the surface only.
- Don't use any sharp tools to point the internal components, connectors or contacts, doing which may lead to device malfunction and void the Warranty simultaneously.

Product Specifications

Functions	EMV chip card reader (ISO 7816 compliant class A, B, C card) NFC Card Reader (EMV contactless, ISO 14443A/B) Over-the-air firmware update Over-the-air key update
Charging	USB C and wireless charge
Power & Battery	Lithium polymer rechargeable battery 500mAh, 3.7V
Message displayed in LED matrix	"TAP" + "BEEP"- Ready for tapping card "CARD READ" – Reading card i nformation "PROCESSING" + "BEEP" – Card reading process successfully completed "APPROVED" + "BEEP" – Transaction completed A rolling dot "." – Standby mode
Key Management	DUKPT, MK/SK
Encryption Algorithm	TDES
Supported OS	Android 2.1 or above iOS 6.0 or above Windows Phone 8 MS Windows
Operating Temperature	0°C – 45°C (32°F – 113°F)
Operating Humidity	Max 95%
Storage Temperature	-20°C – 55°C (-4°F – 131°F)
Storage Humidity	Max 95%

FCC Caution Statement

- FCC Supplier's Declaration of Conformity:
- BBPOS / QB33 (CHB80)
- This equipment complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
 - (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

- · BBPOS Corp.
- 970 Reserve Drive, Suite 132 Roseville, CA 95678
- www.bbpos.com

Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Documents / Resources



bbpos QB33 Intuit Node [pdf] Instruction Manual QB33, 2AB7X-QB33, 2AB7XQB33, QB33 Intuit Node, QB33, Intuit Node

References

• **BBPOS** – Business Beyond Point of Sale

Manuals+