

### **BDE-RFM208-IN Multi-Band Wireless Module User Guide**

Home » BDE » BDE-RFM208-IN Multi-Band Wireless Module User Guide 🖺



#### Contents

- 1 BDE-RFM208-IN Multi-Band Wireless Module
- 2 Introduction
- 3 Build Your First Application
- **4 Multi-Band Wireless Module**
- 5 Software Development Kit (SDK) installation
- **6 Revision History**
- 7 Documents / Resources
- **8 Related Posts**



#### **BDE-RFM208-IN Multi-Band Wireless Module**



#### Introduction

This user guide is for BDE-RFM208-IN, a Wireless Module based on TI CC1352R. It is a quick start guide for how to connect the module with the evaluation board BDE-EVB07 or with the TI launchpad, and how to build the first application. It also shows a demo for how BDE-RFM208-IN receives a data packet that is sent from another BDE-RFM208-IN.

#### **Get Ready**

The following tools are recommended to develop with BDE-RFM208-IN.

#### **Hardware tools:**

- Two modules of BDE-RFM208-IN (BDE-RFM208-IN-BDE Technology Inc. (bdecomm.com))
- Two BDE-ADP208 V1.0 (adaptor board)
- PC or Laptop
- Two BDE-EVB07 (BDE-EVB07-BDE Technology Inc. (bdecomm.com)) or
- Two TI Launchpad (LAUNCHXL-CC13X2R1 Evaluation board | Tl.com)
- USB cable for power supply and debugging

#### Software tools:

- Terminal software such as CCS, IAR.
- · CCS download
- Software Development Kit (SDK)


#### **Build Your First Application**

Once have the Hardware and Software tools in place, please following the following steps: Connect the Hardware


If chose EVB07: Use USB cable to connect EVB07 and PC or laptop. Plug BDE-RFM208-IN with the adaptor

board into the dev board and connect all the pins with Jumpers as the following picture shows.

### **Multi-Band Wireless Module**



If chose TI Launchpad: The connection is as follows.



Connection Designator	BDE-RFM208-IN LaunchPad Pin	
3V3 Power	VDD	3V3
Ground	GND	GND
RST	RST	RESET
TMS	TMS	TMS
TCK	TCK	TCK
TDO	DIO16	TDO
TDI	DIO17	TDI

Optional: TDO TDI RXD TXD


**Build the Application** 

#### · Download and install the CCS and SDK

From the above links, follow the instructions in the following steps to download and install the CCS and SDK.

#### • ■ CCS Installation


1. Click on this option




2. Select an option to download CCS


## Download options






5. Click "Next"


















8. Select the Installation Directory




9. Select the default option








1. Click on this option



2. Select an option you need to download SDK



3. Log in to your TI account, if you are a new user, register a TI account first

# myTl account

# Existing myTl user?



TI's Terms of use & Privacy policy.


4. Select "civil" if your application is for civil use



#### 5. Select "Yes" and submit

compliance with any such import, use, or export restrictions.

- I / We hereby certify that we will adhere to the conditions above.
- I / We do not know of any additional facts different from the above.
- I / We take responsibility to comply with these terms.
- I / We understand we are responsible to abide by the most current. versions
  of the Export Administration Regulations and other U.S. export and
  sanctions laws.




#### 6. Download SDK

## TI Request


# You have been approved to receive this file. Click "Download" to proceed.

In a few moments, you will also receive an email with the link to this file.




Thank you, Texas Instruments

#### 7. Installation




8. Click "Next"




9. Select the default option




10. Select the Installation directory



11. Click "Next"




12. Waiting for installation to complete




#### Run an example/demo code

1. For the first module, find the option named "Import CCS project..."




According to the following path to find the sending end project:
 ti\simplelink\_cc13x2\_26x2\_sdk\_5\_10\_00\_48\examples\rtos\CC1352R1\_LAUNCHXL\ easylink\
 rfEasyLinkRx\tirtos\ccs




3. Right Click the project to build the receiving end project

📦 workspace\_v18 - Code Composer Studio

File Edit View Navigate Project Run Scripts Window Help



4. Click this bug icon (means download and debugging)



5. C lick on this option to start debugging

```
workspace v22 - rfEasyLinkRx CC1352R1 LAUNCHXL tirtos ccs/rfEasyLinkRx.c - Code
 File Edit View Project Tools Run Scripts Window Help
E

♦ Debug ☒

▼ ® rfEasyLinkRx ■1352R1 LAUNCHXL tirtos ccs [Code Composer Studio - Device Devic
         Texas Instruments XDS110 USB Debug Probe/Cortex M4 0 (Suspended - HW Br
                       = main() at rfEas LinkRx.c:211 0x00003524
                       c int00() at boot.asm:254 0x00004E14 ( c int00 does not contain frame info
  208 * ====== main =======
    209 */
    210 int main(void)
211 {
                            /* Call driver init functions */
    212
    213
                           Board_initGeneral();
    214
                           /* Open LED pins */
    215
                           ledPinHandle = PIN open(&ledPinState, pinTable);
    216
                           Assert_isTrue(ledPinHandle != NULL, NULL);
    217
    218
                           /* Clear LED pins */
    219
    220
                           PIN_setOutputValue(ledPinHandle, CONFIG_PIN_GLED, 0);
    221
                           PTN setOutputValue(ledPinHandle CONFIG PTN RIFD 0):
```

6. Find the file which is named "rfEasyLinkRx.c" and the function which is named "rxDoneCb", and set a breakpoint at the line as the arrows shows

😚 workspace v22 - rfEasyLinkRx CC1352R1 LAUNCHXL tirtos ccs/rfEasyLinkRx.c - Code Compos File Edit View Project Tools Run Scripts Window Help ♦ Debug 

□ Texas Instruments XDS110 USB Debug Probe/Cortex M4 0 (Running) 🖻 rfEasyLinkRx.c 🖾 runction definitions \*\*\*\*\*/ 94#ifdef RFEASYLINKRX ASYNC 95 void rxDoneCb(EasyLink\_RxPacket \* rxPacket, EasyLink\_Status status) 96 { 97 if (status == EasyLink\_Status\_Success) 98 { 99 /\* Toggle RLED to indicate RX \*/ PIN setOutputValue(pinHandle, CONFIG PIN RLED,!PIN getOutputValu 100

104 /\* Toggle GLED to indicate command aborted \*/
7. For another module, according to the following path to find the sending end project:


ti\simplelink\_cc13x2\_26x2\_sdk\_5\_10\_00\_48\examples\rtos\ CC1352R1\_LAUNCHXL \ easylink\
rfEasyLinkTx\tirtos\ccs

lse if(status == EasyLink\_Status\_Aborted)


102

103


{



8. Right Click the project to build the sending end project




9. Click this bug icon (means download and debugging)



😚 workspace\_v23 - rfEasyLinkTx\_CC1352R1\_LAUNCHXL\_tirtos\_ccs/rfEasyLinkTx.c - Code Co File Edit View Project Tools Run Scripts Window Help □ 3. ⑤ R 田 □ % B ▼ B ▼ B ▼ \* Debug ♡ 🗸 👽 rfEasyLinkTx CC1352R1 LAUNC XL tirtos ccs [Code Composer Studio - Device Debug Texas Instruments XDS110 USB Debug Probe/Cortex M4 0 (Suspended - HW Break) = main() at rfEasyLinkTx.c:250 0x00003500 c int00() at boot.asm:254 0x00004E50 ( c int00 does not contain frame information of contain frame info ☐ rfEasyLinkTx.c 
☐ 250 { 251 /\* Call driver init functions. 252 Board\_initGeneral(); 253 254 /\* Open LED pins \*/ 255 pinHandle = PIN\_open(&pinState, pinTable); 256 Assert\_isTrue(pinHandle != NULL, NULL); 257 258 /\* Clear LED pins \*/ 259 PIN\_setOutputValue(pinHandle, CONFIG\_PIN\_GLED, 0); 260 PIN\_setOutputValue(pinHandle, CONFIG\_PIN\_RLED, 0); 261 262 txTask\_init(pinHandle); 263 /\* Start BIOS \*/ 264 265 BIOS\_start(); 266 267 return (0); 268}

11. You can see the lights flashing (means sending a data uninterruptedly)



12. The program stops at the breakpoint

🙀 workspace v22 - rfEasyLinkRx CC1352R1 LAUNCHXL tirtos ccs/rfEasyLinkRx.c - C File Edit View Project Tools Run Scripts Window Help P Texas Instruments XDS110 USB Debug Probe/Cortex M4 0 (Suspended - HW) = rxDoneCb(struct <unnamed> \*, int)() at rfEasyLinkRx.c:100 0x000039C2 < In rfEasyLinkRx.c 

 □ runction definitions \*\*\*\*\*/ 94#ifdef RFEASYLINKRX ASYNC 95 void rxDoneCb(EasyLink\_RxPacket \* rxPacket, EasyLink\_Status st 96 { if (status == EasyLink Status Success) 97 98 { /\* Toggle RLED to indicate RX \*/ 99 PIN setOutputValue(pinHandle, CONFIG PIN RLED,!PIN get 100 101 else if(status == EasyLink\_Status\_Aborted) 102 103 { /\* Toggle GLED to indicate command aborted \*/ 104 PIN setOutputValue(pinHandle, CONFIG PIN GLED, !PIN get 105 106 107 else 108 /\* Toggle GLED and RLED to indicate error \*/ 109 PIN setOutputValue(pinHandle, CONFIG PIN GLED, !PIN get 110 PIN setOutputValue(pinHandle, CONFIG\_PIN\_RLED,!PIN\_get 111

By far you should've built your first application successfully. For further development, please check out the CC1352R1 datasheet, product information, and support | Tl.com page and download the User Guide (https://www.ti.com/lit/pdf/swcu185)

#### **Other Resources**

112

- Mac OS Installer for SimpleLink CC13X2 26X2 SDK
- Linux Installer for SimpleLink CC13X2 26X2 SDK
- Mac OS Installer for Code Composer Studio IDE
- Linux Installer for Code Composer Studio IDE

}

- CC1352R SimpleLink™ High-Performance Multi-Band Wireless MCU
- Windows Installer for SmartRF Flash Programmer 2

#### **Revision History**

Revision	Date	Description
V1.0	15-Feb-2020	Initial Released
V2.0	14-Apr-2021	Changed template

#### **More Questions:**

Please search existing answers on TI E2E support forums Contact your local TI sales representative.

Or

Contact BDE Technology, Inc.

#### China:

B2-403, 162 Science Ave, Huangpu District, Guangzhou, 510663

**Tel:** +86-020-28065335

Website: http://www.bdecomm.com/cn/ Email: shu@bdecomm.com

#### USA:

67 E Madison St, #1603A, Chicago, IL 60603

Tel: +1-312-379-9589

Website: <a href="http://www.bdecomm.com/">http://www.bdecomm.com/</a> Email: <a href="mailto:info@bdecomm.com/">info@bdecomm.com/</a>

#### **Documents / Resources**



BDE BDE-RFM208-IN Multi-Band Wireless Module [pdf] User Guide

BDE-RFM208-IN, Multi-Band Wireless Module

Manuals+,