



behringer CL9 Compressor Limiter User Guide

[Home](#) » [Behringer](#) » behringer CL9 Compressor Limiter User Guide 

behringer CL9 Compressor Limiter User Guide



Contents

- 1 COMPRESSOR/LIMITER CL9
- 2 Documents / Resources
 - 2.1 References
- 3 Related Posts

COMPRESSOR/LIMITER CL9

Thank you for showing your confidence in us by purchasing the BEHRINGER COMPRESSOR/LIMITER CL9. This ultimate effects pedal is specifically designed to achieve super-smooth compression and extended sustain. Thanks to its high-performance features you can compress loud and boost low signals without degrading the original sound. A compressor limits the dynamic range of a signal. This means that signal peaks will be attenuated and the level differences between loudest and softest playing are reduced. This results in a more powerful tone.

CONTROLS



1. The ATTACK TIME control determines how fast the compressor responds to input signal peaks.
2. The LEVEL control adjusts the output level.
3. The SUSTAIN control determines the amount of compression.
4. The ON/BATT LED illuminates when the effect is activated. It also serves as a battery level indicator.
5. Use the footswitch to activate/deactivate the effect.
6. Use this 1/4" TS IN connector to plug in the instrument cable.
7. The 1/4" TS OUT connector sends the signal to your amp.

Use the DC IN connection to plug in a 9 V power supply (not included). The BATTERY COMPARTMENT is

located underneath the pedal cover. To install or replace the 9 V battery (not included), press the hinges with a ballpoint pen and remove the pedal cover. Be careful not to scratch the unit

The CL9 has no on/off switch. As soon as you insert the plug into the IN connector, the CL9 is on. When not in use, remove the plug from the IN connector. This extends the life of the battery.

WARRANTY

For our current warranty terms, please refer to our website at <http://www.behringer.com>.

SPECIFICATIONS

In

Connector 1/4" TS

Impedance 500 k Ω

Out

Connector 1/4" TS

Impedance 1 k Ω

Power supply 9 V , 100 mA regulated

BEHRINGER PSU-SB

USA/Canada 120 V~, 60 Hz

Europe/U.K./Australia 230 V~, 50 Hz

China 220 V~, 50 Hz

Korea 220 V~, 60 Hz

Japan 100 V~, 50/60 Hz

Power connector 2 mm DC jack, negative center

Battery 9 V type 6LR61

Power consumption 30 mA

Dimensions (H x W x D) approx. 54 mm (2 1/8") x 70 mm (2 3/4") x 123 mm (4 4/5")

Weight approx. 0.33 kg (0.73 lbs)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

SAFETY INSTRUCTIONS

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

Die deutsche Anleitung ist erhältlich @ www.behringer.com

Manuel francophone en téléchargement sur www.behringer.com

Manual en Español disponible en www.behringer.com

Manual Italian disponibili @ www.behringer.com

Русскоязычное руководство @ www.behringer.com

Polka instrukcja dustpan jest pod adRise @ www.behringer.com

Nederland's handloading beschikbaar @ www.behringer.com

Suomenkielinen käyttöohje saatavilla osoitteesta www.behringer.com

Sevens manual fins tillgänglig på www.behringer.com

Dansk vejledning findes på www.behringer.com

