

BELL 5374-0 Adjustable Open Center Bracket Owner's Manual

Home » Bell » BELL 5374-0 Adjustable Open Center Bracket Owner's Manual

Contents

- 1 BELL 5374-0 Adjustable Open Center
- **2 Product Usage Instructions**
- 3 Features
- 4 Application
- **5 Dimensions**
- **6 Certifications and Compliance**
- **7 Product Assets**
- 8 FAQ
- 9 Documents / Resources
 - 9.1 References



BELL 5374-0 Adjustable Open Center Bracket



Specifications

• Brand: Bell

• Catalog #: 5374-0

• Stud Spacing: 16 to 24 inches

• Cover Type: Blank/Flat

Material: SteelColor: Gray

• Dimensions:

Depth: 0.063 inHeight: 4.125 inWeight: 0.268 lbWidth: 4.125 in

· Certifications:

• UL Listed

CSA Certified

• Nema Rating: NEMA 3R

Product Usage Instructions

Installation

- 1. Ensure the stud spacing is between 16 to 24 inches.
- 2. Mount the adjustable open center bracket securely on the wall using the provided mounting hardware.
- 3. Place the 4 in. round splice box within the bracket.

4. Secure the box in place using the included gasket.

Adjustable Open Center Bracket for 16" to 24" stud spacing By Bell Catalog # 5374-0
4 in. Round Blank Cover – Box Mount

Features

- Rugged metallic construction
- State-of-the-art powder coat finish provides maximum weather ability and scratch resistance
- Includes gasket and mounting hardware
- Multi-lingual instructions in each package

Application

For use with 4 in. round splice boxes

General

- Color
 - Gray
 - Gris
- Construction Metallic
- Cover Type Blank/Flat
- Material Steel
- Type
 - Cover
 - Cover
- UPC 050169537404

Dimensions

- Actual Depth 0.063 in
- Height 4.125 in
- Weight 0.268 lb
- Width 4.125 in

Certifications and Compliance

- · Certified Listed UL Listed
- CSA Certified
- Nema Rating NEMA 3R

Logistics

- · Carton Quantity 30
- · Packaging Type Shrink
- Pallet Quantity 4500
- Standard Package 30

Product Assets

- Catalogs RACO / TayMac / Bell Full Catalog
- Certifications UL COC E195978-2
- Customer Notices Prop 65 Cancer & Reproductive Harm
- Notice
- Sales Drawings 4_ Round Cover
- SDS HCC_SDS
- Sell Sheets Wet Location 4 in. Round Blank Metal Cover
- Terms and Conditions HCC Terms & Conditions

A proud member of the Hubbell Family.

FAQ

What is the maximum stud spacing for this bracket?

The bracket is designed for stud spacings between 16 to 24 inches.

What certifications does this product have?

This product is UL Listed and CSA Certified for safety and compliance.

Is the cover weatherproof?

Yes, the rugged metallic construction and powder coat finish provide maximum weather ability, and it has a NEMA 3R rating for outdoor use.

What is included in the package?

The package includes the adjustable open center bracket, mounting hardware, gasket, and multi-lingual instructions.

©2024 Hubbell Incorporated. All rights reserved. BELL_MX-5374-0-SPEC-EN | REV 1/2024

Documents / Resources



<u>BELL 5374-0 Adjustable Open Center Bracket</u> [pdf] Owner's Manual 5374-0 Adjustable Open Center Bracket, 5374-0, Adjustable Open Center Bracket, Open Center Bracket, Bracket

References

User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.