


BEOK CONTROLS
BOT306RF WIFI Boiler
Thermostat



BEOK CONTROLS BOT306RF WIFI Boiler Thermostat Instruction Manual

[Home](#) » [BEOK CONTROLS](#) » BEOK CONTROLS BOT306RF WIFI Boiler Thermostat Instruction Manual 

Contents

- 1 BEOK CONTROLS BOT306RF WIFI Boiler Thermostat
- 2 Product Information
- 3 Product Usage Instructions
- 4 Product Summary
- 5 Technical Parameter
- 6 Main Button Instruction
- 7 User Interface Explanation
- 8 Model Spec
- 9 Operation Instruction
- 10 Advanced Setting
- 11 Wiring Diagram
- 12 WIFI Configure
- 13 Installation Instruction
- 14 Set Sequence Number
- 15 ATT
- 16 Documents / Resources
 - 16.1 References
- 17 Related Posts



BEOK CONTROLS BOT306RF WIFI Boiler Thermostat



Product Information

Specifications

- **Model:** BOT306RF-WIFI
- **Wireless Function:** Yes
- **Terminal Receiver:** BOT-W306
- **Wi-Fi Function:** BOT-X306

Technical Parameters:

- **Working Voltage:** USB Type C (5V)
- **Current Load:** 3A
- **Setting Temperature Range:** 5-35°C
- **Limiting Temperature Range Consumption:** Temperature Sensor

Product Usage Instructions

Installation

1. Choose a suitable location for mounting the thermostat, ensuring it is within range of your heating system.
2. Connect the thermostat to the power source using the provided USB Type C cable.
3. Follow the manufacturer's instructions to pair the thermostat with the receiver and set up the Wi-Fi connection if needed.
4. Mount the thermostat securely on the wall or place it on a flat surface.

Operation:

To set the desired temperature:

1. Press the temperature adjustment buttons to increase or decrease the temperature.
2. Use the menu options on the LCD screen to access additional settings such as scheduling and modes.
3. Confirm your selections by pressing the appropriate buttons on the thermostat.

Frequently Asked Questions (FAQ)

Q: Can the thermostat be controlled remotely via a smartphone?

A: Yes, if the Wi-Fi function is enabled and set up, you can control the thermostat remotely using a compatible smartphone app.

BOT306RF-WIFI BOILER THERMOSTAT















Product Summary

BOT series boiler thermostats are with LCD digital display big screen, and it is developed according to the market's requirements. Thermostats can be installed on the wall, or directly put on the table. This series of thermostats are easy to operate and with complete functions. It can be used to control boilers, motorized ball valves, motorized valves, electric valves, solenoid valves, etc.


Technical Parameter

Working Voltage	USB type C (5V)
Current Load	3A
Temperature Control Accuracy	$\pm 1^{\circ}\text{C}$ (0.5-4.5 $^{\circ}\text{C}$ adjustable)
Setting Temperature Range	5-35 $^{\circ}\text{C}$
Limiting Temperature Range	5-35 $^{\circ}\text{C}$
Consumption	<0.3W
Temperature Sensor	NTC

Main Button Instruction

-  : ON/OFF Switch;
-  : Mode Button. Switch between  Manual Mode  Auto Period Control Mode,  Temporary Manual Mode. Long press to enter period setting.
-  : Time Set. Hour, minute and week setting;
-  : Up Button. To increase temperature. When press it with  and  it can set programmable function;
-  : Down Button. To reduce temperature. When press it with  and  it can set programmable function;
-  : Key Lock. Long press  5 seconds to lock or unlock;

User Interface Explanation



☺:Manual Control. ⌚:Temporary Manual Control. ⚙️:Auto Control.

🔥:Heating.

☀️:First Period. Wake up in the morning.

🏠:Second Period. Out of home in the morning.


🏠:Third Period. Go home in the afternoon.

🏠:Forth Period. Out of home in the afternoon.

🏠:Fifth Period. Go home in the evening.

🌙:Sixth Period. Sleep in the evening.

❄️: Anti-frozed function open.



Model Spec


Model	Wireless Function	Terminal Receiver	Wi-Fi Function
BOT-W306			
BOT-X306	✓	✓	
BOT306RF-WIFI	✓	✓	✓



Operation Instruction

Time Setting



Press , ⌚ the time area will display Minute, Hour and Week, then press or ▲ or ▼ to modify time.

Programmable Period Temperature Setting




First step, long press , screen display Loop(Cycling Control), screen displays 12345 (From Monday to Friday); Press  one time, it displays 123456 (From Monday to Saturday); Press two times, it displays 1234567 (From Monday to Sunday);

Second step, time and temperature setting in every period. When screen display 12345 or 123456 or 1234567,

press  to enter temperature setting. Press  to enter time setting. To modify and save through or .









Att: When auto-control ,if user needs to reset the temperature, it can be changed to temporary manual control.

Temporary manual control means when the thermostat is in auto-control mode(program mode), user press  or to modify temperature setting, thermostat now is in temporary manual control state. When next periods comes, thermostat will automatically return to the acquiescent period program control mode.

Programmable Period Time Setting

First press  then press  to change to time options, user can modify time in the period.


Default Program Data

Period	Icon	Default Time	Default Temperature
Workday	1 	06:00	20°C
	2 	08:00	15°C
	3 	11:30	15°C
	4 	12:30	15°C
	5 	17:30	22°C
	6 	22:00	15°C
Weekends	1 	08:00	22°C
	2 	23:00	15°C

Att:

1. The default temperature values of 3 and 4 period in workday is same with 2 period. If user need, please change this default temperature.
2. Setting temperature is 00, it means this period is power off.


Advanced Setting



In the state of power-off, long press and hold [clock icon] then press [power icon] into advanced setting mode. Then press [circular arrow icon] to set relative item.

Display Code	Function	Setting And Options	Factory Default
dIF	Limit temp. return difference	0.5-4.5℃	1℃
SVH	Set temp. upper Limit	5-35℃	35℃
SVL	Set temp. low limit	5-35℃	5℃
Adj	Measure temp.	-5-5℃(0.5℃accuracy correction)	0.0℃
FrE	Anti-frozen	00 : Close anti-frozen 01 : Open anti-frozen	00
LOC	Button lock function	00: Unlock 01: except power switch, all buttons are locked 02: All buttons are locked	00
SNP	Set Sequence Number	00 : Close this function 01 : Open this function	0
FAC	Factory setting	08 : Just display 00 : Return to factory setting	08

Wiring Diagram



The button inside receiver is Reset button. When status indicator light stay on or not on, user can press reset button to resume normal work.

Att:

Installation wires should be changed to be 1.5-2.5mm² hard line.

Please rightly connect the wires strictly according to the connect diagram. Don't make water, mud and other debris into the thermostat, otherwise it will damage the thermostat.


WIFI Configure

1. Install APP on phone

For iOS system: Login in App Store, search “ Beek RF Boiler”, you can download it on your iphone.


For Android System: Login in Google Play, search “ ”, you can download it on your phone. Beek RFBoiler

2. Connection Thermostat with Phone




Thermostat Setting










1. Download and Install APP on phone.
2. Press thermostat button for 10 seconds when thermostat is in turn-off state, then WIFI signal will appear and quickly twinkle.
3. Enter your wifi name and password, then start connection configure.




APP Interface on the Phone



Thermostat Setting through Phone Operation

1. Clock : You can press Time Matching  switch to match your phone clock with thermostat clock.
2. Children lock (screen locking) : Press  to lock the thermostat.
3. Anti-Freezing: Press  thermostat will show  on the screen , it means Anti-freezing function open.
4. Temperature setting: You can drag the pointer on Temperature  Setting Dial to set temperature. Or press  and to set temperature step. directly
5. .Period setting: Long press Period Display, then you will go into the Period Setting mode:
6. Advanced Setting: Long Press Senior  , you will go into Advanced setting mode:
7. Switch of Manual mode and Auto mode: Press  to switch manual mode or Auto mode.
8. Power off : Press  to turn on or off thermostat.

Installation Instruction



Insert the equipped USB (Type-C) connector into the charger.

Set Sequence Number



1. Every thermostat has a matched receiver, and thermostat and receiver have a same group of sequence number. If user mix during installation, sequence number can be set through the following method.(Sequence number is unique)







2. In Advance Setting, SNP need to be set 01. Then to set SN through the following four steps.




The first step, press button under power off state, then press button, then press button to enter parameter setting;



The second step, after appearing SN1, press  or to modify the number;

The third step, every time pressing once , it will appear SN2, SN3, SN4, SN5 and SN6 in order. Refer to second step, press  or  or to modify.



The forth step, after SN is finished setting, if CHK Code is the same with bar code, it is correct. If not consistent, it is not correct. Please input again.

3.VAC: Control valves1-8 place numbers. The default value is 01.

(This setting is only useful when thermostat is applied to control Wireless Main-Control Centralize d Controller. If thermostat is used to control boiler, this setting must be 01.)

ATT

Thank you for buying this product!

Please read this manual for complete instructions on installing and operating your thermostat. If you require further assistance, please feel free to contact us.

In the box you will find:


Model	BOT-W306	BOT-X306	BOT306RF-WIFI
Thermostat	✓	✓	✓
User Manual	✓	✓	✓
Screws	✓	✓	✓
Receiver		✓	✓
USB Cable			✓
Support Bracket			✓

Our Service:

We offer the warranty of 24 months from the sales day.

During the warranty, if it is belong to the quality issue, we will fix or replace them for you by free after test them.

If it is not quality problem or beyond the warranty time, we will charge for the after-sales service.




Warning:

The symbol means the unit is being installed, it may cause electrical shock hazard during maintaining, so please make sure it is operated by the professional technical worker.



Documents / Resources

	<p>BEOK CONTROLS BOT306RF WIFI Boiler Thermostat [pdf] Instruction Manual BOT-W306, BOT-X306, BOT306RF-WIFI, BOT306RF WIFI Boiler Thermostat, BOT306RF, WIFI Boiler Thermostat, Boiler Thermostat, Thermostat</p>
---	---

References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.