

BLUEVOLUTION FTXTP-M + RXTP-R Wall Mounted Unit User Guide

Home » BLUEVOLUTION » BLUEVOLUTION FTXTP-M + RXTP-R Wall Mounted Unit User Guide Talente (1997)



BLUEVOLUTION

Contents

- 1 BLUEVOLUTION FTXTP-M + RXTP-R Wall Mounted Unit User
- 2 Documents / Resources
- **3 Related Posts**

BLUEVOLUTION FTXTP-M + RXTP-R Wall Mounted Unit User Guide



Wall mounted unit providing high efficiency and comfort down to -25°C

- Guaranteed heating capacity at low ambient temperature, down to -25°C
- The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- Seasonal efficiency values: full range A++ in cooling and heating
- Onecta app: control your indoor from any location with an app, via your local network or internet.

- Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc
- Space saving contemporary wall mounted design
- Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces



More details and final information can be found by scanning or clicking the QR codes.




Efficiency data		,	TXTP + RXTP	25M + 25R	35M + 35R	
Cooling capacity	Min./Nom./Max.		kw	0.80/2.50/4.00	0.80/3.50/4.40	
Heating capacity	Min./Nom./Max. kW			1.20/3.20/6.20	1,20/4,00/6,70	
Power input	Cooling	Nom.	WW.	0.57	0.92	
	Heating	Nom.	kW	0.65	0.90	
	Energy efficiency class					
	Capacity	Pdesign	kW	2.50	3.50	
	SEER	nenda Rede TV		7.10	7.20	
	Annual energy co	onsumption	kWh/a	125	170	
ge climate)	Energy efficiency class				33	
	Capacity	Pdesign	kW/	2.50	3.00	
	SCOP/A		22701	4.93	4.81	
	Annual energy of	onsumption	kWh/a	710	873	
climate)	Energy efficiency class					
	Capacity	Pdesignh	kW	3.65	4.38	
	Annual energy consumption kWh/a			1,941	2,394	
	SCOP/C			3.95	3.84	
Nominal efficiency	EER			4,40	3.80	
	COP			4.95	4.44	
	Annual energy of	onsumption	kWh	284	461	
	Energy labeling Directive Cooling/Heating			A/A		

Indoor unit				FTXTP	25M	358	
Dimensions	Unit	Heighb\W	AdthsDepth	mm	286x770x225		
Weight	Unit	kg			9.00		
Air filter	Type				Removable/washable		
Fan	Air flow rate	Coaling	Silent operation/Low/ Medium/High			3.9/5.5/8.3/11.5	
		Heating	Silent operation/Low/ Medium/High	m²/min		4.5/5.6/8.7/11.5	
Sound power level	Cooling dBA					58	
	Heating dBA		dBA	58			
Sound pressure level	Cooling			dBA	21/26/43		
	Heating	ing Silent operation/Low/High dBA		ABb		21/26/43	
Control systems	Infrared remote control				ARC480A53		
Outdoor unit				RXTP	25R	358	i
Dimensions	Unit	Heights/WidthxDepth mm			551x763x312		
Weight	Unit	kg		38			
Sound power level	Cooling	g Nom.		dBA	61.0		
	Heating	g Nom. d		ABb	61,0		
Sound pressure level	Cooling	ng Nom.		dBA	48		
	Heating	leating Nom.		dBA	49		
Operation range	Cooling	Ambient MinMax.		*CDB	-10-46		
	Heating	eating Ambient MinMax. 1		"CWB	-25-18		
Refrigerant	Type				R-32		
	GWP				675		
	Charge IgNOSs		1.1/0.75				
Piping connections	Liquid	guid 00 m		mm	6.35		
	Gas	00		mm		9.50	
	Piping length	OU-IU	Max.	m		20	
	Additional refrigerant charge kg/m			kg/m	0.02 (for piping length exceeding 10m)		
			m	18			
Power supply	Phase/Frequency/Voltage Hz/V			Hz/V	1-/50 /220-240		
Current - 50Hz	Maximum fuse amps (MFA) A				16		

Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range | See separate drawing for electrical data | Cooling: indoor temp. 27°CDB, 19.0°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | **Heating:** indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | Contains fluorinated greenhouse gases

Read More About This Manual & Download PDF:

Documents / Resources



<u>BLUEVOLUTION FTXTP-M + RXTP-R Wall Mounted Unit</u> [pdf] User Guide FTXTP-M RXTP-R Wall Mounted Unit, FTXTP-M RXTP-R, Wall Mounted Unit, Un it

