



BLUSTREAM IP500UHD-TZ Multicast UHD Transceiver User Manual

[Home](#) » [BLUSTREAM](#) » BLUSTREAM IP500UHD-TZ Multicast UHD Transceiver User Manual 



IP500UHD-TZ Multicast UHD Transceiver User Manual

Contents

- [1 IP500UHD-TZ Multicast UHD Transceiver](#)
- [2 Specifications](#)
- [3 Documents / Resources](#)
- [4 Related Posts](#)


IP500UHD-TZ Multicast UHD Transceiver

Description

The Blustream IP500UHD-TZ Transceiver is an SDVoE compliant AV over IP solution that provides the highest quality, uncompromised 4K with zero latency Audio/Video extension over copper or optical fibre 10G networks.

The IP500UHD-TZ includes support for HDMI 2.0 encompassing distribution of HDR (High Dynamic Range), 10-bit colour content and multi-channel HD audio signals. The IP500UHD-TZ provides advanced features including PoE+ and transmission of multiple control and data signals alongside audio and video, including IR, RS-232, USB (KVM) and 1Gb Ethernet.

The IP500UHD-TZ is ideal for 18Gbps HDMI installations where multiple transceivers can be combined with one or more 10GbE copper / fibre switches to form a distributed video matrix, multi-viewer or video wall system.



Key Features

- Advanced 18Gbps UHD Video over 10Gb network with uncompromised video quality and zero latency
- Supports HDMI 2.0 18Gbps specification with pass-through for up to 4K 60Hz 4:4:4 and 10/12-bit HDR sources, including Dolby Vision LLM (Low Latency) up to 12-bit
- Supports video scaling and single-frame switching
- Supports all known digital HDMI audio formats including Dolby TrueHD, Atmos, DTS-HD Master Audio and DTS:X transmissions
- Support fixed signal routing function for IR, RS-232, CEC and USB
- USB end to end/point to point pass-through
- Analogue L/R audio embedding and audio breakout (balanced and unbalanced)
- Bi-directional 10/100/1000BaseT Ethernet pass-through
- Supports bi-directional 5V or 12V IR pass-through
- PoE (Power over Ethernet) to power Blustream products from PoE+ switch
- HDCP 2.2 compliant with advanced EDID management

- Local 12V 2.5A power supply (should Ethernet switch not support PoE+) (power supply sold separately)
- Features 4 operational modes:
 - Matrix distribution (requires 10Gb network switch)
 - Video wall (requires 10Gb network switch)
 - Multiview mode (requires 10Gb network switch)
 - One-to-one HDMI extender (no network switch required)



Connectivity

- Video Input: 1x HDMI Type A, female
- Video Output: 1x HDMI Type A, female
- Audio Input / Output Connector : 1x 5-Pin Phoenix connector
- Ethernet Port: 1x 10GBaseT RJ45 video network, 1x SFP+ module video network, 1x 1Gb LAN RJ45 pass-through
- RS-232 Serial Port: 1x 3-Pin Phoenix connector
- USB / KVM Port: 1x USB-Type B (host) , 2x USB-Type A (device)
- IR Input: 1x 3.5mm stereo jack
- IR Output: 1x 3.5mm mono jack

Specifications

- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature : -4°F to 140°F (-20°C to 60°C)
- Unit Dimensions (W x D x H): 190mm x 156mm x 25mm (without feet & connections)
- Unit Dimensions (W x D x H): 190mm x 159mm x 29mm(with feet & connections)
- PoE+ draw: 12.8W (typical), 13.5W (max load)

Included Accessories


IR Accessories	1 x IRR, 1 x IRE
Serial Accessories	1 x DB9
Rubber Feet	4 x
Rack Mount	1 x Mounting Kit

Control

IR
App (via ACM500)
RS-232 (via ACM500)
TCP-IP (via ACM500)
Front Panel Buttons

Regulatory Compliance










Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.



Documents / Resources

	<p>BLUSTREAM IP500UHD-TZ Multicast UHD Transceiver [pdf] User Manual IP500UHD-TZ Multicast UHD Transceiver, IP500UHD-TZ, Multicast UHD Transceiver, UHD Transceiver, Transceiver</p>
---	---