



BOSS Speaker and Amplifier System User Manual

[Home](#) » [Boss](#) » BOSS Speaker and Amplifier System User Manual 



Contents

- [1 BOSS Speaker and Amplifier System User Manual](#)
- [2 Specifications](#)
- [3 Bluetooth](#)
- [4 Contents](#)
- [5 Features](#)
- [6 Installation](#)
- [7 Wiring](#)
- [8 Power Switch](#)
- [9 Connections](#)
- [10 Amplifier and Loudspeaker Mounting Installation](#)
- [Reminder](#)
- [11 Documents / Resources](#)
- [12 Related Posts](#)

BOSS Speaker and Amplifier System User Manual



MCBK425BA

BLUETOOTH® | 3" (76 mm) WEATHER RATED SPEAKER AND AMPLIFIER SYSTEM FEATURING BUILT-IN AMPLIFIER

BOSS Audio Systems

3451 Lunar Court – Oxnard, CA 93030

www.bossaudio.com

805-751-4853 Customer Service

Tech Support: www.bossaudio.com/support



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by BOSS Audio Systems is under license. Other trademarks and trade names are those of their respective owners.

Congratulations on your purchase of a BOSS Audio Systems amplified speaker system. It has been designed, engineered and manufactured to bring you the highest level of performance and quality, for years of listening pleasure.

Thank you for making BOSS AUDIO SYSTEMS your choice for entertainment!

Specifications

Operation Voltage	10 ~ 16 V
Total Harmonic Distortion	<0.1%
Signal-to-Noise	>75 dB
Channel Separation	>50 dB
Frequency Response	50Hz - 15KHz
Speaker Wires	5.5'
Volume Control Wire	4.9'
Audio Input Cable	0.8'
Power Cable	5.5'
In-Line Fuse/Power Cable	4.9'
Clamp Size Range	0.75" ~1.25"
Fuse Rating	7.5A

Bluetooth

To pair and connect your Bluetooth device to the MCBK425BA Enter Settings> Bluetooth Menu > Search > "Boss Audio MCBK425BA" > If Prompted to enter a passcode enter : "0000"

Contents

- High-Performance, Weatherproof Speakers 2 PCS
- Speaker Clamp Mounting Hardware 1 PAIR
- Rubber Mounting Shims 4 PCS
- Power Plug with Fuse – 1 PC
- Users Manual 1 PC

Features

- On/Off Switch
- Aux-In (3.5 mm)

- Speaker Clamp Mounts
- Weatherproof Volume Control
- High-Impact, High Temperature Speaker Enclosures
- Weatherproof Speakers
- Bluetooth® Audio Streaming

Installation


1. Screw the clamps to the bottom of the speakers.
2. Find a safe, ideal mounting location and fit the clamps over the chosen mounting bars.
3. Fasten the mounting screws after you review the safety of the mounting location.

Wiring


1. Remove the seat.
2. Route the fused power leads to the battery. (keep away from moving parts and/or hot exhaust)
3. Connect the RED ring terminal to the +12V post of the battery.
4. Connect the BLACK ring terminal to ground post of the battery.
5. Connect to the connector the white mating connector leading the speaker.

Power Switch

1. The switch is used to Power On/off the system.
2. It can be mounted near the volume control for easy access.
3. Reinstall the seat



Connections




Note:

1. AUX 3.5 female input connector for output of other audio device like mobile phone, MP3, I pod and so on.
2. Should use standard 3.5mm 3-pole male plug AUX cable (not included).
3. Stop BT connection first when using the 3.5mm AUX input as an audio source input.

Amplifier and Loudspeaker Mounting Installation Reminder


The components and wiring should not be installed around any moving parts, keep away from ignition parts, fuel lines, or any hot exhaust.

Speakers should not be installed where they might inhibit safety features on the vehicle (i.e. lights, horns, brake levers, etc ...).



Read More About This Manual & Download PDF:

Documents / Resources

	<p>BOSS Speaker and Amplifier System [pdf] User Manual BOSS, Speaker and Amplifier System, MCBK425BA</p>
---	--