

BUILT BRIGHT

BB6110B Work
Bar Strobe 4
Slim



BUILT BRIGHT BB6110B Work Bar Strobe 4 Slim Installation Guide

[Home](#) » [BUILT BRIGHT](#) » BUILT BRIGHT BB6110B Work Bar Strobe 4 Slim Installation Guide 

Contents

- [1 BUILT BRIGHT BB6110B Work Bar Strobe 4 Slim](#)
- [2 FAQ](#)
- [3 SPECIFICATIONS](#)
- [4 INCLUDED](#)
- [5 INSTALLATION](#)
- [6 WIRING](#)
- [7 FLASH PATTERNS](#)
- [8 WARRANTY](#)
- [9 Documents / Resources](#)
 - [9.1 References](#)

BUILT BRIGHT

BUILT BRIGHT BB6110B Work Bar Strobe 4 Slim



FAQ

Q: What is the warranty period for this product?

A: The product comes with a 5-year warranty against manufacturing defects from the date of purchase.

Q: How do I select different flash patterns?

A: The unit provides a range of flash patterns as listed in the manual. Follow the instructions to set your desired pattern.

Q: What should I do if I need warranty service?

A: In case of requiring warranty service, please contact the authorized dealer from whom you originally purchased the product.

Q: Are there any safety warnings associated with this product?

A: Yes, there is a warning regarding cancer and reproductive harm. Please refer to WWW.P65WARNINGS.CA.GOV for more information.

SPECIFICATIONS

- Input Voltage: 12-24VDC
- Operating Current: 0.96A @ 12VDC
- Operating Temperature: -40° to 149°F (-40° to 65°C)


INCLUDED

- 1x LED light bar
- 1x Mounting Bezel
- 1x 3M VHB tape
- 1x Mounting Gasket
- Mounting hardware

INSTALLATION

1. Mount to a flat surface or one with minimal curvature.
2. Mark drill hole locations on the mounting surface using the gasket or VHB tape as a template.
3. Drill a 25/32" (20mm) hole for the wires protruding from the rear of the unit at the correct location. Deburr any sharp edges from this hole.
4. Mount the light along with the mounting gasket. Use the self tapping screws provided to secure the light. Cover with mounting bezel.

WIRING



- Apply YELLOW wire to +VDC:
- Less than 1 second for next pattern
- 2-4 seconds for previous pattern
- 5-7 seconds for default pattern
- 7+ seconds for steady burn
- Synchronization: After setting each light at the right pattern, connect yellow wires of all light heads together.
- Phase Operation: Phase 1 flashes simultaneously with Phase 1, Phase 2 flashes simultaneously with Phase 2, Phase 1 alternates with Phase 2 (Up to 8 units can be synchronized.)

FLASH PATTERNS

FLASH PATTERNS			
1	(Amber) Single Flash, ECE R65 Phase 1*#	27	(Amber) Strobe
2	(Amber) Single Flash, California Title 13 Phase 1*	28	(Amber) Cruise (20%)
3	(Amber) Double Flash Phase 1*	29	(Color 2) Single Flash,ECE R65 Phase 2
4	(Amber) Triple Flash Phase 1*	30	(Color 2) Single Flash, California Title 13 Phase 1
5	(Alt. Amber-Color 2) Single Flash*	31	(Color 2) Single Flash, California Title 13 Phase 2
6	(Alt. Amber-Color 2) Double Flash*	32	(Color 2) Double Flash Phase 1
7	(Alt. Amber-Color 2) Quadruple Flash*	33	(Color 2) Double Flash Phase 2
8	(Alt. Amber-Color 2) Faster Full Bar*	34	(Color 2) Triple Flash Phase 1
9	(Split Amber-Color 2) Left/Right*	35	(Color 2) Triple Flash Phase 2
10	(Split Amber-Color 2) Fast Left/Right*	36	(Color 2) Quadruple Flash Phase 1
11	(Alt. Amber-Color 2) Combination*	37	(Color 2) Quadruple Flash Phase 2
12	(Amber) Single Flash, ECE R65 Phase 2	38	(Color 2) Quintuple Flash Phase 1
13	(Amber) Single Flash, California Title 13 Phase 2	39	(Color 2) Quintuple Flash Phase 2
14	(Amber) Double Flash Phase 2	40	(Color 2) Combo Single/Double Flash Phase 1
15	(Amber) Triple Flash Phase 2	41	(Color 2) Combo Single/Double Flash Phase 2
16	(Amber) Quadruple Flash Phase 1	42	(Color 2) Combo Single/Triple Flash Phase 1
17	(Amber) Quadruple Flash Phase 2	43	(Color 2) Combo Single/Triple Flash Phase 2
18	(Amber) Quintuple Flash Phase 1	44	(Color 2) Combo Single/Quintuple Flash Phase 1
19	(Amber) Quintuple Flash Phase 2	45	(Color 2) Combo Single/Quintuple Flash Phase 2
20	(Amber) Combo Single/Double Flash Phase 1	46	(Color 2) Single Flash Left/Right Split
21	(Amber) Combo Single/Double Flash Phase 2	47	(Color 2) Strobe
22	(Amber) Combo Single/Triple Flash Phase 1	48	(Color 2) Cruise (20%)
23	(Amber) Combo Single/Triple Flash Phase 2	49	(Amber) Steady Burn
24	(Amber) Combo Single/Quintuple Flash Phase 1	50	(Split Amber – Color 2) Quadruple Flash
25	(Amber) Combo Single/Quintuple Flash Phase 2	51	(Alt. Amber – Color 2) Single Flash
26	(Amber) Single Flash Left/Right Split		

* Sync w/ 6002X Series Mini Bar

Default pattern

WARRANTY

ARC Lighting provides a 5 year warranty against manufacturing defects from date of purchase. If warranty service is needed, please contact the authorized dealer of where your product(s) were originally purchased.

Customer Support:

- Phone: [888-608-2220](tel:888-608-2220)
- Email: support@arc.lighting
- Website: www.arc.lighting/warranty-claim


**WARNING: CANCER
AND REPRODUCTIVE HARM**
WWW.P65WARNINGS.CA.GOV

BASTROP, TEXAS 78602
UNITED STATES OF AMERICA
WWW.BUILT-BRIGHT.COM




BUILT RIGHT & DESIGNED BRIGHT | BUILT-BRIGHT.COM

Documents / Resources

	<p>BUILT BRIGHT BB6110B Work Bar Strobe 4 Slim [pdf] Installation Guide BB6110B, BB6110C, BB6110D, BB6110B Work Bar Strobe 4 Slim, BB6110B, Work Bar Strobe 4 Slim, Bar Strobe 4 Slim, Strobe 4 Slim, 4 Slim, Slim</p>
---	--

References

-  P65WARNINGS.CA.GOV
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.