



Carrier SC-43-0200-0001-99 SmartCell Contact Transmitter and Input Device Instruction Manual

[Home](#) » [Carrier](#) » Carrier SC-43-0200-0001-99 SmartCell Contact Transmitter and Input Device Instruction Manual 



SC-43-0200-0001-99

SmartCell Contact Transmitter and Input Device for Information Zones



Contents

- [1 Overview](#)
- [2 Technical specifications](#)
- [3 Documents / Resources](#)
 - [3.1 References](#)

Overview

The SmartCell Input Device is quick and easy to install and offers individual addressing at the SmartCell Control Panel. The device allows non fire to be monitored at the SmartCell Control Panel and to an information alert when activated. Examples may include the monitoring of doors (opening/closing), a loss of power to your fridge, flood detection and an alarm condition on your intruder system.

Features include a resistor monitored input, an alternative magnetic contact option and bidirectional 868 MHz communication.

This device is third party certified and compatible with the full SmartCell product range.

Details

- Full wireless communication with panel
- Quick and easy to install
- Resistor monitored input
- Alternative magnetic contact option (magnet supplied)
- For connection to remote information devices
- NOT FOR FIRE OR SECURITY APPLICATIONS

Technical specifications


General

| | |
|-----------------------|--|
| General | |
| Wireless frequency | 868 MHz |
| Input | |
| Input quantity | 1 |
| Input type and rating | Resistor monitored input |
| Physical | |
| Physical dimensions | 30 x 110 x 28 mm (W x H x D) |
| Net weight | 0.05 kg |
| Colour | White |
| Mounting type | Wall mount |
| Batteries | 1 x ER14505M 3.6 V lithium thionyl chloride battery (Fanso or Titus) |
| Environmental | |
| Operating temperature | -10 to +55°C |
| Storage temperature | 10 to +30°C (with battery) -10 to +55°C (without battery) |
| Relative humidity | 95% noncondensing max. |
| Environment | Indoor |
| Regulatory | |
| Compliance | CE |
| Standards | R&TTE |

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales



Documents / Resources

| | |
|---|--|
|  | <p>Carrier SC-43-0200-0001-99 SmartCell Contact Transmitter and Input Device [pdf] Instruction Manual</p> <p>SC-43-0200-0001-99, SC-43-0200-0001-99 SmartCell Contact Transmitter and Input Device, SmartCell Contact Transmitter and Input Device, Contact Transmitter and Input Device, Transmitter and Input Device, Input Device, Device</p> |
|---|--|

References

- [🌐 Home - Fire Security Products](#)
- [📄 TCPDF](#)
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.