

CEDRAL
C18 Cladding
Board



CEDRAL C18 Cladding Board Installation Guide

[Home](#) » [CEDRAL](#) » CEDRAL C18 Cladding Board Installation Guide 

Contents

- [1 CENTRAL C18 Cladding Board](#)
- [2 Specifications](#)
- [3 Touch Up Paint](#)
- [4 Maintenance](#)
- [5 FAQ](#)
- [6 Documents / Resources](#)
 - [6.1 References](#)
- [7 Related Posts](#)

CEDRAL

CENTRAL C18 Cladding Board



Specifications

- **Product:** Cedral Fibre Cement Facades
- **Features:** Colour Style Finish, Lap Wood Click Smooth
- **Maintenance:** Touchup paint instructions provided
- **Contact:** Etex (Exteriors) UK, Wellington Road, Burton-upon-Trent, Staffordshire, DE14 2AP

Color

- **Style** Lap Click
- **Finish** Wood Smooth

We hope you love your new Cedral facade! This guide is here to offer you advice on maintaining your new Cedral facade so you can enjoy it for many years to come. Should you require any further assistance please don't hesitate to contact your installer/stockist or please contact Cedral directly using the contact details on the reverse.

Touch Up Paint

Depending upon location, Cedral should not require re-painting, however, if it is decided to either change the Cedralcolor or repaint, please contact the technical department for advice on 01283 501505. When Cedral planks are painted in the factory, they go through many processes. The final paint coating is applied to warm planks to make them durable. They durable the board with a slight sheen and cannot be replicated without-up paint on site. This is why the touch-up paint is designed for cut edges and scratches only, it needs to be applied sparingly, using a small/fine artist brush to cut edges and scratches. Any overspill to the front face should be removed immediately using a clean dry cloth.

Maintenance

Periodic inspections of the cladding should be carried out to determine if cleaning is required. Cedral facades in more severe exposures such as coastal locations, areas with high vegetation, etc will need inspections and cleaning more often than other Cedral facades. For minor soiling and general cleaning, we'd advise using warm water using a mild detergent. Use a clean microfibre cloth, nothing like a scourer or steel wool as this could damage the planks. Rinse with clean water and allow the planks to air dry. Ensure that no debris such as leaves or soil builds up at the base of the facade and that no plants or vegetation grow at the base of the facade, to ensure the ventilation for the facade is not blocked.

MORE AT CENTRAL.WORLD



- Etex (Exteriors) UK Wellington Road | Burton-upon-Trent | Staffordshire | DE14 2AP
- infouk@etexgroup.com | 01283 501 555

FAQ


Q: Is touch-up paint necessary for Cedral facades?

A: Touch-up paint is designed for cut edges and scratches only. It is not necessary for general maintenance but can be used if you decide to repaint or change the color.

Q: How can I contact Cedral for further assistance?

A: You can contact Cedral directly using the contact details provided in the manual or reach out to your installer/stockist for help.

Documents / Resources

	CEDRAL C18 Cladding Board [pdf] Installation Guide C18 Cladding Board, C18, Cladding Board, Board
---	--

References

- [User Manual](#)

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.