

CHIPSPACE ESP32 Single 2.4 GHz WiFi and Bluetooth Combo Development Board User Guide

Home » CHIPSPACE » CHIPSPACE ESP32 Single 2.4 GHz WiFi and Bluetooth Combo Development Board User Guide ™

ESP32 Development Board User Guide

Contents

- 1 List of applicable FCC rules
- 2 RF exposure considerations
- 3 Label and compliance information
- 4 Information on test modes and additional testing requirements
- **5 FCC Warning**
- **6 FCC Radiation Exposure Statement:**
- 7 Introduction
- 8 Documents / Resources
- 9 Related Posts

List of applicable FCC rules

FCC Part 15.247

RF exposure considerations

This equipment complies with the FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and any part of your body.

Label and compliance information

FCC ID label on the final system must be labeled with "Contains FCC ID: 2A54N-ESP32" or "Contains transmitter module FCC ID: 2A54N-ESP32".

Information on test modes and additional testing requirements

Contact Shenzhen HiLetgo E-Commerce Co., Ltd will provide a stand-alone modular transmitter test mode. Additional testing and certification may be necessary when multiple modules are used in a host.

Additional testing, Part 15 Subpart B disclaimer

To ensure compliance with all non-transmitter functions the host manufacturer is responsible for ensuring compliance with the module(s) installed and fully operational. For

example, if a host was previously authorized as an unintentional radiator under the Supplier's Declaration of Conformity procedure without a transmitter certified module and a module is added, the host manufacturer is responsible for ensuring that the after the module is installed and operational the host continues to be compliant with the Part 15B unintentional radiator requirements. Since this may depend on the details of how the module is integrated with the host, Shenzhen HiLetgo E-Commerce Co., Ltd shall provide guidance to the host manufacturer for compliance with the Part 15B requirements.

FCC Warning

This device complies with Part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE 1: Any changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. End-users must follow the specific operating instructions for satisfying RF exposure compliance.

Note 1: This module is certified that complies with RF exposure requirements under mobile or fixed conditions, this module is to be installed only in mobile or fixed applications.

A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20-centimeter separation requirement.

A fixed device is defined as a device that is physically secured at one location and is not able to be easily moved to another location.

Note 2: Any modifications made to the module will void the Grant of Certification, this module is limited to OEM installation only and must not be sold to end-users, end-user have no manual instructions to remove or install the device, only software or operating procedure shall be placed in the end-user operating manual of final products.

Note 3: The module may be operated only with the antenna with which it is authorized. Any antenna that is of the same type and of equal or less directional gain as an antenna that is authorized with the intentional radiator may be marketed with and used with, that intentional radiator.

Note 4: For all products markets in the US, OEM has to limit the operation channels in CH1 to CH11 for the 2.4G band by supplied firmware programming tool. OEM shall not supply any tool or info to the end-user regarding Regulatory Domain change.

Introduction

1.1 Overview

ESP32 is a single 2.4 GHz Wi-Fi-and-Bluetooth combo chip designed with the TSMC ultra-low-power 40 nm technology. It is designed to achieve the best power and RF performance, showing robustness, versatility, and reliability in a wide variety of applications and power scenarios.

1.2. WiFi Key Features

- 11 b/g/n
- 11 n (2.4 GHz), up to 150 Mbps
- WMM
- TX/RX A-MPDU, RX A-MSDU
- Immediate Block ACK
- Defragmentation


- Automatic Beacon monitoring (hardware TSF)
- 4 x virtual Wi-Fi interfaces
- Simultaneous support for Infrastructure Station, Sof tAP, and Promiscuous modes
- · Antenna diversity
- Operating temperature range -40C 85C

1.3. Bluetooth Key Features


- Compliant with Bluetooth2 BR/EDR and Bluetooth LE specifications
- Class-1, class-2, and class-3 transmitters without e xternal power amplifier
- Enhanced Power Control
- +9 dBm transmitting power
- NZIF receiver with —94 dBm Bluetooth LE sensitivity
- Adaptive Frequency Hopping (AFH)
- Standard HCI based on SDIO/SPI/UART

- High-speed UART HCI, up to 4 Mbps
- Bluetooth2 BR/EDR Bluetooth LE dual-mode controller
- Synchronous Connection-Oriented/Extended (SCO /SCO)
- · CVSD and SBC for audio codec
- · Bluetooth Piconet and Scatternet
- Multi-connections in Classic Bluetooth and Bluetooth LE
- · Simultaneous advertising and scanning
- Operating temperature range -40C 85C

1.4. Block Diagram



1.5. Pin Descriptions



Documents / Resources



CHIPSPACE ESP32 Single 2.4 GHz WiFi and Bluetooth Combo Development Board [pdf] User Guide

ESP32, 2A54N-ESP32, 2A54NESP32, ESP32 Single 2.4 GHz WiFi and Bluetooth Combo Development Board, Single 2.4 GHz WiFi and Bluetooth Combo Development Board

Manuals+,