

# CombiSteel 7292 Series Countertop Model Ice Cream Display **User Manual**

Home » CombiSteel » CombiSteel 7292 Series Countertop Model Ice Cream Display User Manual



# CombiSteel 7292 Series Countertop Model Ice Cream Display User Manual




#### **Contents**

- 1 CIRCUIT DIAGRAMS
- **2 NON-TROUBLE PHENOMENON**
- **3 SAFETY CAUTIONS**
- **4 PREPARATION &**

#### **INSTALLATION**

- **5 OPERATING CAUTION**
- **6 TEMPERATURE ADJUSTMENT**
- **7 DEFROSTING**
- **8 CABINET CLEANING**
- 9 PACKING LIST
- 10 TECHNICAL DATA
- 11 DISPOSAL
- 12 Documents / Resources
- 13 Related Posts

## **CIRCUIT DIAGRAMS**



NOTICE: These diagrams should be used comparing with the tags.

# **NON-TROUBLE PHENOMENON**

Phenomenon	Cause		
Sound of liquid flowing or boiling	Normal sound of refrigerant in the pipeline, it may also happen when the compressor stops.		
Sound of starting compressor	The motor sounds when the compressor works, the sound will be louder when starting and stopping, which are normal phenomenon.		
Moisture on the outside of the ca binet or surrounding the door.	When it is rainy season or a humid day, there will be slight condensation, w hich is the same reason why there are water drips on the outside of cold cu ps.		
Extraordinary poice	Whether the ground is flat or the machine is stable or not		
Extraordinary noise	Whether the dispenser touches the wall or other things		
Strange small in the cabinet	Whether the ice cream has gone bad		
Strange smell in the cabinet	Whether the cabinet inner need to be cleaned		
Compressor always working	<ul> <li>If the temperature is not low enough, please check:</li> <li>Whether the wind path of the compartment is blocked.</li> <li>Whether the door is not closed tightly or the door is opened too frequently.</li> <li>Whether the ambient temperature is too high.</li> <li>If the inside temperature is too low and it is too hard for scooping, please adjust the electronic thermostat 1-2°C higher(please refer to the tempera ture adjustment).</li> </ul>		

# **SAFETY CAUTIONS**

Please read carefully and observe the following safety precautions.

The power outlet must be in accordance to the tag, an d use a separate European style socket (≥10A) and Pl ug. The sockets of the freezer should be connected to stable ground wire.	The plug and the socket must be fastened together, or it may cause fire. DO NOT crush or drag the plug, DO NOT damage the power wire.
Putting inflammable and explosive dangers and seriou s acid-base things into the cabinet prohibited. DO NO T use appliances inside the cabinet.	If there is electricity leakage, abnormal noise, smells o r smoke, please turn off power and contact our aftersal es service department.
You should install suitable automatic voltage regulator not less than 750w when the voltage beyond the range from 187V to 242V.	Before renewing the lamp, cleaning or maintaining the cabinet, or if you are not using the cabinet for a long ti me, please pull out the plug.
If the power cord is damaged, do not use it, contact us immediately to change for the new one in the appointe d service point. DO NOT disassemble, maintain or alte r it by yourself.	DO NOT keep liquid food in glass bottles or pots, as fro zen glass may break. DO NOT touch the food and cont ainer in the cabinet with your wet fingers in case your fingers are injured.
Once gas leaks, DO NOT touch the cabinet, shut the g as valve first, then open the window letting the air in. D O NOT insert or pull out the plug of the cabinet.	This appliance can be used by children aged from 8 ye
Children aged from 3 to 8 years are allowed to load an d unload refrigerating appliances.	ars and above and persons with reduced physical, sen sory or mental capabilities or lack of experience and k nowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not p lay with the appliance. Cleaning and user maintenance shall not be made by children without supervision.

Since the flammable insulation blowing gases are use d, please contact the professional agent or our aftersal es service to dispose of the appliance.	Since the flammable refrigerants are used, please inst alled, handle, and service the appliance strictly according to the instruction and contact the professional agent or our aftersales service to dispose of the appliance			
For appliances use flammable refrigerants, the inform ation pertaining to the handling, servicing and disposal of the appliance must be complied with.	If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.			
This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction conce rning use of the appliance by a person responsible for their safety. Children should be supervised to ensure that they do not play with the appliance.				
If the supply cord is damaged, it must be replaced by t he manufacturer, its service agent or similarly qualified persons.	<b>WARNING:</b> When positioning the appliance, ensure the supply cord is not trapped or damaged in order to avoid a hazard.			
WARNING: Do not locate multiple portable socket- ou tlets or portable power supplies at the rear of the appli ance.	<b>WARNING:</b> Keep clear of obstruction all ventilation op enings in the appliance enclosure or in the structure fo r building-in.			
<b>WARNING:</b> Do not use mechanical devices or other means to accelerate the defrosting process, other than those recommended by the manufacturer.	WARNING: Do not damage the refrigerant circuit.			

**WARNING:** Do not use electrical appliances inside the food/ice storage compartments unless they are of the type recommended by the manufacturer.

**WARNING:** In order to reduce flammability hazards the installation of this appliance must only be carried out by a suitably qualified person.

Do not store explosive substances such as aerosol cans with a flammable propellant in this appliance.



The symbol indicate there is risk of fire since flammable materials used.

### **PREPARATION & INSTALLATION**

- Remove all packing, including the foam base and the adhesive tape.
- Uplift the cabinet from bottom when moving it, do not lift or pull the door.
- When moving the cabinet, keep it upright, if it needs inclination, please lift it from both sides and the angle of inclination between the compartment body and the ground should be more than 45°.
- Please move carefully and avoid collision and shocking, in case damaging the appearance or breaking the refrigerating pipes.
- Keep the cabinet away from heat source, in a well-ventilated, dry place, out of sunshine.
- Put the cabinet on a solid and flat surface. If the ground is not level, the leveling legs can be adjusted to keep the cabinet level.
- Keep 100mm space surrounding the cabinet for heat dissipation.
- DO NOT put the cabinet in a wet or splash prone area, if there is splash please clean it with a soft cloth immediately.

#### **OPERATING CAUTION**

Do not put the ice cream in immediately after the freezer being plugged in, please put the ice cream in after the freezer has operated for about 1 hour

#### **TEMPERATURE ADJUSTMENT**

- The inner temperature will affect the temperature of the ice cream and the scooping. If the temperature is too low and it is hard to scoop, the temperature should be adjusted 1-2°C higher by turning the thermostat (eg. from -29°C to -27°C); if the temperature is too high and it is too soft for scooping, the temperature should be adjusted 1-2°C lower (eg. from -27°C to -29°C)
- The temperature displayed is the temperature of the air on the bottom of the cabinet, not the real temperature of the ice cream in the cabinet. The set number in thermostat is the lowest temperature on the bottom of the cabinet, the default temperature is -29°C. It would be best to set the temperature ranging from -27°C to -29°C, if the temperature is too high it would be too soft for scooping, if the temperature is too low but the ambient temperature too high (higher than 38°C), the machine would work all the time.

• Setting of the electronic thermostat: press SET for 1-2 seconds, the set number would flash, then use the to increase and use the to reduce the temperature, finally press SET to confirm the new settings.

#### **DEFROSTING**

The cabinet needs to be defrosted by hand, after a long time of use, it will frost on the interior liner, which will affect the refrigeration and increase the power consumption. So when the ice gets thick, it should be defrosted immediately. DO NOT use sharp or mechanical tools or electric heater to defrost.

Turn off the power and open the door when you defrost. If you want to speed up the defrosting, put a bowl of hot water (50°C) inside the cabinet. Turn on the power after defrosting, then put the food in 1 hour later.

#### CABINET CLEANING

- Always unplug your cabinet before cleaning. Clean the cabinet with a warm wet wipe and some neutral
  detergent, then wipe down with a dry cloth. Do wipe off the greasy dirt on the plastic parts avoid the materials
  aging.
- DO NOT use hot water, harsh chemicals, soap, abrasives, petrol, thinner, alcohol, organic solvents or brushes.
- DO NOT wash machine with water directly in case of destroying the insulation.
- Check and dry the plug and power cords after cleaning the machine.
- Please use dry wipes when cleaning electric parts.
- The machine can be used after cleaning and getting the inside dried.
- Once power cut off, wait for at least 5 minutes before plugging in again to avoid damaging the compressor or the system.

#### **PACKING LIST**

 $\begin{tabular}{ll} \textbf{Model} \ 7292.0005 \ / \ 7292.0010 \ / \ 7292.0015 \ / \ 7292.0020 \\ \textbf{User manual} \ 1x \\ \textbf{Defrosting shovel} \ 1x \\ \end{tabular}$ 

This product will be continuously improved. We reserve the rights of changing the component of the cooler, without further notice, please accept our apologies.

# **TECHNICAL DATA**

Model	Climate	Insulation	Power	Bulk	Rated	Rated	Refrigerant
7292.0005 7292.0010 7292.0015 7292.0020	4/N	1	230V	49	180W	1.3A	R290

These data are tested under standard conditions, if any changes, please refer to the tag, this information may alter without notice. The climatic class of the appliance is 4, it means that it can work in the ambient:

Dry bulb temperature °C	Relative humidity %	Dew point °C	Water vapour mass in d ry air g/kg
30	55	20	14,8

### **DISPOSAL**



Help protect the environment and human health. Put the packaging in applicable containers to recycle it. Help to recycle waste of electrical and electronic appliances. Do not dispose appliances marked with this symbol with the household waste. Return the product to your local recycling facility or contact your municipal office.



#### **Documents / Resources**



CombiSteel 7292 Series Countertop Model Ice Cream Display [pdf] User Manual 7292 Series Countertop Model Ice Cream Display, 7292 Series, Countertop Model Ice Cream Display, Model Ice Cream Display, Display

Manuals+,