

[Skip to content](#)

Manuals+

User Manuals Simplified.



COMMAND ACCESS TECHNOLOGIES MLRK1 Motorized Latch-Retraction Kit Instruction Manual

[Home](#) » [COMMAND ACCESS TECHNOLOGIES](#) »
COMMAND ACCESS TECHNOLOGIES MLRK1
Motorized Latch-Retraction Kit Instruction Manual

Contents [hide](#)

[1 COMMAND ACCESS TECHNOLOGIES MLRK1
Motorized Latch-Retraction Kit](#)

[2 INSERT INSTRUCTIONS](#)

[3 Kit Includes](#)

[4 SPECIFICATIONS](#)

[5 Technical Information](#)

[6 Setting PUSH TO SET \(PTS\)](#)

[7 Troubleshooting & Diagnostics](#)

[8 Installation Instructions](#)

[9 Documents / Resources](#)

[9.1 References](#)

[10 Related Posts](#)



COMMAND ACCESS


COMMAND ACCESS TECHNOLOGIES MLRK1 Motorized Latch-Retraction Kit



INSERT INSTRUCTIONS

The Command Access MLRK1 is a field installable motorized latch-retraction kit for:

MLRK1-MRK8 – Marks M8800 Series



Kit Includes

- A. (1) 60728 – MLRK1-MRK8
- B. (1) 51222 – Connecting Bracket
- C. (1) 51048 – Connecting pin
- D. (3) 40067 – E-CLip
- E. (2) 40064 – M4 x 10mm Phillips Flat Head Screw
- F. (1) 40073 – 6-32 x 1/4 Phillips pan head screw
- G. (1) 51263 – MOTOR KIT spacer
- H. (4) 52084 – PAD SPACER
- I. (1) 50030 – 8' Lead w/ VD Connector
- J. (1) 50944 – MOLEX pigtail

SPECIFICATIONS

- Input Voltage: 24VDC +/- 10%
- AVERAGE low Torque LATCH RETRACTION CURRENT: 900 mA
- Average high torque latch retraction current: 2A
- Average holding current: 215 ma
- Wire gauge: Minimum 18 gauge
- Direct wire run – no relays or access control units in-between power supply & module


Optional built-in rex

- SPDT – Rated .5a @24V
- green= Common (C)
- Blue = normally open (NO)
- grey = normally closed (NC)

Recommended Power Supplies: Use a power limited class 2 power supply

All Command Access exit devices & field installable kits have been thoroughly cycle-tested with Command Access power supplies at our factory. If you plan on using a non-command power supply it must be a filtered & regulated linear power supply.


Technical Information



Setting PUSH TO SET (PTS)

Make sure to set PTS before finishing installation

Step 1- Select your preferred torque mode (ships in standard torque) Press the device push pad to the desired setting. (Recommend to fully depress and release 5%, giving the device room for changing door conditions.)



Step 2- While depressing the push pad, apply power. (i.e. presenting the credential to the reader).


Step 3- Continue to keep pad depressed, the device will beep 6 times. After the beeps have stopped, release the pad and now the adjustment is complete. If not to your liking repeat the 3 steps.

Step 4- Once you found the correct location, turn PTS switch to OFF position.


Troubleshooting & Diagnostics

Beeps	Explanation	Solution
2 Beeps	Over Voltage	> 30V unit will shut down. Check voltage & adjust to 24 V.
3 Beeps	Under Voltage	< 20V unit will shut down. Check voltage & adjust to 24 V.
4 Beeps	Failed Sensor	Verify all 3 sensor wires are installed correctly. Replace sensor if problem persists by contacting office. After 1st fail : 5 beeps then immediately attempts to retract again. After 2nd fail : 5 beeps with pause in-between for 30 seconds then device attempts to retract again. After 3rd fail : 5 beeps every 7 minutes, device will not attempt to retract. To Reset: Depress bar for 5 seconds at any time.
5 Beeps	Retraction or dogging failure	
6 Beeps	PUSH TO SET	Device is recording it's new position and power mode after the 6th beep.

Installation Instructions




1. Slide off push pad assembly from exit device.
2. Remove Dogging Assembly if present & install (G) Spacer over existing holes.




3. Line up Mounting Holes on Motor Kit with screw holes on Spacer/Base Rail.



4. Turn full assembly to the side & install (E) Screws from underneath to secure motor kit to Base Rail.




5. Slide the (B) Connecting Bracket over the Dogging post at the end of the push pad. Next, move Attaching Arms




on motor kit up to line up with holes on B Bracket.




6. Once Attaching Arms are lined up insert (C) PIN to connect to (B) bracket.
7. Install the (D) E-CLIP over the end of the link pin to secure.



8. Swap the existing spacers with the (H) PAD SPACER on both sides of push pad next to rubber bumpers to



- connect to (B) bracket.
9. Re-install the Push Pad Assembly into the exit device housing, keeping an eye on the push pad spacer &



rubber bumpers.



10. Locate the hole on the underside of the device and line up the hole with the tapped hole in the base rail.



11. Locate and install the position set screw (F) Pan Head Screw, to secure push pad assembly to housing.



12. Set the "Push to Set Adjustment" following the steps on page 2.



U.S. Customer Support
1-888-622-2377

Visit our website for more details www.commandaccess.com

Canada Customer Support
1-855-823-3002

Documents / Resources



[COMMAND ACCESS TECHNOLOGIES MLRK1 Motorized Latch-Retracton Kit](#) [pdf] Instruction Manual
MLRK1, MRK8, MLRK1 Motorized Latch-Retracton Kit, MLRK1, Motorized Latch-Retracton Kit, Latch-Retracton Kit



[COMMAND ACCESS TECHNOLOGIES MLRK1 Motorized Latch Retractor Kit](#) [pdf] Instruction Manual
MLRK1 Motorized Latch Retractor Kit, MLRK1, MLRK1 Latch Retractor Kit, Motorized Latch Retractor Kit, Latch Retractor Kit, Motorized Retractor Kit, Retractor Kit

References

- [Command Access Technologies](#)

Manuals+

- [home](#)
- [privacy](#)