



# COMMSCOPE FGS-ACC538 FiberGuide Express Exit Spool Kit Instruction Manual

[Home](#) » [CommScope](#) » COMMSCOPE FGS-ACC538 FiberGuide Express Exit Spool Kit Instruction Manual 

## COMMSCOPE®

FGS-ACC538



**FiberGuide® Express Exit Spool Kit, Yellow**

- FiberGuide products are designed and manufactured to ensure total off-frame fiber cable protection
- FiberGuide maintains a minimum bend radius throughout the entire system, regardless the system size
- FiberGuide is an optical raceway system for central offices, mobile switching center,s and data center applications
- Engineers and installers can benefit from the large suite of available FiberGuide design tools

**Contents**

- [1 Product Classification](#)
- [2 General Specifications](#)
- [3 Dimensions](#)
- [4 Ordering Tree](#)
- [5 Material Specifications](#)
- [6 Packaging and Weights](#)
- [7 Documents / Resources](#)
  - [7.1 References](#)
- [8 Related Posts](#)

**Product Classification**

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Portfolio	CommScope®
Product Type	Fiber raceway accessory
Product Brand	FiberGuide®
Product Series	FGS

**General Specifications**

Product Feature	Round
Color	Yellow
Orientation	Horizontal
Section Type	Accessory

**Dimensions**

Height	108.204 mm   4.26 in
Width	68.58 mm   2.7 in
Length	98.044 mm   3.86 in
System Dimensions	102 mm x 152 mm (4 in x 6 in)

**Ordering Tree**

FGS <sup>9</sup> B - MEXP - <sup>10</sup> A/B/F

#### Section Color

9	empty	yellow
	B	black

#### Section Size

10	A/B/F	4 x 4/6/12 in, with 2 x 2 in exit
	E-A/B/F	4 x 4/6/12 in, with 4 x 4 in exit
	G-A/B/F	4 x 4/6/12 in, with 4 x 6 in exit
	LP-A/B/F	4 x 4/6/12 in, with 2 x 2 in exit, low profile
	LP-CA	4 x 4/6/12 in, with 2 x 4 in exit, low profile
	LP-G	2 x 6 in, with 2 x 2 in exit, low profile
	GS-ABF-NC	4 x 4/6/12 in, with 4 x 6 in exit, no cover
	CV	cover
	NC	no cover

## Material Specifications

Material Type	Engineering Thermoplastic
---------------	---------------------------

## Environmental Specifications

Flammability Rating	CSA S143   UL 2024   UL 94 V-0
Halogen Characteristics	Blue Angel   TCO '99   WEEE
Safety Standard	CSA   UL

## Packaging and Weights

Included	Hardware
Packaging quantity	1
Weight, net	0.113 kg   0.249 lb

## Regulatory Compliance/Certifications


Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant

COMMScope®



©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See [www.commscope.com](http://www.commscope.com) for the most current information. Revised: February 18, 2022

**Documents / Resources**

	<p><b><a href="#">COMMSCOPE FGS-ACC538 FiberGuide Express Exit Spool Kit</a></b> [pdf] Instruction Manual FGS-ACC538, FiberGuide Express Exit Spool Kit, FGS-ACC538 FiberGuide Express Exit Spool Kit, Express Exit Spool Kit, Exit Spool Kit, Spool Kit</p>
-----------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**References**

- [CommScope | now meets next](#)
- [Product Compliance](#)