



Connects2 CAM-24 Universal Surface Mounted Fixed Angle Reverse Camera User Manual

[Home](#) » [Connects2](#) » Connects2 CAM-24 Universal Surface Mounted Fixed Angle Reverse Camera User Manual



CONNECTS



User Manual CAM-24
Universal Camera
Threaded Smooth Surface Mount with Fixed Angle
Wedge Shaped in Black Finish

Contents

1 PRODUCT FEATURES:

2 DISCLAIMER:

3 CONTENTS

4 INSTALLATION

**5 Documents /
Resources**

6 Related Posts

PRODUCT FEATURES:

Image Sensor: 1099 HD CCD
TV Lines: 480
Resolution: 976 x 496
Horizontal Angle: 170 Degrees
Vertical Angle: 120 Degrees
Lumen: 0.1 Lux
TV System: PAL
Video Output: 1.0V p-p 75ohm
Operating Voltage: 12V DC (Negative Ground)
Current Consumption: 145mA @ 13.8V
Waterproof Rating: IP68
Operating Temperature: -20 Degrees C to +70 Degrees C
Parking Lines: Yes
Removable Lines: Yes
Image Adjustment: Yes (Mirror/Normal)
Enhanced Performance In Low Light: Yes

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation.

Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 wants to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support center: support.connects2.com

CONTENTS

Connects2Vision

- Camera with 1m cable to mini Male 6 pin connector
- 1m camera connection cable to mini Female 6 pin connector and RCA Female connector
- 6m Male to Male RCA extension cable
- Instructions

INSTALLATION

1. Connect the Black wire to a suitable ground and the Red wire to a switched +12V supply.
2. If the camera is to be used in the rear of the vehicle, the Red wire should be connected to the reversing light circuit or an interface that provides a reverse signal.

3. Select a suitable location for the camera and ensure that the area is free from all cables, fuel & oil. Whenever possible, avoid locations that are subject to road dirt & water spray.
4. Remove the protective backing from the adhesive pad and place the camera in the required position.
5. Use the nut and bolt attached to the camera if additional support is required.
6. Using the supplied video cable, connect the camera to the display screen and ensure that the image is displayed correctly.
7. To swap the image from mirror to normal view, cut the small White looped wire which is located on the camera connection cable. To remove the parking line feature, cut the small Blue looped wire which is located on the camera connection cable.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2
www.connects2.com

Documents / Resources



[Connects2 CAM-24 Universal Surface Mounted Fixed Angle Reverse Camera](#) [pdf] User Manual
 CAM-24, Universal Surface Mounted Fixed Angle Reverse Camera