

ConnectSelect 2022 Colour Select Festoon String and Transformer Instructions

ConnectSelect

2022 Colour Select Festoon String and Transformer Instructions

Contents

- [1 Warnings](#)
- [2 General](#)
- [3 Installation & storage](#)
- [4 Connect the remote control to a sensor](#)
- [5 How to operate with remot control](#)
- [6 Documents / Resources](#)
- [7 Related Posts](#)

Warnings

In the interest of the safe and proper use of this product, please read these instructions carefully and retain them for future reference.

1. For decorative purposes only. Keep out of reach of children and animals. Risk of electric shock, Strangulation hazard
2. Do NOT submerge this product in water
3. Keep away from sources of heat
4. 3 Pin Starter cable plug is NOT waterproof.
5. Check regularly for signs of wear and tear, discontinue use immediately if damaged. Dispose of accordingly.
6. Individual LED bulbs cannot be replaced.
7. For technical advice consult Festive Light Ltd.
8. If you are installing a large display, we recommend using a weather repellent spray in all connections to reduce the likelihood of electrical trips and to eliminate human error. Q20 is available to purchase from Festive Lights Ltd. Please retain this information for future reference.
9. For any technical information relating to this product, please email Festive Lights Ltd on contact@festive-lights.com. We aim to respond within 2 working days. Alternatively, contact our help line on (01257) 792111. This service is available between 9.00am -5.00pm Monday to Friday.

General

1. This product should only be used in conjunction with our colour select starter cable (MV095B).

2. All products in this range come with weatherproof, 2 pin connectors, which will connect seamlessly with all products within this 240V colour select range.
3. Check your power rating label for maximum LED quantity and power consumption of this product, and do not exceed this maximum number.
4. Products in this 240V range are manufactured to IP65 standards, allowing indoor and outdoor use.
5. Suitable for commercial use, this high quality connectable system uses durable rubber cabling, and innovative bulb sealing technology, meaning these lights are built to withstand changeable weather conditions and prolonged outdoor use.



**Remove the safety cap from product(s)
Before you start**

1. Check the product for any damage or defects before connecting to an electricity supply, check all water seals (rubber o" rings) are in place.
2. Before installation, test all products are working correctly. (Festive Lights Ltd will not cover any costs related to pre/reinstallation).
3. This product **MUST NOT BE MODIFIED**; if any modification is made i.e., cutting / extending lead wires, or using a different power source than supplied, the warranty will be invalidated and may render the product unsafe.
4. Make sure you connect the power supply to a standard 230V socket, do NOT switch on until all connections are secure.
5. Carefully position cables to avoid causing a 'tripping' hazard.

Installation & storage



Connect starter cable to first product / accessory

1. Always plug the power source/starter cable indoors or in a suitable weatherproof socket to ensure a safe connection.
2. Avoid using sharp-edged tools or mounting accessories (e.g., metal wires) to hang or fasten any part of your system.
3. The LED bulbs used are designed for long life and are non-replaceable. Do not attempt to repair or replace them.
4. When not in use, store in a secure dry place away from children and animals. Do not store in direct sunlight.

Please note: The festoon light strings must always be supported using a catenary wire cable.

Connect the remote control to a sensor

If the remote control does not automatically connect to the product or to use one remote to control for multiple sensors:

1. Connect the light strings to the colour select starter cable (MVOS%) and plug in to a power supply.
2. Press and hold the button on the sensor box. When the string lights flash white press any button on the remote (apart from OFF) and release the button on the sensor.
3. Press the RESET button to confirm and pair.
4. Repeat this process to connect the remote control to other sensor.

Please note: The maximum working distance between the sensor and the remote control is 20m. The remote control can be used on an unlimited number of sensors, but must be within the maximum range of 20m.

3



Continue connecting
required lights /
accessories

PRODUCT	Max No. meters/sets that can be powered by the MV095B plug
Fairy Lights	15 x 10m sets
Festoon Lights	30 x 5m sets
Pope Light	30 meters

How to operate with remot control



Secure end screw cap to finish light chain

How to operate with remote control

1. ON and OFF

2. Timer: Press each button once and the LEDs will flash white to indicate the timer has been activated, ON or OFF (TIMER ON, the lights will remain on for 8 hours and off for 16 hours).

3. Colour buttons: For single colour options press the R (Red), G (Green), B (Blue), W (White), Y (Yellow), SB (Sea Blue), P (Purple) or the M (Multi colour) button.

4. +/- Mode: Use these buttons to cycle through flash, chasing and wave functions in all colours.


5. Speed Fast and Slow: These functions work with the flash, chasing and wave options.

6. Jump: This function is RGB colour changing flash LED.

7. Flash Multi: This function will flash between each colour Red, Green, Blue, White, Yellow, Sea Blue, Purple or Multi.



Documents / Resources

	ConnectSelect 2022 Colour Select Festoon String and Transformer [pdf] Instructions 2022 Colour Select Festoon String and Transformer, Select Festoon String and Transformer, Fe stoon String and Transformer, String and Transformer, Transformer
---	---

[Manuals+](#).